

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : METALSTAR SuperEco 14 2877 PANTONE 877
Material number : 028106RC0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Short-term (acute) aquatic hazard, Category 2, H401
Long-term (chronic) aquatic hazard, Category 2, H411

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

GHS-Labelling

Symbol(s)

:



Hazard statements

: H411: Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label**SECTION 3: Composition/information on ingredients**

Substance No.

:

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 20
octadecylamine	124-30-1 204-695-3	;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400	0,25 - 1

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

		Aquatic Chronic;1;H410	
--	--	---------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet, Carbon dioxide (CO₂)**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.

6.2 Environmental precautionsGeneral advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

If the product contaminates rivers and lakes or drains inform
respective authorities.

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : For personal protection see section 8. Smoking, eating and
drinking should be prohibited in the application area.

Advice on protection against : Normal measures for preventive fire protection.
fire and explosion

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Earthing of containers and apparatuses is essential. Reaction
areas and containers with water liberates extremely flammable gas (hydrogen) Take
measures to prevent the build up of electrostatic charge. Use
explosion-proof equipment. Store in original container. Keep
containers tightly closed in a cool, well-ventilated place. Keep
away from sources of ignition - No smoking. Keep container
closed when not in use.

Containers which are opened must be carefully resealed and
kept upright to prevent leakage. Electrical installations /

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2021-07-02	DE TRGS 900

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

Peak-limit: excursion factor (category)	2;(II)
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child

8.2 Exposure controls**Personal protective equipment**

- Eye protection : Goggles
: Safety glasses
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Protective suit
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : No personal respiratory protective equipment normally required.

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

Environmental exposure controls

General advice : The product should not be allowed to enter drains, water courses or the soil.

: Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: > 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm ² /s (40 °C)
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

10.4 Conditions to avoidConditions to avoid : Do not allow evaporation to dryness.
No data available**10.5 Incompatible materials**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****octadecylamine (124-30-1) :**

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**Additional ecological
information: An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal., Toxic to aquatic life with
long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product

: The product should not be allowed to enter drains, water
courses or the soil.

SECTION 14: Transport information**14.1 UN number**

Page 12 / 16

102000037501

A member of  **ALTANA**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

ADR : 3082**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3082**IATA** : 3082**14.2 Proper shipping name**

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(paint related material)

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(,paint related material)

IATA : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(paint related material)

14.3 Transport hazard class**ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

IATA : 9**14.4 Packing group****ADR**

Packaging group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III
Labels : 9
EmS Code : F-A, S-F

IATA

Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packaging group : III
Labels : 9

14.5 Environmental hazards**ADR** : Environmentally hazardous**IMDG** : Marine pollutant

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

14.6 Special precautions for user

For single packagings ≤ 5L / 5 kg, or combination packagings containing inner packagings ≤ 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (aluminium powder (stabilised))

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALSTAR SuperEco 14 2877 PANTONE 877

Version 1.0

Revision Date 22.04.2024

Print Date 02.12.2024

SECTION 16: Other information**Full text of H-Statements**

H228	: Flammable solid.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H401	: Toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.