

Date of impression 06.12.2024/18:14:55

page/of 1

edition 09.01.2024

material denomination

STAPA IL HYDROLAN 161 55900/G Aluminium Paste

material-no.

005300HV0

material description

Pigmentpaste of flaky aluminiumpowder produced of pure aluminium min. 99,5 % EN 576, with an inorganic coating

Specific gravity app. 1,4 kg/l

The solvent contained is isopropanol (IL) including lubricant and

material specification

insp. characteristic	specification	unit
Tl00004 pigment content / non volatile	58,0 - 62,0	%
Tl00004 volatile content	38,0 - 42,0	%
TI00005 sieving < 63 µm	99,9 - 100,0	%
TI00033 aqueous paint spray-out	pass	
TI00489 D 10	10,0 - 14,0	μm
TI00489 D 50	25,0 - 31,0	μm
TI00489 D 90	46,0 - 54,0	μm

total shelf life in month: 24

EC-safety data sheet-no. 005300HV0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.

The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

DraftApprovalReleaseTechnical servicesProductionQuality control09.01.202409.01.202409.01.2024

This document has been printed automatically and will not be signed.