according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier				
Trade name	: STANDART PCU 2000 Aluminium Powder			
Product code	: 041242D60			
1.2 Relevant identified uses of the substance or mixture and uses advised against				

Use of the Substance/Mixture	:	Colouring agents, pigments
---------------------------------	---	----------------------------

#### 1.3 Details of the supplier of the safety data sheet

Company	:	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	:	+499152770
Telefax	:	+499152777008
E-mail address of person responsible for the SDS	:	msds.eckart@altana.com

#### **1.4 Emergency telephone number**

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)Flammable solids, Category 1H228: Flammable solid.

Information concerning particular hazards for human and environment: Please refer to our website for further important safety instructions for handling aluminium powder:

http://www.eckart.net/fileadmin/eckart/Service/GDA\_Alupulver\_Safety\_engl.pdf

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024	SDS Number: 102000000314	Print Date: 02.12.2024 Date of first issue: 03.01.2014
Hazard pictograms			
Signa	al word	: Danger	
Haza	rd statements	: H228	Flammable solid.
Preca	autionary statements	Prevention P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P240	Ground and bond container and receiving equipment.
		P241	Use explosion-proof electrical/ventilating/ lighting equipment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
		<b>Response:</b> P370 + P37	
		P370 + P37	•

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

#### **SECTION 4: First aid measures**

4.1 Description of first aid measur	res	
General advice	:	Move the victim to fresh air.
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
		If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed** None known.

4.3 Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	ABC powder Carbon dioxide (CO2) Water Foam

5.2 Special hazards arising from the substance or mixture				
Specific hazards during	:	Contact with water liberates extremely flammable gas		
firefighting		(hydrogen).		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024	SDS Number: 102000000314		Print Date: 02.12.2024 Date of first issue: 03.01.2014
Specia for fire	<b>for firefighters</b> al protective equipment fighters r information		necessary. For safety reason separately in clos Use extinguishing	ned breathing apparatus for firefighting if is in case of fire, cans should be stored ed containments. I measures that are appropriate to local d the surrounding environment.
			Use a water sprag	y to cool fully closed containers.

#### **SECTION 6:** Accidental release measures

Personal precautions :	e equipment and emergency procedures Use personal protective equipment. Evacuate personnel to safe areas. Avoid dust formation. Remove all sources of ignition.
6.2 Environmental precautions	
General advice :	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contai	nment and cleaning up
	Use mechanical handling equipment. Do not use a vacuum cleaner.
	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	: Avoid creating dust.
	Routine housekeeping should be instituted to ensure that
	dusts do not accumulate on surfaces.
	Store away from heat.
	,

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Vers 4.0	sion	Revision Date: 26.06.2024	-	DS Number: 2000000314	Print Date: 02.12.2024 Date of first issue: 03.01.2014	
Advice on protection against fire and explosion		:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area. Open drum carefully as content may be under pressur Dispose of rinse water in accordance with local and na regulations. Use explosion-proof equipment. During processing, d form explosive mixture in air. Take measures to preve build up of electrostatic charge. When transferring from container to another apply earthing measures and use conductive hose material.			
					ate exhaust ventilation at places where dust away from open flames, hot surfaces and n.	
	Hygier	ne measures	:	Wash hands before breaks and at the end of workday.		
7.2	Conditi	ons for safe storage,	inc	luding any incom	patibilities	
	Requirements for storage areas and containers		:	: Earthing of containers and apparatuses is essential. Re with water liberates extremely flammable gas (hydrogen explosion-proof equipment. Store in original container. containers tightly closed in a cool, well-ventilated place away from sources of ignition - No smoking. Keep conta closed when not in use.		
				ventilated place.	p container tightly closed in a dry and well- Electrical installations / working materials the technological safety standards.	
		r information on e conditions	:	Protect from hum	idity and water.	
	Advice	e on common storage	:	Never allow prod storage. Keep away from	ether with oxidizing and self-igniting products. uct to get in contact with water during oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.	
		r information on e stability	:	Keep in a dry plac No decompositio	ce. n if stored and applied as directed.	
7.3	Specifi	c end use(s)				

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Da 26.06.2024			int Date: 02.12.2024 ate of first issue: 03.01.2014	
alumii (stabi	nium powder lised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
	·		TWA (Respirable fraction)	4 mg/m3	GB EH40
			TWA (inhalable dust)	10 mg/m3	GB EH40
		inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions and contain comp should be cor	t are those fractions of is undertaken in a eneral methods for pracic and inhalable zardous to health ind in air equal to or great t or 4 mg.m-3 8-hou be subject to COSHI dusts have been as with the appropriate wide range of sizes. ticle after entry into t it elicits, depend or two size fractions for e'., Inhalable dust appropriate enters the nose and deposition in the responsation of the penetrates to t d explanatory matering onents that have the mplied with., Where times the long-term	beses of these limits, respirable of airborne dust which will be accordance with the methods sampling and gravimetric and aerosols., The COSHH defi- cludes dust of any kind when eater than 10 mg.m-3 8-hour r TWA of respirable dust. This if people are exposed to designed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition as the human respiratory system the nature and size of the por limit-setting purposes term oproximates to the fraction of mouth during breathing and biratory tract. Respirable dust he gas exchange region of the al are given in MDHS14/4., are own assigned WEL, all the no specific short-term expose exposure limit should be us	e collected described in alysis or nition of a present at a TWA of s means that ust above these contain and fate of any n, and the body article. HSE ed 'inhalable' f airborne is therefore at approximates he lung. Fuller Where dusts e relevant limits sure limit is listed, ed.
			TWA (Respirable dust)	4 mg/m3	GB EH40
		inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for c	t are those fractions of is undertaken in a eneral methods for pracic and inhalable zardous to health ind in air equal to or great tor 4 mg.m-3 8-hou be subject to COSHI dusts have been as with the appropriate wide range of sizes. ticle after entry into the it elicits, depend or two size fractions for e'., Inhalable dust a enters the nose and deposition in the resp	oses of these limits, respirable of airborne dust which will b accordance with the methods sampling and gravimetric and aerosols., The COSHH defi- cludes dust of any kind when eater than 10 mg.m-3 8-hour r TWA of respirable dust. This d if people are exposed to d signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the p or limit-setting purposes term oproximates to the fraction o mouth during breathing and biratory tract. Respirable dus he gas exchange region of the	e collected described in alysis or nition of a present at a TWA of s means that ust above these contain and fate of any n, and the body article. HSE ed 'inhalable' f airborne is therefore at approximates

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# STANDART PCU 2000 Aluminium Powder

ersion Revision I 0 26.06.2024	
	definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed a figure three times the long-term exposure limit should be used.
silicon dioxide	7631-86-9 TWA (inhalable 6 mg/m3 GB EH40 (silica)
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed a figure three times the long-term exposure limit should be used.
	TWA (Respirable2.4 mg/m3GB EH40dust)(Silica)
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health	Value
			effects	Value
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3
3-trimethoxysilylpropyl methacrylate	Workers	Inhalation	Long-term systemic effects	130 mg/m3
	Workers	Inhalation	Long-term local effects	0.6 mg/m3
	Workers	Dermal	Long-term systemic effects	0.14 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.18 mg/m3
	Consumers	Inhalation	Long-term local effects	0.1 mg/m3
	Consumers	Inhalation	Acute systemic effects	26400 mg/m3
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg
	Consumers	Dermal	Long-term systemic effects	0.14 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

#### 8.2 Exposure controls

#### Personal protective equipment Eye/face protection Face-shield : Tightly fitting safety goggles Hand protection Material : Leather Glove length : Long sleeve gloves Leather gloves The choice of an appropriate glove does not Remarks : only depend on its material but also on other quality features and is different from one producer to the other. The suitability for a specific workplace should be discussed

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024	SDS Number: 102000000314	Print Date: 02.12.2024 Date of first issue: 03.01.2014
Skin a	and body protection	: Anti-static and fir	rs of the protective gloves. re resistant protective clothing. DIN EN EN 1149-1. Anti-static safety shoes. protective suit
Respi	ratory protection	Choose body pro	btection according to the amount and the dangerous substance at the work place. athing protection if workplace concentration

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Form	:	powder
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	> 600 °C
Boiling point/boiling range	:	No data available
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	30 g/m3
Flash point	:	No data available
Auto-ignition temperature	:	340 °C
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024		S Number: 2000000314	Print Date: 02.12.2024 Date of first issue: 03.01.2014
octan	ion coefficient: n- ol/water ur pressure	:	No data available No data available	
	ve density	:	No data available	2
Densi Relati	ity ve vapour density	:	2.5 g/cm3 No data available	9
Partic	le characteristics article Size Distribution	:	No data available	9
9.2 Other	information			

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

#### 10.4 Conditions to avoid

```
Conditions to avoid : Heat, flames and sparks.
```

#### 10.5 Incompatible materials

Materials to avoid

: Acids Bases Oxidizing agents Water

#### 10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

:

#### Acute toxicity

Not classified based on available information.

#### **Components:**

#### aluminium powder (stabilised):

Acute inhalation toxicity

LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Further information**

Product:

Remarks

No data available

:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### **12.2 Persistence and degradability** No data available

# 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

#### Product:

Additional ecological	:	No data available
information		

:

#### **SECTION 13: Disposal considerations**

European Waste Catalogue European Waste Catalogue	:	
<b>13.1 Waste treatment methods</b> Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024	-	OS Number: 2000000314		Print Date: 02.12.2024 Date of first issue: 03.01.2014
			Do not burn,	or u	se a cutting torch on, the empty drum.
SECTIO	N 14: Transport infor	ma	tion		
14.1 UN r	number or ID number				
ADR		:	UN 1309		
IMDO	6	:	UN 1309		
ΙΑΤΑ		:	UN 1309		
14.2 UN p	proper shipping name				
ADR		:	ALUMINIUM	PO	WDER, COATED
IMDO	3	:	ALUMINIUM	PO	WDER, COATED
ΙΑΤΑ		:	Aluminium p	owd	er, coated
14.3 Tran	sport hazard class(es)				
			Class		Subsidiary risks
ADR		:	4.1		
IMDO	6	:	4.1		
ΙΑΤΑ		:	4.1		
14.4 Pack	king group				
ADR					
Pack Class Haza Labe	ing group sification Code rd Identification Number Is el restriction code		II F3 40 4.1 (E)		
IMDO		•	(⊏)		
Labe	Code	: : :	ll 4.1 F-G, S-G IMDG Code	segr	egation group 15 - Powdered metals
Pack aircra		:	448		
	ing instruction (LQ) ing group Is	:	Y441 II 4.1		
Pack	( <b>Passenger)</b> ing instruction senger aircraft)	:	445		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version 4.0	Revision Date: 26.06.2024	SDS Number: 102000000314	Print Date: 02.12.2024 Date of first issue: 03.01.2014
Packir Labels	ng instruction (LQ) ng group s onmental hazards	: Y441 : II : 4.1	
<b>ADR</b> Enviro	nmentally hazardous	: no	
IMDG Marine	e pollutant	: no	

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	aluminium powder (stabilised)
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		
This product is regulated by Regulation (EU) 2019/1148:	all	aluminium powder (stabilise

This product is regulated by Regulation (EU) 2019/1148: all aluminium powder (stabilised) suspicious transactions, and significant disappearances and thefts (ANNEX II) should be reported to the relevant national contact point.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	10200000314	Date of first issue: 03.01.2014

#### 15.2 Chemical safety assessment

No data available

#### **SECTION 16: Other information**

#### Full text of H-Statements

H228

Flammable solid.

#### Full text of other abbreviations

Flam. Sol.	:	Flammable solids
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture:

**Classification procedure:** 

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### STANDART PCU 2000 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
4.0	26.06.2024	102000000314	Date of first issue: 03.01.2014
Flam.	Sol. 1	H228	Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN