

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

SECTION 1. IDENTIFICATION

Product name : PLATINSTAR G2 FX-1965 SILVER
Product code : 046107CLO

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation
Address : 830 East Erie Street
Painesville OH 44077
Telephone : 866-458-7837
(440) 954-7600
Telefax : (440) 354-6224
e-mail adresse : info.eckart.america.oh@altana.com
Emergency telephone : **CHEMTREC:** 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC)
US: +1 866 928 0789 (Toll free)
Canada: +1 800 579 7421 (Toll Free)
Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Precautionary Statements

:

Prevention:

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal:

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous ingredients which must be listed on the label:

Acetic acid ethyl ester
2-Propanol, 1-methoxy-
2-Propanol

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

1-Propanol

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Acetic acid ethyl ester	141-78-6	$\geq 20 - < 30$
2-Propanol, 1-methoxy-	107-98-2	$\geq 20 - < 30$
2-Propanol	67-63-0	$\geq 10 - < 20$
Ethanol	64-17-5	$\geq 10 - < 20$
Aluminum	7429-90-5	$\geq 10 - < 20$
1-Propanol	71-23-8	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Take the victim into fresh air. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: Wash off immediately with soap and plenty of water. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation. May cause drowsiness or dizziness.

SECTION 5. FIRE-FIGHTING MEASURES

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Suitable extinguishing media	:	Dry sand ABC powder Foam
Unsuitable extinguishing media	:	High volume water jet Carbon dioxide (CO ₂)
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Environmental precautions	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Do not flush with water.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Earthing of containers and apparatuses is essential.
Reaction with water liberates extremely flammable gas (hydrogen)
Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep away from sources of ignition - No smoking.
Keep container closed when not in use.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.
- Technical measures/Precautions : Protect from humidity and water.
- Materials to avoid : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetic acid ethyl ester	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m ³	NIOSH REL
		TWA	400 ppm 1,400 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,400 mg/m ³	OSHA P0
2-Propanol, 1-methoxy-	107-98-2	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		ST	150 ppm 540 mg/m ³	NIOSH REL
		TWA	100 ppm 360 mg/m ³	NIOSH REL
		TWA	100 ppm 360 mg/m ³	OSHA P0
		STEL	150 ppm 540 mg/m ³	OSHA P0
2-Propanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0

PLATINSTAR G2 FX-1965 SILVER

Version 4.3 Revision Date: 04/01/2025 SDS Number: 102000032926 Date of last issue: 09/04/2024
 Date of first issue: 05/18/2020

Ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (welding)	5 mg/m3 (Aluminum)	NIOSH REL

PLATINSTAR G2 FX-1965 SILVER

Version 4.3 Revision Date: 04/01/2025 SDS Number: 102000032926 Date of last issue: 09/04/2024
 Date of first issue: 05/18/2020

		fumes)		
		TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
		TWA (Fumes)	5 mg/m3	OSHA P0
		TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0
1-Propanol	71-23-8	TWA	100 ppm	ACGIH
		TWA	200 ppm 500 mg/m3	NIOSH REL
		ST	250 ppm 625 mg/m3	NIOSH REL
		TWA	200 ppm 500 mg/m3	OSHA Z-1
		STEL	250 ppm 625 mg/m3	OSHA P0
		TWA	200 ppm 500 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 In the case of vapor formation use a respirator with an approved filter.

Hand protection
 Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection	:	Goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	silver
Odor	:	solvent
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	Not applicable
Boiling point/boiling range	:	77 °C
Flash point	:	-4 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	0.85 - 1 g/cm3
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-	:	No data available

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

octanol/water
Autoignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Total Volatile organic
compounds (VOC) content : 80.00 - 90.00 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : Contact with acids and alkalis may release hydrogen.
Stable under recommended storage conditions.
Vapors may form explosive mixture with air.

Conditions to avoid : Do not allow evaporation to dryness.
Heat, flames and sparks.

Incompatible materials : Acids
Bases
Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**Acetic acid ethyl ester:**

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

2-Propanol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Ethanol:

Acute oral toxicity : LD50 (Rat, male and female): 10,470 mg/kg
Method: OECD Test Guideline 401

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Acute inhalation toxicity : LC50 (Rat, male and female): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Skin corrosion/irritation

Not classified based on available information.

Components:**Ethanol:**

Result: No skin irritation

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Acetic acid ethyl ester:**

Result: Eye irritation

2-Propanol:

Result: Eye irritation

Ethanol:

Result: Eye irritation

Remarks: Based on available data, the classification criteria are not met.

1-Propanol:

Result: Irreversible effects on the eye

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Carcinogenicity

Not classified based on available information.

IARC

Group 1: Carcinogenic to humans

Ethanol

64-17-5

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Acetic acid ethyl ester:**

Assessment: May cause drowsiness or dizziness.

2-Propanol, 1-methoxy-:

Assessment: May cause drowsiness or dizziness.

2-Propanol:

Assessment: May cause drowsiness or dizziness.

1-Propanol:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Further information

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Acetic acid ethyl ester:**

Toxicity to daphnia and other : (Daphnia): 717 mg/l
aquatic invertebrates

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION**Domestic regulation****49 CFR**

UN/ID/NA number	:	UN 1210
Proper shipping name	:	Printing ink
Class	:	3
Packing group	:	II
Labels	:	FLAMMABLE LIQUID
ERG Code	:	129
Marine pollutant	:	no

International Regulations

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

IATA-DGR

UN/ID No.	: UN 1210
Proper shipping name	: Printing ink
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG-Code

UN number	: UN 1210
Proper shipping name	: PRINTING INK
Class	: 3
Packing group	: II
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
Acetic acid ethyl ester	141-78-6	5000
Phosphoric acid	7664-38-2	5000
Phosphoric acid	7664-38-2	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)
-----------------------------	---

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Propanol	67-63-0	>= 10 - < 20 %
Aluminum	7429-90-5	>= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Acetic acid ethyl ester	141-78-6	>= 20 - < 30 %
2-Propanol, 1-methoxy-	107-98-2	>= 20 - < 30 %
2-Propanol	67-63-0	>= 20 - < 30 %
Ethanol	64-17-5	>= 10 - < 20 %
1-Propanol	71-23-8	>= 1 - < 5 %
Acetic acid, propyl ester	109-60-4	>= 0.1 - < 1 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Phosphoric acid	7664-38-2	%
Phosphoric acid	7664-38-2	%

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Phosphoric acid	7664-38-2	%
Phosphoric acid	7664-38-2	%

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307
This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations**Massachusetts Right To Know**

PLATINSTAR G2 FX-1965 SILVER

Version 4.3	Revision Date: 04/01/2025	SDS Number: 102000032926	Date of last issue: 09/04/2024 Date of first issue: 05/18/2020
----------------	------------------------------	-----------------------------	---

Acetic acid ethyl ester	141-78-6
2-Propanol, 1-methoxy-	107-98-2
2-Propanol	67-63-0
Ethanol	64-17-5
Aluminum	7429-90-5
1-Propanol	71-23-8

Pennsylvania Right To Know

Acetic acid ethyl ester	141-78-6
2-Propanol, 1-methoxy-	107-98-2
2-Propanol	67-63-0
Ethanol	64-17-5
Aluminum	7429-90-5
1-Propanol	71-23-8

California Prop. 65

WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



WARNING: This product can expose you to chemicals including Ethanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Acetic acid ethyl ester	141-78-6
2-Propanol, 1-methoxy-	107-98-2
2-Propanol	67-63-0
Ethanol	64-17-5

PLATINSTAR G2 FX-1965 SILVER

Version 4.3	Revision Date: 04/01/2025	SDS Number: 102000032926	Date of last issue: 09/04/2024 Date of first issue: 05/18/2020
----------------	------------------------------	-----------------------------	---

Aluminum	7429-90-5
----------	-----------

1-Propanol	71-23-8
------------	---------

California Permissible Exposure Limits for Chemical Contaminants

Acetic acid ethyl ester	141-78-6
-------------------------	----------

2-Propanol, 1-methoxy-	107-98-2
------------------------	----------

2-Propanol	67-63-0
------------	---------

Ethanol	64-17-5
---------	---------

Aluminum	7429-90-5
----------	-----------

1-Propanol	71-23-8
------------	---------

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the Canadian NDSL.

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3

PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / STEL : Short-term exposure limit

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/01/2025

SAFETY DATA SHEET



PLATINSTAR G2 FX-1965 SILVER

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2024
4.3	04/01/2025	102000032926	Date of first issue: 05/18/2020

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8