

METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

SECTION 1. IDENTIFICATION

Product name : METALSTAR EB 21-3056 GOLD

Product code : 046799DP0

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation

Address : 830 East Erie Street

Painesville OH 44077

Telephone : 866-458-7837

(440) 954-7600

Telefax : (440) 354-6224

e-mail adresse : info.eckart.america.oh@altana.com

Emergency telephone : CHEMTREC: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

H351 Suspected of causing cancer.

Precautionary Statements

_					
$\mathbf{\nu}$	ra	/en	111	nn.	•
	16	<i>,</i> – 1	ıu.	UII.	

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be

allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/

eve protection/ face protection.

Response:

P308 + P313

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse

mouth

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/

... ...

attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label:

Copper

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

Polyester acrylate

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Copper	7440-50-8	>= 30 - < 50
2-Propenoic acid, 1,1'-[2-[[2,2-bis[[(1-oxo-2-	94108-97-1	>= 30 - < 50
propen-1-yl)oxy]methyl]butoxy]methyl]-2-		
ethyl-1,3-propanediyl] ester		
Poly(oxy-1,2-ethanediyl), .alphahydro-	28961-43-5	>= 10 - < 20
.omega[(1-oxo-2-propen-1-yl)oxy]-, ether		
with 2-ethyl-2-(hydroxymethyl)-1,3-		
propanediol (3:1)	50400.04.4	
Poly[oxy(methyl-1,2-	52408-84-1	>= 1 - < 5
ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-		
propanetriyltris[.omega[(1-oxo-2-propen-1-		
yl)oxy]-	7440 66 6) 1 1 E
Zinc	7440-66-6	>= 1 - < 5
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-	55818-57-0	>= 1 - < 5
propenoate		
Polyester acrylate	Not Assigned	>= 1 - < 5
2,5-Cyclohexadien-1-one, 2,6-bis(1,1-	7078-98-0	>= 0.1 - < 1
dimethylethyl)-4-(phenylmethylene)-	1010 30 0	>= 0.1 < 1
2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-	15625-89-5	>= 0.1 - < 1
propen-1-yl)oxy]methyl]-1,3-propanediyl]	10020-03-0) - 0.1 - \ 1
lester		
00.01		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Take the victim into fresh air.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

If inhaled : Remove to fresh air.

If unconscious, place in recovery position and seek medical



METALSTAR EB 21-3056 GOLD

Version Revision Date: SDS Number: Date of last issue: 09/17/2024 2.4 09/24/2024 102000026860 Date of first issue: 03/26/2018

advice.

If symptoms persist, call a physician.

In case of skin contact Wash off immediately with soap and plenty of water.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

Harmful if swallowed.

May cause an allergic skin reaction.

delayed

Causes serious eye irritation. Suspected of causing cancer.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Special powder against metal fire

> Dry sand ABC powder

Unsuitable extinguishing

media

Water

High volume water jet

Specific hazards during fire

fighting

Carbon dioxide (CO2)

courses.

Further information Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

Do not allow run-off from fire fighting to enter drains or water

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment.

General advice The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Use mechanical handling equipment.

Pick up and transfer to properly labeled containers.

Do not flush with water.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Keep away from heat and sources of ignition.

No smoking.

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep

Keep away from sources of ignition - No smoking.

Do not store near combustible materials.



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Technical

measures/Precautions

Materials to avoid

Protect from humidity and water.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Further information on storage stability

: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Copper	7440-50-8	TWA	1 mg/m3 (Copper)	ACGIH
		TWA (dust and mists)	1 mg/m3 (Copper)	NIOSH REL
		TWA	1 mg/m3 (Copper)	OSHA P0
		TWA	0.2 mg/m3 (Copper)	ACGIH
		TWA	0.1 mg/m3 (Copper)	OSHA P0
		TWA (Dust and mist)	1 mg/m3 (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m3 (Copper)	ACGIH
		TWA (Dust)	1 mg/m3 (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m3 (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m3 (Copper)	OSHA Z-1
		TWA	0.1 mg/m3	OSHA Z-1



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

		(Fumes)	(Copper)	
		TWA	0.1 mg/m3	OSHA P0
		(Fumes)	(Copper)	
		TWA (Dust	1 mg/m3	OSHA P0
		and mist)	(Copper)	
Zinc	7440-66-6	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester	15625-89-5	TWA	1 mg/m3	US WEEL

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Equipment should conform to EN 14387

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Eye protection : Safety glasses



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid Color : gold

Odor : characteristic
Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/range : Not applicable Boiling point/boiling range : > 100 °C

Flash point : > 100 °C

Evaporation rate : No data available Flammability (solid, gas) : No data available Upper explosion limit / Upper : No data available

flammability limit

Lower explosion limit / Lower

flammability limit

Vapor pressure : No data available Relative density : No data available Density : 1.4 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous : Stable under recommended storage conditions.

Ro decomposition if stored and applied as directed.

No decomposition if stored and applied as directed.

No data available



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

Conditions to avoid : Do not allow evaporation to dryness.

No data available

Hazardous decomposition products

Thermal decomposition : Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Components:

Copper:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Zinc:

Acute oral toxicity : (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Components:

Copper:

Remarks: May cause skin irritation in susceptible persons.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Copper:

Result: Eye irritation



METALSTAR EB 21-3056 GOLD

Version Revision Date: SDS Number: D2.4 09/24/2024 102000026860

Date of last issue: 09/17/2024 Date of first issue: 03/26/2018

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: Irritating to eyes.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: Eye irritation

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: May cause sensitization by skin contact.

Remarks: Causes sensitization.

May cause sensitization of susceptible persons by skin contact.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: May cause sensitization by skin contact.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

Result: May cause sensitization by skin contact.

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-:

Result: May cause sensitization by skin contact.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: May cause sensitization by skin contact.



METALSTAR EB 21-3056 GOLD

Version Re

Revision Date: 09/24/2024

SDS Number: 102000026860

Date of last issue: 09/17/2024 Date of first issue: 03/26/2018

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Components:

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Carcinogenicity -

Assessment

IARC

: Limited evidence of carcinogenicity in animal studies

Group 2B: Possibly carcinogenic to humans

2-Propenoic acid, 1,1'-[2- 15625-89-5

ethyl-2-[[(1-oxo-2-propen-1-

yl)oxy]methyl]-1,3propanediyl] ester

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Components:

Copper:

Remarks: No data available

Zinc:

Remarks: No data available



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Copper:

M-Factor (Acute aquatic

toxicity)

M-Factor (Chronic aquatic

toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Zinc:

M-Factor (Acute aquatic

toxicity)

M-Factor (Chronic aquatic

toxicity)

1

: 1

: 10

: 10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.



METALSTAR EB 21-3056 GOLD

Version Revision Date: 2.4 09/24/2024

SDS Number: 102000026860

Date of last issue: 09/17/2024 Date of first issue: 03/26/2018

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:

Copper:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-

oxo-2-propen-1-yl)oxy]-:

Additional ecological

information

: No data available

Zinc:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR

Not regulated as a dangerous good



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Copper metal powder)

Class : 9 Packing group : III

Labels : Miscellaneous Dangerous Goods

964

Packing instruction (cargo

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Copper metal powder)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Remarks : For single packagings <=5L / 5 kg, or combination

packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197

IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)
Copper	7440-50-8	5000
Zinc	7440-66-6	1000
Cyclohexane	110-82-7	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Respiratory or skin sensitization Serious eye damage or eye irritation

Carcinogenicity

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Copper 7440-50-8 >= 30 - < 50 %

Zinc 7440-66-6 >= 1 - < 5 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Copper 7440-50-8 33.915 %

Zinc 7440-66-6 3.42 %

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Copper 7440-50-8 33.915 %

Zinc 7440-66-6 3.42 %

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table

116.4A:

Cyclohexane 110-82-7 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table

117.3:

Cyclohexane 110-82-7 %

US State Regulations

Massachusetts Right To Know



52408-84-1

METALSTAR EB 21-3056 GOLD

Version 2.4

Revision Date: 09/24/2024

SDS Number: 102000026860

Date of last issue: 09/17/2024 Date of first issue: 03/26/2018

Copper 7440-50-8

Zinc 7440-66-6

Pennsylvania Right To Know

Copper 7440-50-8

2-Propenoic acid, 1,1'-[2-[[2,2-bis[[(1-oxo-2-propen-1-94108-97-1

 $yl) oxy] methyl] butoxy] methyl] -2-ethyl -1, 3-propanediyl] \ ester$

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- 28961-43-5

propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

Kein gefährlicher Stoff oder gefährliches Gemisch gemäß dem Not Assigned

Global Harmonisierten System (GHS).

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-vl)oxy]-

Zinc 7440-66-6

Aluminum 7429-90-5

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



WARNING: This product can expose you to chemicals including 2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Copper 7440-50-8

Zinc 7440-66-6

California Permissible Exposure Limits for Chemical Contaminants

Copper 7440-50-8

Zinc 7440-66-6

The ingredients of this product are reported in the following inventories:



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

DSL : This product contains one or several components that are not

on the Canadian DSL nor NDSL.

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

TSCA list

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Zinc 7440-66-6

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -



METALSTAR EB 21-3056 GOLD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/17/2024

 2.4
 09/24/2024
 102000026860
 Date of first issue: 03/26/2018

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/24/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8