

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

SECTION 1. IDENTIFICATION

Product name Product code	:	STANDART PCS 3500 Aluminium Powder 040626EV0
Manufacturer or supplier's of	deta	ils
Company name of supplier	:	ECKART America Corporation
Address	:	830 East Erie Street
		Painesville OH 44077
Telephone	:	866-458-7837
		(440) 954-7600
Telefax	:	(440) 354-6224
e-mail adresse	:	info.eckart.america.oh@altana.com
Emergency telephone	:	CHEMTREC: 800-424-9300
		CHEMTREC: 1-703-527-3387 (International)
		NCEC:
		(contract no. ECKART29003-NCEC)
		US: +1 866 928 0789 (Toll free)
		Canada: +1 800 579 7421 (Toll Free)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Mexico: +52 55 5004 8763

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

None known.

Information concerning particular hazards for human and environment:

Please refer to our website for further important safety instructions for handling aluminium powder: http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 90 - <= 100
Silica	7631-86-9	>= 5 - < 10





Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Take the victim into fresh air. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical
		advice.
		lf symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
In case of eye contact	:	Remove contact lenses.
		If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear.
		Do not give milk or alcoholic beverages.
		Never give anything by mouth to an unconscious person.
		If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delaved	:	None known.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Unsuitable extinguishing media	:	Dry sand Special powder against metal fire ABC powder Carbon dioxide (CO2) Water Foam
Specific hazards during fire fighting	:	Contact with water liberates extremely flammable gas (hydrogen).
Further information	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Evacuate personnel to safe areas. Avoid dust formation.
General advice	:	The product should not be allowed to enter drains, water courses or the soil. No special environmental precautions required.

SAFETY DATA SHEET



STANDART PCS 3500 Aluminium Powder

Versio 1.0	on	Revision Date: 02/03/2025	-	0S Number: 2000038401	Date of last issue: - Date of first issue: 02/03/2025
E	Environ	mental precautions	:	The product shou courses or the so	ld not be allowed to enter drains, water I.
				No special enviror	nmental precautions required.
		s and materials for ment and cleaning up	:	Use mechanical h Do not use a vacu	andling equipment. ium cleaner.
				Sweep up and sh	ge disposal without creating dust. ovel. closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	During processing, dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge. Earthing of containers and apparatuses is essential. Use explosion-proof equipment. When transferring from one container to another apply earthing measures and use conductive hose material.
	Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling :	Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Keep away from heat and sources of ignition. Do not smoke. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Conditions for safe storage :	Reaction with water liberates extremely flammable gas (hydrogen) Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking. Electrical installations / working materials must comply with the technological safety standards.
Technical : measures/Precautions	Protect from humidity and water.
Materials to avoid :	Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and





ersion Revision Date: 0 02/03/2025				SDS Number: 102000038401	Date of last issue : - Date of first issue : 02/03/2025		
		strongly acid	d materials in ord	er to avoid exothermic	reactions.		
		No materials	to be especially	mentioned.			
	er information on ge stability	: Keep in a dr	y place.				
CTION	8. EXPOSURE CON	TROLS/PERSONAL	PROTECTION				
	edients with workplac	-					
Comp	ponents	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Alum	inum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-		
			TWA (Respirable)	5 mg/m3	NIOSH R		
			TWA (total dust)	15 mg/m3	OSHA Z-		
			TWA (total)	10 mg/m3	NIOSH R		
			TWA (respirable fraction)	5 mg/m3	OSHA Z-		
			TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-		
			TWA (Respirable particulate matter)	1 mg/m3	ACGIH		
			TWA	5 mg/m3 (Aluminum)	NIOSH R		
			TWA (Total)	15 mg/m3 (Aluminum)	OSHA P		
			TWA (Respirable	5 mg/m3 (Aluminum)	OSHA P		

A member of **C ALTANA**

OSHA Z-1

OSHA Z-1

OSHA P0

fraction) TWA (total dust)

(respirable fraction) TWA (Total

TWA

dust)

15 mg/m3 (Aluminum)

5 mg/m3 (Aluminum)

15 mg/m3

(Aluminum)



Version Revision Date: 1.0 02/03/2025		SDS Number: 102000038401	Date of las Date of firs	t issue: - st issue: 02/03/2025	
			TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA PO
			TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
			TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
			TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
			TWA (Fumes)	5 mg/m3	OSHA P0
			TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0

		(powder)	(Aluminum)	
Silica	7631-86-9	TWA (Dust)	20 Million	OSHA Z-3
			particles per cubic	
			foot	
			(Silica)	
		TWA (Dust)	80 mg/m3	OSHA Z-3
			/ %SiO2	
			(Silica)	
		TWA	6 mg/m3	NIOSH REL
			(Silica)	

Personal protective equipme	ent	
Respiratory protection		Use suitable breathing protection if workplace concentration requires. Breathing apparatus with filter. P1 filter No personal respiratory protective equipment normally required.
Hand protection		
Material	:	Leather
Glove length	:	Long sleeve gloves
Remarks		Leather gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Eye protection	-	Face-shield Safety glasses
Skin and body protection	:	Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1; Anti-static safety shoes Protective suit



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold pH Melting point/ range	: : : : : : : : : : : : : : : : : : : :	powder silver characteristic No data available substance/mixture is non-soluble (in water) 660 °C
Flash point Evaporation rate Flammability (solid, gas)	:	Not applicable Not applicable No data available Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	30 g/m3
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	2.5 g/cm3
Solubility(ies) Water solubility Partition coefficient: n-	:	insoluble No data available
octanol/water Autoignition temperature	:	340 °C
5	-	
Decomposition temperature Viscosity	:	No data available No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reactions	 No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Contact with acids and alkalis may release hydrogen. Stable under recommended storage conditions. Dust may form explosive mixture in air.
Conditions to avoid Incompatible materials	 No data available Acids Bases Oxidizing agents Water





Version	Revision Date:
1.0	02/03/2025

SDS Number: 102000038401

Date of last issue: -Date of first issue: 02/03/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity				
Not classified due to lack of da	ata.			
<u>Components:</u>				
Silica:				
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg			
	(Mouse): 15,000 mg/kg			
Acute inhalation toxicity	: (Rat): 0.139 mg/l Exposure time: 4 h			
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg			
Skin corrosion/irritation Not classified due to lack of da	ata.			
Serious eye damage/eye irri Not classified due to lack of da				
Respiratory or skin sensitiza	ation			
Skin sensitization Not classified due to lack of da	ata.			
Respiratory sensitization Not classified due to lack of da	ata.			
Germ cell mutagenicity Not classified due to lack of data.				
Carcinogenicity Not classified due to lack of da	ata.			
IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.			
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.			
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.			





Version		SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity		
Components:		
Silica:		
Toxicity to daphnia and other aquatic invertebrates	:	(Daphnia): 7,600 mg/l
Toxicity to algae	:	(Chlorella pyrenoidosa): 440 mg/l
Persistence and degradabili	ty	
No data available		
Bioaccumulative potential		
No data available		
Other adverse effects		
No data available		
Components:		
Silica:		
Additional ecological information	:	No data available

Disposal methods

Contaminated packaging	:	Empty containers should be taken to an approved waste
		handling site for recycling or disposal.





_



STANDART PCS 3500 Aluminium Powder

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

SECTION 14. TRANSPORT INFORMATION

Demostic regulation	
Domestic regulation	
49 CFR Not regulated as a dan	igerous good
49 CFR	: Not classified as dangerous in the meaning of transport regulations.
International Regulati	ons
UNRTDG Not regulated as a dan	igerous good
IATA-DGR Not regulated as a dan	igerous good
IMDG-Code Not regulated as a dan	igerous good
Remarks	 Not classified as dangerous in the meaning of transport regulations.
ADR	: Not classified as dangerous in the meaning of transport regulations.
IATA-DGR	: Not classified as dangerous in the meaning of transport regulations.
IMDG-Code	: Not classified as dangerous in the meaning of transport regulations.
Not dangerous goods	in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards		
SARA 313	:	The following components established by SARA Title	•	
		Aluminum	7429-90-5	>= 90 - <= 100 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know	
Aluminum	7429-90-5
Silica	7631-86-9
Pennsylvania Right To Know	
Aluminum	7429-90-5

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



ersion D	Revision Date: 02/03/2025	SDS Number: 102000038401	Date of last issue: - Date of first issue: 02/03/2025
Califo	rnia List of Hazardo	us Substances	
	Aluminum		7429-90-5
	Silica		7631-86-9
Califo		posure Limits for Ch	emical Contaminants
	Aluminum		7429-90-5
	Silica		7631-86-9
The ir	ngredients of this pr	oduct are reported ir	the following inventories:
DSL TSCA		•	s of this product are on the Canadian DSL listed as active on the TSCA inventory
TSCA			
No su	bstances are subject	to a Significant New U	se Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA PO	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0/TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average
AIIC - Australian Inventory of	of Ir	ndustrial Chemicals; ASTM - American Society for the Testing of
and Liability Act; CMR - Ca German Institute for Stand	rcin ardi	RCLA - Comprehensive Environmental Response, Compensation, ogen, Mutagen or Reproductive Toxicant; DIN - Standard of the sation; DOT - Department of Transportation; DSL - Domestic - Concentration associated with x% response; EHS - Extremely



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/03/2025	102000038401	Date of first issue: 02/03/2025

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/03/2025

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8