

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA IL HYDROLAN 8154 55900/G Aluminium Paste
Material number : 005322GD0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colouring agent

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Flammable solids, Category 1, H228
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Specific target organ toxicity - single exposure, Category 3,
Central nervous system, H336

GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H228: Flammable solid.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P317 If eye irritation persists: Get medical help.
P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.
P370 + P378 In case of fire: Use for extinction: Dry sand.
Storage:

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

| | |
|--|------------|
| Identification | CAS-No. |
| propan-2-ol | 67-63-0 |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 |

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

| Chemical name | CAS-No. EINECS-No. | Classification and labelling | Concentration[%] |
|---------------|------------------------|---|------------------|
| aluminium | 7429-90-5 231-072-3 | Flam. Sol.;1;H228 | 50 - 100 |
| propan-2-ol | 67-63-0 200-661-7 | Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 Eye Dam./Irrit.;2A;H319 STOT SE;3;H336 | 25 - 50 |
| ethanol | 64-17-5 200-578-6 | Flam. Liq.;2;H225 Eye Dam./Irrit.;2A;H319 | 1 - 10 |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | | | |
|--|-------------------------|---|---------|
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 918-481-9 | Flam. Liq.;4;H227 Asp. Tox.;1;H304 | 1 - 10 |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 918-668-5 | Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411 | 1 - 2,5 |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine | 1760-24-3 217-164-6 | Eye Dam./Irrit.;1;H318 Skin Sens.;1B;H317 STOT SE;3;H335 | 0,1 - 1 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

If swallowed

- Remove contact lenses.
- Keep eye wide open while rinsing.
- : Keep respiratory tract clear.
- Do not give milk or alcoholic beverages.
- Never give anything by mouth to an unconscious person.
- If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Carbon dioxide (CO₂), ABC powder, Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Use personal protective equipment.
Avoid dust formation.
Remove all sources of ignition.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|---|-----------|---|----------------------------------|------------|-------------|
| aluminium | 7429-90-5 | AGW (Inhalable fraction) | 10 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| aluminium | 7429-90-5 | AGW (Alveolate fraction) | 1,25 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| propan-2-ol | 67-63-0 | AGW | 200 ppm 500 mg/m ³ | 2006-01-01 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| ethanol | 64-17-5 | AGW | 200 ppm 380 mg/m ³ | 2018-06-07 | DE TRGS 900 |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste


Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | | | | | |
|--|------------|--|-----------|------------|-------------|
| Peak-limit: excursion factor (category) | | 4;(II) | | | |
| Further information | | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| silicon dioxide | 7631-86-9 | AGW (Inhalable fraction) | 4 mg/m3 | 2013-09-19 | DE TRGS 900 |
| Further information | | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | AGW | 300 mg/m3 | 2017-11-30 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900 | | | |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | AGW | 100 mg/m3 | 2009-02-16 | DE TRGS 900 |
| Peak-limit: excursion factor (category) | | 2;(II) | | | |
| Further information | | Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900 | | | |

United States of America (USA):

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|-------------|---------|-------------------------------|--------------------|---|-------|
| Page 9 / 23 | | 10200000226 | | A member of  | |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | | | | | |
|-----------|-----------|-------------------------------------|-------------------------------------|------------|--|
| aluminium | 7429-90-5 | TWA (total dust) | 50 Million particles per cubic foot | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (Respirable) | 5 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (total dust) | 15 mg/m ³ | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (total) | 10 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 5 mg/m ³ | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 15 Million particles per cubic foot | 2012-07-01 | |
| aluminium | 7429-90-5 | PEL (Total dust) | 10 mg/m ³ | 2014-11-26 | |
| aluminium | 7429-90-5 | PEL (respirable dust fraction) | 5 mg/m ³ | 2014-11-26 | |
| aluminium | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m ³ | 2008-01-01 | |
| aluminium | 7429-90-5 | TWA | 5 mg/m ³ | 2005-09-01 | |
| aluminium | 7429-90-5 | TWA (Total) | 15 mg/m ³ | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (Respirable fraction) | 5 mg/m ³ | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (total dust) | 15 mg/m ³ | 2011-07-01 | |
| aluminium | 7429-90-5 | TWA (respirable fraction) | 5 mg/m ³ | 2011-07-01 | |
| aluminium | 7429-90-5 | TWA (Total dust) | 15 mg/m ³ | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (respirable dust fraction) | 5 mg/m ³ | 1989-01-19 | |
| aluminium | 7429-90-5 | TWA (welding fumes) | 5 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (pyro powders) | 5 mg/m ³ | 2013-10-08 | |
| aluminium | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m ³ | 2013-03-01 | |
| aluminium | 7429-90-5 | TWA (Fumes) | 5 mg/m ³ | 1989-01-19 | |
| aluminium | 7429-90-5 | PEL (Welding fumes) | 5 mg/m ³ | 2017-10-02 | |
| aluminium | 7429-90-5 | PEL (Pyro | 5 mg/m ³ | 2017-10-02 | |

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | | | | | |
|--|------------|--------------|---|------------|--|
| | | powders) | | | |
| aluminium | 7429-90-5 | TWA (powder) | 5 mg/m ³ | 1989-01-19 | |
| propan-2-ol | 67-63-0 | TWA | 200 ppm | 2013-03-01 | |
| propan-2-ol | 67-63-0 | STEL | 400 ppm | 2013-03-01 | |
| propan-2-ol | 67-63-0 | TWA | 400 ppm 980 mg/m ³ | 2013-10-08 | |
| propan-2-ol | 67-63-0 | ST | 500 ppm 1 225 mg/m ³ | 2013-10-08 | |
| propan-2-ol | 67-63-0 | TWA | 400 ppm 980 mg/m ³ | 1997-08-04 | |
| propan-2-ol | 67-63-0 | TWA | 400 ppm 980 mg/m ³ | 1989-01-19 | |
| propan-2-ol | 67-63-0 | STEL | 500 ppm 1 225 mg/m ³ | 1989-01-19 | |
| propan-2-ol | 67-63-0 | PEL | 400 ppm 980 mg/m ³ | 2014-11-26 | |
| propan-2-ol | 67-63-0 | STEL | 500 ppm 1 225 mg/m ³ | 2014-11-26 | |
| ethanol | 64-17-5 | TWA | 1 000 ppm | 2009-01-01 | |
| ethanol | 64-17-5 | TWA | 1 000 ppm 1 900 mg/m ³ | 2013-10-08 | |
| ethanol | 64-17-5 | TWA | 1 000 ppm 1 900 mg/m ³ | 1997-08-04 | |
| ethanol | 64-17-5 | TWA | 1 000 ppm 1 900 mg/m ³ | 1989-01-19 | |
| ethanol | 64-17-5 | STEL | 1 000 ppm | 2013-03-01 | |
| ethanol | 64-17-5 | PEL | 1 000 ppm 1 900 mg/m ³ | 2014-11-26 | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 20 Million particles per cubic foot | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA (Dust) | 80 mg/m ³ / %SiO ₂ | 2012-07-01 | |
| silicon dioxide | 7631-86-9 | TWA | 6 mg/m ³ | 2013-10-08 | |
| silicon dioxide | 7631-86-9 | PEL | 6 mg/m ³ | 2014-11-26 | |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | TWA | 500 ppm 2 000 mg/m ³ | 2007-01-01 | |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | | | | | |
|--|------------|-----|------------------------------------|------------|--|
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | TWA | 400 ppm 1 600 mg/m ³ | 1989-01-19 | |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | TWA | 500 ppm 2 000 mg/m ³ | 2007-01-01 | |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | TWA | 200 mg/m ³ | 2010-03-01 | |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | TWA | 400 ppm 1 600 mg/m ³ | 1989-01-19 | |

8.2 Exposure controls

Personal protective equipment

- Eye protection : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

- Skin should be washed after contact.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 : Long sleeved clothing
 Safety shoes
 : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 : In the case of dust or aerosol formation use respirator with an approved filter.

Environmental exposure controls

- General advice : The product should not be allowed to enter drains, water courses or the soil.
 : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

- Appearance : Pasty solid
- Colour : silver
- Odour : characteristic
- pH : substance/mixture is non-soluble (in water)
- Freezing point : No data available
- Boiling point/boiling range : 82 - 83 °C

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

| | |
|--|--|
| Flash point | : No data available |
| Bulk density | : No data available |
| Flammability (solid, gas) | : The substance or mixture is a flammable solid with the category 1. |
| Auto-flammability | : not auto-flammable |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Density | : 1,3 - 2,0 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Miscibility with water | : partly miscible |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Flow time | : No data available |
| Explosive properties | : Not explosive Vapours may form explosive mixture with air. |

9.2 Other information

No data available

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Components:**propan-2-ol :**

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

ethanol :

Acute oral toxicity : LD50 Rat, male and female: 10 470 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 Rat, male and female: 124,7 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Naphtha (petroleum), hydrotreated heavy :

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product**

Eye irritation

Respiratory or skin sensitisation**Product**

Result: Does not cause skin sensitisation.

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may
degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****Solvent naphtha (petroleum), light arom. (64742-95-6) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

| | |
|------------------------|--|
| Product | : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations. |
| Contaminated packaging | : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

Do not burn, or use a cutting torch on, the empty drum.
 In accordance with local and national regulations.

SECTION 14: Transport information
14.1 UN number

| | |
|------|--------|
| ADR | : 1325 |
| TDG | : 1325 |
| CFR | : 1325 |
| IMDG | : 1325 |
| IATA | : 1325 |

14.2 Proper shipping name

| | |
|------|---|
| ADR | : FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste) |
| TDG | : FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste) |
| CFR | : FLAMMABLE SOLIDS, ORGANIC, N.O.S. (Aluminum pigment paste) |
| IMDG | : FLAMMABLE SOLID, ORGANIC, N.O.S. (,Aluminium pigment paste) |
| IATA | : FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste) |

14.3 Transport hazard class

| | |
|------|-------|
| ADR | : 4.1 |
| TDG | : 4.1 |
| CFR | : 4.1 |
| IMDG | : 4.1 |
| IATA | : 4.1 |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

14.4 Packing group**ADR**

Packaging group : II
Classification Code : F1
Hazard Identification Number : 40
Labels : 4.1
Tunnel restriction code : (E)

TDG

Packaging group : II
Labels : 4.1

CFR

Packaging group : II
Labels : 4.1

IMDG

Packaging group : II
Labels : 4.1
EmS Number : F-G, S-G

IATA

Packing instruction (cargo aircraft) : 448
Packing instruction (passenger aircraft) : 445
Packing instruction (LQ) : Y441
Packaging group : II
Labels : 4.1

14.5 Environmental hazards

IMDG :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

14.6 Special precautions for user

IMDG Code- segregation group:

: IMDG Code segregation group 15 - Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|--|---|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : Not applicable |
| REACH - List of substances subject to authorisation (Annex XIV) | : Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : Not applicable |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast) | : Not applicable |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : Banned and/or restricted (aluminium powder (stabilised)) (propan-2-ol) (ethanol) (Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha) (Solvent naphtha (petroleum), light arom.) (N-(3-(trimethoxysilyl)propyl)ethylenediamine) |

STAPA IL HYDROLAN 8154 55900/G Aluminium Paste

Version 6.0

Revision Date 09.01.2025

Print Date 14.01.2025

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

| | |
|------|--|
| H225 | : Highly flammable liquid and vapour. |
| H226 | : Flammable liquid and vapour. |
| H227 | : Combustible liquid. |
| H228 | : Flammable solid. |
| H303 | : May be harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H313 | : May be harmful in contact with skin. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H411 | : Toxic to aquatic life with long lasting effects. |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.