according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version	Revision Date:	SDS Number:	Print Date: 30.11.2024
3.1	02.04.2024	102000029891	Date of first issue: 06.08.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name	: HYDRO PELLET 1700
Product code	: 024075HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture					
Classification (REGULATION (EC) No 1272/2008)					
Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.			H412: Harmful to aquatic life with long lasting effects.		
2.2 Label elements					
Labelling (REGULATION (EC) No 1272/2008)					
Hazard statements	:	H412	Harmful to aquatic life with long lasting effects.		
Precautionary statements	:	Preventio P273	n: Avoid release to the environment.		

according to Regulation (EC) No. 1907/2006

HYDRO PELLET 1700



approved waste disposal plant.

Version	Revision Date:	SDS Number:	Print Date: 30.11.2024
3.1	02.04.2024	102000029891	Date of first issue: 06.08.2018
		Disposal: P501	Dispose of contents/ container to an

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Phosphoric acid, C11-14-isoalkyl	154518-38-4(52933-	Skin Irrit. 2; H315	>= 3 - < 10
esters, C13-rich	07-0)	Eye Dam. 1; H318	
	,	Aquatic Chronic 2;	
		H411	
	01-2119976356-25		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move the victim to fresh air.	
	No hazards which require special first a	id measures.
If inhaled	 If unconscious, place in recovery positionadvice. If symptoms persist, call a physician. 	on and seek medical
In case of skin contact	: Wash off immediately with soap and ple	enty of water.
	If skin irritation persists, call a physician If on skin, rinse well with water. If on clothes, remove clothes.	

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024	SDS Number: 102000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018	
In cas	se of eye contact	Remove conta Keep eye wide	h water as a precaution. ct lenses. open while rinsing. persists, consult a specialist.	
If swallowed		Do not give mi Never give any	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.	

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	ABC powder Carbon dioxide (CO2) Water Foam
5.2 Special hazards arising from	the	substance or mixture
Specific hazards during firefighting	:	Contact with water liberates extremely flammable gas (hydrogen).
		Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

according to Regulation (EC) No. 1907/2006

HYDRO PELLET 1700



Version 3.1	Revision Date: 02.04.2024	SDS Number: 102000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018	
Personal precautions		Evacuate p Use person Avoid dust	Use personal protective equipment. Evacuate personnel to safe areas. Use personal protective equipment. Avoid dust formation. Avoid breathing dust.	
6.2 Envir	onmental precautions	;		
General advice		courses or Prevent pro Prevent fur	oduct from entering drains. ther leakage or spillage if safe to do so. Ict contaminates rivers and lakes or drains inform	
6.3 Metho	ods and material for o	ontainment and o	cleaning up	
Meth	Methods for cleaning up		nical handling equipment. a vacuum cleaner.	
			h with water. table, closed containers for disposal.	

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	I	
Advice on safe handling	:	Avoid dust formation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Store away from heat. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
		Dispose of rinse water in accordance with local and national
Advice on protection against fire and explosion	:	regulations. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	ncl	uding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

technological safety standards.

resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024		S Number: 2000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018				
Further information on storage conditions		: Protect from humidity and water.						
Advi	Advice on common storage		 Do not store together with oxidizing and self-igniting product Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions 					
	Further information on : storage stability		No decomposition	on if stored and applied as directed.				

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
· ·		TWA (Respirable fraction)	4 mg/m3	GB EH40		
		TWA (inhalable dust)	10 mg/m3	GB EH40		
	, e e e e e e e e e e e e e e e e e e e					

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024	SDS Number 10200002989		int Date: 30.11.2024 ate of first issue: 06.08.20	018
		TWA (F dust)	Respirable	4 mg/m3	GB EH40
	ir M M re S C C ir a le n P P re d a n te S S S	nhalable dust are those when sampling is under ADHS14/4 General m espirable, thoracic an substance hazardous concentration in air eq nhalable dust or 4 mg any dust will be subject evels. Some dusts has nust comply with the a particles of a wide range particular particle after esponse that it elicits listinguishes two size and 'respirable'., Inhala naterial that enters the vailable for deposition the fraction that pen definitions and explana- contain components the should be complied with	se fractions ertaken in a ethods for s d inhalable to health ind ual to or gre .m-3 8-hour ct to COSHI- ve been ass appropriate ge of sizes. entry into t depend on fractions for able dust ap e nose and n in the resp netrates to the atory materinat have the ith., Where n	beses of these limits, respi of airborne dust which w ccordance with the methe sampling and gravimetric aerosols., The COSHH of cludes dust of any kind w eater than 10 mg.m-3 8-h TWA of respirable dust. If people are exposed to signed specific WELs and limits., Most industrial du The behaviour, deposition he human respiratory syst the nature and size of the proximates to the fraction mouth during breathing a biratory tract. Respirable he gas exchange region al are given in MDHS14/ ir own assigned WEL, al no specific short-term ex exposure limit should be	ill be collected ods described in analysis or definition of a hen present at a nour TWA of This means that o dust above these d exposure to these d exposure to these usts contain on and fate of any stem, and the body he particle. HSE ermed 'inhalable' on of airborne and is therefore dust approximates of the lung. Fuller 4., Where dusts I the relevant limits posure limit is listed,

Derived No Effect Leve	el (DNEL) accord	ing to Regulation	(EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Phosphoric acid, C11- 14-isoalkyl esters, C13-rich	Workers	Inhalation	Long-term systemic effects	34.94 mg/m3
	Workers	Dermal	Long-term systemic effects	100.13 mg/kg
	Consumers	Inhalation	Long-term systemic effects	10.43 mg/m3
	Consumers	Dermal	Long-term systemic effects	60.08 mg/kg
	Consumers	Oral	Long-term systemic effects	6.01 mg/kg
2,2',2"-nitrilotriethanol	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Dermal	Long-term systemic effects	7.5 mg/kg
	Workers	Dermal	Long-term local	0.14 mg/cm2

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

				ate: 30.11.2024 first issue: 06.08.201	18				
						effects			
		Consume	rs	Inhalation		Long-term local effects		0.4 mg/m3	
		Consume	rs	Oral		Long-term systemic effects		3.3 mg/kg	
		Consume	rs	Dermal		Long-term systemic effects	;	2.66 mg/kg	
		Consumers		Dermal		Long-term local effects		0.07 mg/cm	
Predi	cted No Effect Co	oncentratio	on (PN	IEC) accor	ding to I	Regulation (EC) No.	190	07/2006:	
Subst	tance name		Envir	onmental C	Compartr	nent	Va	alue	
alumii	nium powder (stab	oilised)	Fresh	Fresh water			0.0	0749 mg/l	
			clarif	ication plar	nt		20	mg/l	
	Phosphoric acid, C11-14-isoalkyl esters, C13-rich		Fresh	Fresh water			0.0	0.00631 mg/l	
			Fresh water sediment				0.1	113 mg/kg	
			Intermittent water release				0.0	0631 mg/l	
		Marine water				0.000631 mg/l			
			Marir	ne sedimen	t		0.0	0113 mg/kg	
			STP				10	mg/l	
			Soil	Soil				0188 mg/kg	
2,2',2	"-nitrilotriethanol		Fresh	n water				32 mg/l	
			Marir	ne water				032 mg/l	
			1						

Fresh water sediment

Marine sediment clarification plant

Soil

8.2 Exposure controls

Personal protective equipm Eye/face protection Hand protection Material	:	Tightly fitting safety goggles Protective gloves
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Long sleeved clothing Dust impervious protective suit Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration

1.7 mg/kg

10 mg/l

0.17 mg/kg

0.151 mg/kg

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024	SDS Number: 102000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018			
		requires. Breathing app	aratus with filter.			
	P1 filter					
OFOTIO	CECTION 0. Developed and a coming properties					

SECTION 9: Physical and chemical properties

9.1	Information on basic physical Form	l an :	d chemical properties pellets
	Colour	:	silver
	Odour	:	characteristic
	Odour Threshold	:	No data available
	Melting point/range	:	160 °C
	Boiling point/boiling range	:	No data available
	Flammability	:	Combustible Solids
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	Not applicable
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	substance/mixture is non-soluble (in water)
	Viscosity, kinematic	:	No data available
	Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	No data available
	Relative density	:	No data available
	Density	:	2.5 g/cm3
	Relative vapour density	:	No data available

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024	•-	S Number: 2000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018
	cle characteristics article Size Distribution	:	No data available	
9.2 Other	information			
	mable solids			
Burn	ing number	:	1	
Self-	ignition	:	No data available	9
Misc	ibility with water	:	immiscible	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	Contact with acids and alkalis may release hydrogen.	
		Stable under recommended storage conditions.
		Dust may form explosive mixture in air.
10.4 Conditions to avoid Conditions to avoid	:	No data available
10.5 Incompatible materials		
Materials to avoid	:	Acids Bases Oxidizing agents Water

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

rsion	Revision Date: 02.04.2024	SDS Number: 102000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018	
<u>Comp</u>	onents:			
alumi	nium powder (stabil	lised):		
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist				
	corrosion/irritation	ailable information.		
<u>Produ</u>	ct:			
Remai		: May cause skin	irritation and/or dermatitis.	
<u>Comp</u>	onents:			
Phose	horic acid. C11-14-i	isoalkyl esters, C13-ri	ch:	
Result		: Skin irritation		
	us eye damage/eye assified based on ava			
Produ	<u>ct:</u>			
Asses	sment	: No eye irritation		
Remai	ks	: Product dust may be irritating to eyes, skin and respiratory system.		
<u>Comp</u>	onents:			
Phosp	horic acid, C11-14-i	isoalkyl esters, C13-ri	ch:	
Result		: Irreversible effe		
Respi	ratory or skin sensi	tisation		
	ensitisation assified based on ava	ailable information.		
-	ratory sensitisation	ailable information.		
	cell mutagenicity assified based on ava	ailable information.		
	nogenicity assified based on ava	ailable information.		
Repro	ductive toxicity			

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024		OS Number: 2000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018	
	- single exposure lassified based on availa	able	information.		
	- repeated exposure lassified based on availa	able	information.		
•	ration toxicity lassified based on availa	able	information.		
11.2 Infor	mation on other hazard	ds			
Furth	er information				
<u>Prode</u> Rema		:	No data available	•	
SECTIO	N 12: Ecological info	rma	tion		
12.1 Toxic	city				
<u>Com</u>	oonents:				
Phos	phoric acid, C11-14-isc	alk	yl esters, C13-ric	h:	
Toxic	xicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l Exposure time: 96 h				
	ity to daphnia and other ic invertebrates	:	: EC50 (Daphnia magna (Water flea)): 6.31 mg/l Exposure time: 48 h		
Toxic plants	ity to algae/aquatic	:	: EC50 (algae): 150 mg/l Exposure time: 72 h		
Ecoto	oxicology Assessment				
Chror	nic aquatic toxicity	:	Toxic to aquatic I	ife with long lasting effects.	
	i stence and degradabil ata available	ity			
	ccumulative potential ata available				
	l ity in soil ata available				
12.5 Resu	lts of PBT and vPvB a	sse	ssment		
Prod	uct: ssment	:		nixture contains no components considered stent, bioaccumulative and toxic (PBT), or	

A member of **C ALTANA**

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024		DS Number: 2000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018
	ocrine disrupting prope ata available	ertie	s	
12.7 Othe	er adverse effects			
	<u>uct:</u> tional ecological mation	:	unprofessional ha	hazard cannot be excluded in the event of andling or disposal. c life with long lasting effects.
SECTIO	N 13: Disposal consid	der	ations	
	pean Waste Catalogue pean Waste Catalogue	:		rrous metal dust and particles particulates and dust (including ball-mill dust) ous substances
13.1 Wast	te treatment methods			
Prod	uct	:	courses or the so Do not contamina chemical or used Send to a license	te ponds, waterways or ditches with

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. In accordance with local and national regulations.
--

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version 3.1	Revision Date: 02.04.2024	SDS Number: 102000029891	Print Date: 30.11.2024 Date of first issue: 06.08.2018
IMDG		: Not regulated	as a dangerous good
ΙΑΤΑ		: Not regulated	as a dangerous good
14.4 Packi	ng group		
ADR		: Not regulated	as a dangerous good
IMDG		: Not regulated	as a dangerous good
IATA	(Cargo)	: Not regulated	as a dangerous good
IATA (Passenger)		: Not regulated	as a dangerous good
14.5 Envir	onmental hazards		
Not reg	gulated as a dangerou	is good	
14.6 Speci	al precautions for us	er	
Remar	ks	: Not classified regulations.	as dangerous in the meaning of transport
14.7 Mariti	me transport in bulk	according to IMO i	nstruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	aluminium powder (stabilised)
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		
This product is regulated by Regulation (EU) 2019/1148: suspicious transactions, and significant disappearances a should be reported to the relevant national contact point.	and	aluminium powder (stabilised) thefts (ANNEX II)

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version	Revision Date:	SDS Number:	Print Date: 30.11
3.1	02.04.2024	102000029891	Date of first issue

1.2024 ue: 06.08.2018

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228	:	Flammable solid.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbrev	iations	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Flam. Sol.	:	Flammable solids
Skin Irrit.	:	Skin irritation
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period

: Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern: TCSI - Taiwan Chemical Substance Inventory: TECI - Thailand Existing Chemicals

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 1700

Version	Revision Date:	SDS Number:	Print Date: 30.11.2024
3.1	02.04.2024	102000029891	Date of first issue: 06.08.2018

Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN