

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HYDRO PELLET 5000

Material number : 024073HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770 Telefax : +499152777008

E-mail address : msds.eckart@altana.com

Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Skin corrosion/irritation, Category 3, H316

Short-term (acute) aquatic hazard, Category 3, H402 Long-term (chronic) aquatic hazard, Category 3, H412

Page 1 / 17	102000029890	A member of () ALTANA



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

GHS-Labelling

Signal word : Warning

Hazard statements : H316: Causes mild skin irritation.

H412: Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

P332 + P317 If skin irritation occurs: Get medical help.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label

Other hazards which do not result in classification

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0)	;2;H315 ;1;H318 Aquatic Acute;2;H401	3 - 10

Page 2 / 17	102000029890	A member of ALTANA
-------------	--------------	---------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

	Aquatic Chronic;2;H411	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

Page 3 / 17	102000029890	A member of O ALTANA
		The second secon



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing

media

: ABC powder, Carbon dioxide (CO2), Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Contact with water liberates extremely flammable gas

(hydrogen).

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and

contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Evacuate personnel to safe areas. Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Page 4 / 17	102000029890	A member of C ALTANA
-------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Do not use a vacuum cleaner.

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

This information is not available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid dust formation. Routine housekeeping should be

instituted to ensure that dusts do not accumulate on surfaces.

Store away from heat.

Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance

with local and national regulations.

Advice on protection against

fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

Page 5 / 17	102000029890	A member of O ALTANA
-------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

areas and containers place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the

technological safety standards.

Further information on

storage conditions

: Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic

reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	2014-04-02	DE TRGS 900
Peak-limit: exc factor (categor		2;(II)			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m3	2014-04-02	DE TRGS 900
Peak-limit: exc	ursion	2;(II)			

Page 6 / 17	102000029890	A member of C ALTANA
-------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

factor (categor	y)				
2,2',2"- nitrilotriethan ol	102-71-6	AGW (Inhalable fraction)	1 mg/m3	2018-06-07	DE TRGS 900
Peak-limit: exc factor (categor		1;(l)			
Further inform	ation	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	

Page 7 / 17	102000029890	A member of C ALTANA
-------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

(stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (Respirable particulate matter)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable particulate matter)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	
2,2',2"- nitrilotriethan ol	102-71-6	TWA	5 mg/m3	2013-03-01	
2,2',2"- nitrilotriethan ol	102-71-6	PEL	5 mg/m3	2014-11-26	

8.2 Exposure controls

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

The exact break through time can be obtained from the protective glove producer and this has to be observed.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing

: Dust impervious protective suit

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Page 9 / 17	102000029890	A member of C ALTANA



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

Breathing apparatus with filter.

P1 filter

Environmental exposure controls

General advice

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Water : The product should not be allowed to enter drains, water

courses or the soil.

:

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : pellets

Colour : silver

Odour : characteristic

pH : substance/mixture is non-soluble (in water)

Freezing point : No data available
Boiling point/boiling range : No data available

Flash point

Not applicable

Bulk density : No data available Flammability (solid, gas) : Combustible Solids

Auto-flammability : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available

Page 10 / 17	102000029890	A member of C ALTANA
--------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

Vapour pressure : No data available
Density : No data available

Solubility(ies)

Water solubility : insoluble

Miscibility with water : immiscible

Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Ignition temperature : No data available
Thermal decomposition : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available

9.2 Other information

Self-Accelerating : No data available

decomposition temperature

(SADT)

Self-heating substances : No data available
Heat of combustion : No data available
Impact sensitivity : No data available
Surface tension : No data available

Conductivity : No data available
Sublimation point : No data available
Molecular weight : No data available

Page 11 / 17 102000029890 A n	member of C ALTANA
-------------------------------	---------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid

: No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Water

10.6 Hazardous decomposition products

Hazardous decomposition

: No data available

products

Other information : No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

A member of C ALIANA	Page 12 / 17	102000029890	A member of C ALTANA
----------------------	--------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

No data available

Skin corrosion/irritation

Product

May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product

Result: No eye irritation

Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

Page 13 / 17	102000029890	A member of C ALTANA
		At Intelliber of Calabana



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Revision Date 22.09.2021 Version 2.1 Print Date 30.11.2024

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich (154518-38-4) :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6,31 mg/l

Exposure time: 48 h

: EC50 (algae): 150 mg/l Toxicity to algae

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Page 14 / 17	102000029890	A member of C ALTANA
--------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

Page 15 / 17	102000029890	A member of C ALTANA



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

SECTION 14: Transport information

- 14.1 UN number
- 14.2 Proper shipping name
- 14.3 Transport hazard class
- 14.4 Packing group
- 14.5 Environmental hazards

14.6 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

: Not applicable

: Not applicable

: Not applicable

: Banned and/or restricted

(aluminium powder (stabilised)) (Phosphoric acid, C11-14-isoalkyl

esters, C13-rich)

Page 16 / 17	102000029890	A member of C ALTANA
--------------	--------------	-----------------------------



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLET 5000

Version 2.1 Revision Date 22.09.2021 Print Date 30.11.2024

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H315 : Causes skin irritation.
H316 : Causes mild skin irritation.
H318 : Causes serious eye damage.

H401 : Toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.