

Globally Harmonized System of Classification and Labeling of
Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : ROTOSTAR UV/LED FPG 730 876 FLEXO INK
Material number : 027815U11

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Acute toxicity, Category 4, Oral, H302
Skin corrosion/irritation, Category 2, H315
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

Skin sensitization, Category 1, H317
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

Symbol(s)



Signal Word

: Warning

Hazard Statements

: H302: Harmful if swallowed.
 H315 + H319: Causes skin irritation and serious eye irritation.
 H317: May cause an allergic skin reaction.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**
 P261 Avoid breathing mist or vapors.
 P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P317 If skin irritation or rash occurs: Get medical help.
 P337 + P317 If eye irritation persists: Get medical help.
 P391 Collect spillage.
Disposal:

Globally Harmonized System of Classification and Labeling of
Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label

| | |
|--|--------------|
| Identification | CAS-No. |
| copper | 7440-50-8 |
| Propylidynetrimehanol, ethoxylated, esters with acrylic acid | 28961-43-5 |
| 2-Propenoic acid, reaction products with dipentaerythritol | 1384855-91-7 |
| Glycerol, propoxylated, esters with acrylic acid | 52408-84-1 |
| phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | 162881-26-7 |
| | 2067275-86-7 |

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous ingredients

| Chemical name | CAS-No. EINECS-No. | Classification and labeling | Concentration[%] |
|--|------------------------|--|------------------|
| copper | 7440-50-8 231-159-6 | Acute Tox.;4;H302 Eye Dam./Irrit.;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410 | 25 - 30 |
| Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2,2- | 51728-26-8 | Skin Corr./Irrit.;2;H315 Eye Dam./Irrit.;2A;H319 | 10 - 20 |

Globally Harmonized System of Classification and Labeling of
Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

| | | | |
|--|--------------------------|--|----------|
| bis(hydroxymethyl)-1,3-propanediol (4:1) | | Aquatic Chronic;2;H411 | |
| Propylidyntrimethanol, ethoxylated, esters with acrylic acid | 28961-43-5 | Eye Dam./Irrit.;2A;H319 Skin Sens.;1;H317 Aquatic Chronic;3;H412 | 10 - 20 |
| 2-Propenoic acid, reaction products with dipentaerythritol | 1384855-91-7 | Eye Dam./Irrit.;2A;H319 Skin Sens.;1A;H317 Aquatic Chronic;3;H412 | 2,5 - 10 |
| 2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane | 144086-02-2 604-394-0 | Eye Dam./Irrit.;2A;H319 Aquatic Chronic;2;H411 | 2,5 - 10 |
| zinc | 7440-66-6 231-175-3 | Aquatic Acute;1;H400 Aquatic Chronic;1;H410 | 2,5 - 10 |
| Glycerol, propoxylated, esters with acrylic acid | 52408-84-1 | Eye Dam./Irrit.;2A;H319 Skin Sens.;1;H317 | 1 - 10 |
| phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | 162881-26-7 | Acute Tox.;5;H303 Acute Tox.;5;H313 Skin Sens.;1;H317 Aquatic Chronic;4;H413 | 1 - 2,5 |

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

| | | | |
|--|--------------|---|------------|
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with oxirane, 4-(dimethylamino)benzoate | 2067275-86-7 | Skin Sens.;1B;H317 Aquatic Chronic;4;H413 | 1 - 2,5 |
| 2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)- | 7078-98-0 | Skin Sens.;1;H317 Aquatic Chronic;4;H413 | 0,1 - 0,25 |
| Polymer with quaternized ammonium groups | 1431957-88-8 | Aquatic Acute;1;H400 Aquatic Chronic;1;H410 | 0,1 - 0,25 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first-aid measures

- General advice : Take the victim into fresh air.
Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If skin irritation persists, call a physician.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

| | |
|--------------|--|
| If swallowed | Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. : Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |
|--------------|--|

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures
5.1 Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Special powder against metal fire, Dry sand, ABC powder |
| Unsuitable extinguishing media | : Water, High volume water jet, Carbon dioxide (CO ₂) |

5.2 Special hazards arising from the substance or mixture

| | |
|---------------------------------------|---|
| Specific hazards during fire fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
|---------------------------------------|---|

5.3 Advice for firefighters

| | |
|--|--|
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : Standard procedure for chemical fires. |

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Pick up and transfer to properly labeled containers.
Do not flush with water.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on : Protect from humidity and water.

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

storage conditions

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|---------------------|-----------|---|------------------------|------------|-------------|
| copper | 7440-50-8 | AGW (inhalable fraction) | 1 mg/m ³ | | DE TRGS 900 |
| zinc | 7440-66-6 | AGW (Inhalable fraction) | 10 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit category | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| zinc | 7440-66-6 | AGW (Alveolate fraction) | 1,25 mg/m ³ | 2021-07-02 | DE TRGS 900 |
| Peak-limit category | | 2;(II) | | | |
| Further information | | When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

8.2 Exposure controls
Personal protective equipment

- Eye protection : Safety glasses
 : Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
 Recommended preventive skin protection
 Skin should be washed after contact.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 Equipment should conform to EN 14387

Environmental exposure controls

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

General advice : The product should not be allowed to enter drains, water courses or the soil.
: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance : liquid
Color : gold
Odor : characteristic
pH : substance/mixture is non-soluble (in water)
Freezing point : No data available
Boiling point/boiling range : > 100 °C
Flash point : > 100 °C

Bulk density : No data available
Flammability (solid, gas) : No data available
Auto-flammability : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapor pressure : No data available
Density : 1,4 g/cm³
Solubility(ies)
Water solubility : insoluble
Miscibility with water : immiscible

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

| | |
|--|---------------------|
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Flow time | : No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

10.4 Conditions to avoidConditions to avoid : Do not allow evaporation to dryness.
No data available**10.5 Incompatible materials**

Materials to avoid : No data available

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

10.6 Hazardous decomposition products

Hazardous decomposition products :
Other information : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****copper :**

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide :

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Rat: > 2 000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitization

Product

Causes sensitization.

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

copper (7440-50-8) :

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1) (51728-26-8) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid (28961-43-5) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

2-Propenoic acid, reaction products with dipentaerythritol (1384855-91-7) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane (144086-02-2) :

Ecotoxicology Assessment

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

zinc (7440-66-6) :

M-Factor : 1

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7) :
Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

(2067275-86-7) :
Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)- (7078-98-0) :
Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

Polymer with quaternized ammonium groups (1431957-88-8) :
Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**Additional ecological
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information**14.1 UN number**

ADR : 3082

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3082**IATA** : 3082**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(,Copper metal powder)**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9**IATA** : 9

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

14.4 Packing group**ADR**

Packaging group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III
Labels : 9
EmS Code : F-A, S-F

IATA

Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packaging group : III
Labels : 9

14.5 Environmental hazards**ADR** : Environmentally hazardous**IMDG** : Marine pollutant

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

14.6 Special precautions for user

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|--|--|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : Banned and/or restricted (Propylidynetrimethanol, ethoxylated, esters with acrylic acid) (2-Propenoic acid, reaction products with dipentaerythritol) (2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane) (Glycerol, propoxylated, esters with acrylic acid) (2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one) |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : (Copper) (phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide) (2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one) |

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

| | | |
|--|--|------------------|
| REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). | (2-ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate]) | : Not applicable |
| Regulation (EU) No 2024/590 on substances that deplete the ozone layer | | : Not applicable |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast) | | : Not applicable |
| Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals | | : Not applicable |

15.2 Chemical Safety Assessment

No data available

SECTION 16: Other information
Full text of H-Statements

| | |
|-------------|---|
| H302 | : Harmful if swallowed. |
| H303 | : May be harmful if swallowed. |
| H313 | : May be harmful in contact with skin. |
| H315 | : Causes skin irritation. |
| H315 + H319 | : Causes skin irritation and serious eye irritation. |
| H317 | : May cause an allergic skin reaction. |
| H319 | : Causes serious eye irritation. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| H413 | : May cause long lasting harmful effects to aquatic life. |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

Globally Harmonized System of Classification and Labeling of
Chemicals (GHS)

ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 4.0

Revision Date 05.03.2026

Print Date 06.03.2026

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.