according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAY/STEEL 316L K Flake Standard Grade

Product code : 046692BFL

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - repeated H373: May cause damage to organs through

exposure, Category 2 prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, H413: May cause long lasting harmful effects to

Category 4 aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H373 May cause damage to organs through

prolonged or repeated exposure.

H413 May cause long lasting harmful effects to

aquatic life.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P308 + P313 IF exposed or concerned: Get medical

advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

Hazardous components which must be listed on the label:

nickel

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
chromium	7440-47-3	Aquatic Chronic 4;	>= 10 - < 20
	231-157-5	H413	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version 4.1	Revision Date: 05.02.2025	SDS Number: 102000002383	Print Date: 06.02.2025 Date of first issue: 09.01.2014	
nickel		7440-02-0 231-111-4 028-002-00-7	Skin Sens. 1; H317 Carc. 2; H351 STOT RE 1; H372 Aquatic Chronic 3; H412	>= 2.5 - < 10
Subst	ances with a workpla	ce exposure limit :		
mang	anese	7439-96-5 231-105-1		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : Call a physician or poison control centre immediately.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid dust formation.

Avoid breathing dust.

Ensure adequate ventilation.

6.2 Environmental precautions

General advice : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

Keep in a dry place.

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
iron	7439-89-6	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable	4 mg/m3	GB EH40
		fraction)		
chromium	7440-47-3	TWA	2 mg/m3	2006/15/EC
	Further inform	nation: Indicative		
		TWA	0.5 mg/m3	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA	2 mg/m3	2006/15/EC
			(chromium)	
	Further inform	nation: Indicative		
nickel	7440-02-0	TWA	0.5 mg/m3	GB EH40
			(Nickel)	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Capable of causing occupational asthma., Capable of causing cancer and/or heritable genetic damage.			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

molybdenum	7439-98-7	TWA	10 mg/m3 (Molybdenum)	GB EH40	
		STEL	20 mg/m3 (Molybdenum)	GB EH40	
manganese	7439-96-5	TWA (inhalable fraction)	0.2 mg/m3 (Manganese)	2017/164/EU	
	Further inform	Further information: Indicative			
		TWA (Respirable fraction)	0.05 mg/m3 (Manganese)	2017/164/EU	
	Further inform	nation: Indicative			
		TWA (Inhalable)	0.2 mg/m3 (Manganese)	GB EH40	
		TWA (Respirable fraction)	0.05 mg/m3 (Manganese)	GB EH40	

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
chromium	7440-47-3	chromium (chromium): 10 µmol/mol creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	(21122) 0000	ranig to regulation	(=0) 1101 10017=0001	
Substance name	End Use	Exposure routes	Potential health effects	Value
iron	Workers	Inhalation	Long-term local effects	3 mg/m3
	Consumers	Inhalation	Long-term local effects	1.5 mg/m3
	Consumers	Oral	Long-term systemic effects	0.71 mg/kg
manganese	Workers	Inhalation	Long-term systemic effects	0.2 mg/m3
	Workers	Inhalation	Long-term local effects	0.2 mg/m3
	Workers	Inhalation	Acute local effects	0.2 mg/m3
	Workers	Dermal	Long-term systemic effects	0.004 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.041 mg/m3
	Consumers	Inhalation	Long-term local effects	0.041 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.02 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
manganese	Fresh water	0.034 mg/l
	Marine water	0.003 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Fresh water sediment	3.3 mg/kg
Marine sediment	0.34 mg/kg
Intermittent Release	0.028 mg/l
STP Microorganisms	100 mg/l
Soil	3.4 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection

Safety glasses

Remarks

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Dust impervious protective suit

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form : powder

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/ range : Not applicable

Boiling point/boiling range : Not applicable

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : 8 g/cm3

Bulk density : 0.24 - 0.39 kg/m3 Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : 31 - 50 µm

9.2 Other information

Flammable solids

Burning number : 1

Self-ignition : No data available

Miscibility with water : immiscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

chromium:

Acute oral toxicity : LD50 Oral: > 5,000 mg/kg

Acute inhalation toxicity : LC50: > 5.41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

nickel:

Acute oral toxicity : LD50 Oral: 9,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Product dust may be irritating to eyes, skin and respiratory

system.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

May cause sensitisation of susceptible persons by skin

contact.

May cause sensitisation of susceptible persons by inhalation

of aerosol or dust.

Components:

nickel:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Components:

nickel:

Carcinogenicity - : Limited evidence of carcinogenicity in animal studies

Assessment

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

nickel:

Exposure routes : Inhalation

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

chromium:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

nickel:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21* - Wastes from thermal aluminium metallurgy, other

particles and dust (including ball mill dust) containing

dangerous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version Revision Date: SDS Number: Print Date: 06.02.2025

4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

chromium (Number on list 72, 28)

nickel (Number on list 27)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) on substances that deplete the ozone

ayer

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

Not applicable

: Not applicable

Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H317 : May cause an allergic skin reaction. H351 : Suspected of causing cancer.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Revision Date: SDS Number: Print Date: 06.02.2025 Version 4.1 05.02.2025 102000002383 Date of first issue: 09.01.2014

Carcinogenicity Carc. Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure Europe. Indicative occupational exposure limit values 2006/15/EC 2017/164/EU Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values

UK. EH40 WEL - Workplace Exposure Limits

GB EH40 GB EH40 BAT UK. Biological monitoring guidance values

2006/15/EC / TWA Limit Value - eight hours 2006/15/EC / TWA Limit Value - eight hours 2017/164/EU / TWA Limit Value - eight hours

GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period) GB EH40 / STEL Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan): ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Skin Sens. 1 H317 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STAY/STEEL 316L K Flake Standard Grade

Version 4.1	Revision Date: 05.02.2025	SDS Number: 102000002383	Print Date: 06.02.2025 Date of first issue: 09.01.2014	
Carc.	2	H351	Calculation method	
STOT	RE 2	H373	Calculation method	
Aquat	ic Chronic 4	H413	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN