

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STAPA METALLUX 1580 Aluminium Paste  
Product code : 053042G60

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colouring agents, pigments

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412      Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** P273      Avoid release to the environment.  
**Disposal:**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

P501      Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5  231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 50 - <= 100
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9  918-481-9 01-2119457273-39	Asp. Tox. 1; H304	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6  918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice      :    Move the victim to fresh air.

No hazards which require special first aid measures.

If inhaled      :    If unconscious, place in recovery position and seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 03.12.2024
3.0	13.02.2023	102000030587	Date of first issue: 02.10.2018

---

- If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Remove contact lenses.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Dry sand  
Special powder against metal fire
- Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.
- Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 03.12.2024
3.0	13.02.2023	102000030587	Date of first issue: 02.10.2018

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.

#### 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up and shovel.  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Store in original container. Keep containers tightly closed in a

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

areas and containers      cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions      :    Protect from humidity and water. Do not allow to dry.

Advice on common storage      :    Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability      :    No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version  
3.0

Revision Date:  
13.02.2023

SDS Number:  
102000030587

Print Date: 03.12.2024  
Date of first issue: 02.10.2018

	to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic effects	300 mg/kg
	Consumers	Skin contact	Long-term systemic effects	300 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version  
3.0

Revision Date:  
13.02.2023

SDS Number:  
102000030587

Print Date: 03.12.2024  
Date of first issue: 02.10.2018

	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Skin contact	Long-term systemic effects	25 mg/kg
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Inhalation	Long-term local effects	11 mg/kg
	Consumers	Ingestion	Long-term systemic effects	11 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing  
Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 140 - 200 °C

Flammability : Combustible Solids

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : No data available

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : No data available

Density : 1.3 - 2.0 g/cm<sup>3</sup>

Relative vapour density : No data available

Particle Size Distribution :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 03.12.2024
3.0	13.02.2023	102000030587	Date of first issue: 02.10.2018

---

### 9.2 Other information

Explosives	:	Not explosive
Self-ignition	:	not auto-flammable
Miscibility with water	:	immiscible

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	Do not allow to dry.  No data available
---------------------	---	---

### 10.5 Incompatible materials

Materials to avoid	:	Acids Bases Oxidizing agents Highly halogenated compounds
--------------------	---	--

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

**aluminium powder (stabilised):**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapour  
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Germ cell mutagenicity-Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Solvent naphtha (petroleum), light arom.:**

Germ cell mutagenicity-Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Carcinogenicity**

Not classified based on available information.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### Components:

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Solvent naphtha (petroleum), light arom.:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

### Components:

#### **Solvent naphtha (petroleum), light arom.:**

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Further information**

#### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Components:**

**Solvent naphtha (petroleum), light arom.:**

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**Components:**

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Additional ecological information : No data available

---

### SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
In accordance with local and national regulations.
- Contaminated packaging : In accordance with local and national regulations.
- 

## SECTION 14: Transport information

### 14.1 UN number or ID number

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.4 Packing group

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

- Remarks : Not classified as dangerous in the meaning of transport regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version 3.0      Revision Date: 13.02.2023      SDS Number: 102000030587      Print Date: 03.12.2024  
Date of first issue: 02.10.2018

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
aluminium powder (stabilised) (Number on list 40)  
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (Number on list 3)  
Solvent naphtha (petroleum), light arom. (Number on list 3)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

#### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H228 : Flammable solid.  
H304 : May be fatal if swallowed and enters airways.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA METALLUX 1580 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 03.12.2024
3.0	13.02.2023	102000030587	Date of first issue: 02.10.2018

---

Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aquatic Chronic 3                      H412

#### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN