



Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

SECTION 1. IDENTIFICATION

Product name Product code	:	SILVERDREAM Starlight 70 IL 007302FX0
Manufacturer or supplier's de	eta	ils
Company name of supplier	:	ECKART America Corporation
Address	:	830 East Erie Street
		Painesville OH 44077
Telephone	:	866-458-7837
		(440) 954-7600
Telefax	:	(440) 354-6224
e-mail adresse	:	info.eckart.america.oh@altana.com
Emergency telephone	:	CHEMTREC: 800-424-9300
		CHEMTREC: 1-703-527-3387 (International)
		NCEC:
		(contract no. ECKART29003-NCEC)
		US: +1 866 928 0789 (Toll free)
		Canada: +1 800 579 7421 (Toll Free)
		Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accord 1910.1200)	dan	ce with the OSHA Hazard Communication Standard (29 CFR
Flammable solids	:	Category 1
Eye irritation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
GHS label elements Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H228 Flammable solid. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET



SILVERDREAM Starlight 70 IL

Version 2.1	Revision Date: 02/21/2024	SDS Number: 102000021521	Date of last issue: 12/05/2019 Date of first issue: 03/21/2018
Preca	autionary Statements	 Prevention: P210 P240 P241 P261 P264 P271 P280 	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Avoid breathing dust. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.
		Response: P304 + P340 + P305 + P351 + P337 + P313 P370 + P378 P370 + P378 Storage: P403 + P233	 P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use for extinction: Special powder for metal fires. In case of fire: Use for extinction: Dry sand. Store in a well-ventilated place. Keep
		P405 Disposal: P501	container tightly closed. Store locked up. Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label: 2-Propanol

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
	0/45	



Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

Aluminum	7429-90-5	>= 70 - < 90
2-Propanol	67-63-0	>= 20 - < 30
Actual concentration is with	ald as a trada assert	

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Take the victim into fresh air. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	Wash off immediately with soap and plenty of water. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Causes serious eye irritation. May cause drowsiness or dizziness.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	Carbon dioxide (CO2) ABC powder Water Foam
Specific hazards during fire fighting	:	Contact with water liberates extremely flammable gas (hydrogen).
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	:	





Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas. Use personal protective equipment. Use personal protective equipment. Avoid dust formation. Remove all sources of ignition.
General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Environmental precautions	:	The product should not be allowed to enter drains, water courses or the soil.
		Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
		Do not flush with water. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.
		Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles.





Version 2.1	Revision Date: 02/21/2024	SDS Number: 102000021521	Date of last issue: 12/05/2019 Date of first issue: 03/21/2018
Cond	litions for safe storage	Avoid contact For personal p Smoking, eatir application are Provide suffici Dispose of ring regulations. Store in origina Keep containe Keep containe	e - obtain special instructions before use. with skin and eyes. rotection see section 8. Ig and drinking should be prohibited in the a. ent air exchange and/or exhaust in work rooms. se water in accordance with local and national
	nical sures/Precautions rials to avoid	Keep containe place. Electrical insta the technologi Protect from he Do not allow to Do not store to Never allow pr storage. Keep away fro	r tightly closed in a dry and well-ventilated llations / working materials must comply with cal safety standards. umidity and water. o dry. gether with oxidizing and self-igniting products. oduct to get in contact with water during m oxidizing agents, strongly alkaline and naterials in order to avoid exothermic reactions.
	er information on ge stability	: No decompos	ition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (respirable	5 mg/m3	OSHA Z-3

A member of **C ALTANA**





Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

		fraction)		1
		TWA	15 Million	OSHA Z-3
		(respirable	particles per cubic	
		fraction)	foot	
		TWA	1 mg/m3	ACGIH
		(Respirable	·	
		particulate		
		matter)		
		TWA	5 mg/m3	NIOSH REL
			(Aluminum)	
		TWA (Total)	15 mg/m3	OSHA P0
			(Aluminum)	
		TWA	5 mg/m3	OSHA P0
		(Respirable	(Aluminum)	
		fraction)		
		TWA (total	15 mg/m3	OSHA Z-1
				USHA Z-1
		dust)	(Aluminum)	
		TWA	5 mg/m3	OSHA Z-1
		(respirable	(Aluminum)	
		fraction)	45 / 0	
		TWA (Total	15 mg/m3	OSHA P0
		dust)	(Aluminum)	
		TWA	5 mg/m3	OSHA P0
		(respirable	(Aluminum)	
		dust fraction)	- / -	
		TWA	5 mg/m3	NIOSH REL
		(welding	(Aluminum)	
		fumes)		
		TWA (pyro	5 mg/m3	NIOSH REL
		powders)	(Aluminum)	
		TWA	1 mg/m3	ACGIH
		(Respirable	(Aluminum)	
		particulate		
		matter)		
		TWA	5 mg/m3	OSHA P0
		(Fumes)		
		TWA	5 mg/m3	OSHA P0
		(powder)	(Aluminum)	
2-Propanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm	NIOSH REL
			980 mg/m3	
				-
		ST	500 ppm	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL

A member of **C ALTANA**





Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

	980 mg/m3	
TWA	400 ppm	OSHA P0
	980 mg/m3	
STEL	500 ppm	OSHA P0
	1,225 mg/m3	

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
2-Propanol	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection :	Use suitable breathing protection if workplace concentration requires. In the case of dust or aerosol formation use respirator with an
Hand protection Material :	approved filter. Solvent-resistant gloves (butyl-rubber)
Remarks :	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection :	Eye wash bottle with pure water Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection :	Long sleeved clothing Safety shoes Choose body protection according to the amount and
	7 / 15 A member of C ALTANA





/ersion 2.1	Revision Date: 02/21/2024	SDS Number: 102000021521	Date of last issue: 12/05/2019 Date of first issue: 03/21/2018
Hygier	ne measures	: When using do When using do	f the dangerous substance at the work place. not eat or drink. not smoke. fore breaks and at the end of workday.
ECTION 9	9. PHYSICAL AND CH	EMICAL PROPERTI	ES
pH Melting	rance Treshold g point/freezing point g point/boiling range	 Pasty solid silver characteristic No data availal substance/mix No data availal 82 °C 	ture is non-soluble (in water)
Flash p	point	: 13 °C	
	ration rate ability (solid, gas)	 No data availal The substance category 1. 	ole or mixture is a flammable solid with the
Upper flamm Lower	lammability explosion limit / Upper ability limit explosion limit / Lower	not auto-flammNo data availalNo data availal	ble
Vapor	ability limit pressure re density y	 No data availal No data availal 1.3 - 2.0 g/cm3 	ble
Wa Partitic octanc	lity(ies) ter solubility on coefficient: n- ol/water nition temperature	: insoluble : No data availal : No data availal	
Decon Viscos	nposition temperature	: No data availal : No data availal	ble

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen.
---	---	--







Version 2.1	Revision Date: 02/21/2024	SDS Number: 102000021521	Date of last issue: 12/05/2019 Date of first issue: 03/21/2018
	itions to avoid npatible materials	Stable under r : Do not allow to Heat, flames a : Acids Bases Oxidizing age	and sparks.
SECTION	11. TOXICOLOGICA	L INFORMATION	
	e toxicity lassified based on ava	ailable information.	
<u>Com</u>	<u>oonents:</u>		
	panol: e oral toxicity	: LD50 (Rat): >2	2,000 mg/kg
Acute	e dermal toxicity	: LD50 (Rabbit):	> 2,000 mg/kg
-	corrosion/irritation lassified based on ava	ailable information.	
	us eye damage/eye es serious eye irritatio		
<u>Com</u>	oonents:		
	panol: t: Eye irritation		
Resp	iratory or skin sensi	tization	
-	sensitization lassified based on ava	ailable information.	
-	iratory sensitization		
	cell mutagenicity lassified based on ava	ailable information.	
	nogenicity lassified based on ava		





rsion	Revision Date: 02/21/2024	SDS Number: 102000021521	Date of last issue: 12/05/2019 Date of first issue: 03/21/2018	
IARC			his product present at levels greater than or dentified as probable, possible or confirmed n by IARC.	
OSH	A	-	this product present at levels greater than or on OSHA's list of regulated carcinogens.	
NTP No ingredient of this product present at levels greater that equal to 0.1% is identified as a known or anticipated carc by NTP.				
-	oductive toxicity assified based on ava	ailable information.		
	-single exposure			
	ause drowsiness or c	lizziness.		
-	<u>oonents:</u>			
	panol: ssment: May cause di	owsiness or dizziness		
STOT	-repeated exposure			
	assified based on ava	ailable information.		
Aspir	ation toxicity			
-	assified based on ava	ailable information.		
Furth	er information			
CTION	12. ECOLOGICAL IN	FORMATION		
	oxicity ata available			
	stence and degradal ata available	bility		
	cumulative potentia ata available	l		
Other	adverse effects			

SAFETY DATA SHEET



SILVERDREAM Starlight 70 IL

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	Send to a licensed waste management company.In accordance with local and national regulations.Empty remaining contents.
	Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR UN/ID/NA number Proper shipping name Class Packing group Labels ERG Code Marine pollutant	UN 1325 Flammable solids, organic, n.o.s. (Aluminum pigment paste) 4.1 II FLAMMABLE SOLID 133 no	
International Regulations		
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passenger aircraft)	UN 1325 Flammable solid, organic, n.o.s. (Aluminium pigment paste) 4.1 II Flammable Solid 448 445	
IMDG-Code UN number Proper shipping name Class Packing group	UN 1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste) 4.1 II	





Version	Revision Date:	SDS Number: 102000021521	Date of last issue: 12/05/2019
2.1	02/21/2024		Date of first issue: 03/21/2018

Labels	:	4.1
EmS Code	:	F-G, S-G
Marine pollutant	:	no
Remarks	:	IMDG Code segregation group 15 - Powdered metals

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aeroso Serious eye damage or ey Specific target organ toxic	e irritation	,
SARA 313	:	The following components established by SARA Title		orting levels
		Aluminum	7429-90-5	>= 70 - < 90 %
		2-Propanol	67-63-0	>= 20 - < 30 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

67-63-0

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

2-Propanol



Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know				
ļ	Aluminum	7429-90-5		
2	2-Propanol	67-63-0		
Pennsylvania Right To Know				
I	Aluminum	7429-90-5		
2	2-Propanol	67-63-0		
ę	9-Octadecenoic acid (9Z)-	112-80-1		

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances Aluminum	7429-90-5
2-Propanol	67-63-0
California Permissible Exposure Limits for Chemical Contaminants Aluminum	7429-90-5
2-Propanol	67-63-0

The ingredients of this product are reported in the following inventories:			
DSL	:	All components of this product are on the Canadian DSL	
TSCA	:	All substances listed as active on the TSCA inventory	



Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviati	ions	
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA PO	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0/TWA	:	8-hour time weighted average
OSHA P0/STEL	:	Short-term exposure limit
OSHA Z-1 / TWA		8-hour time weighted average
OSHA Z-3 / TWA		8-hour time weighted average
AllC - Australian Inventory	of Ir	ndustrial Chemicals; ASTM - American Society for the Testing

ralian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National



Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2019
2.1	02/21/2024	102000021521	Date of first issue: 03/21/2018

Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/21/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8