

STANDART PCA 9155 Aluminium Powder

Version 4.0 Revision Date: 06/26/2024 SDS Number: 102000000285 Date of last issue: 04/10/2024
Date of first issue: 03/21/2018

SECTION 1. IDENTIFICATION

Product name : STANDART PCA 9155 Aluminium Powder
Product code : 049136D60

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation
Address : 830 East Erie Street
Painesville OH 44077
Telephone : 866-458-7837
(440) 954-7600
Telefax : (440) 354-6224
e-mail adresse : info.eckart.america.oh@altana.com
Emergency telephone : **CHEMTREC:** 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC)
US: +1 866 928 0789 (Toll free)
Canada: +1 800 579 7421 (Toll Free)
Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable solids : Category 1

Combustible dust

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H228 Flammable solid.
May form combustible dust concentrations in air.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/
hot surfaces. No smoking.

STANDART PCA 9155 Aluminium Powder

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 4.0 | Revision Date: 06/26/2024 | SDS Number: 102000000285 | Date of last issue: 04/10/2024 Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|---|

| | |
|------|---|
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P280 | Wear protective gloves/ eye protection/ face protection. |

Response:

| | |
|-------------|--|
| P370 + P378 | In case of fire: Use for extinction: Special powder for metal fires. |
| P370 + P378 | In case of fire: Use for extinction: Dry sand. |

Other hazards

None known.

Information concerning particular hazards for human and environment:

Please refer to our website for further important safety instructions for handling aluminium powder:
http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------|-----------|-----------------------|
| Aluminum | 7429-90-5 | >= 70 - < 90 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

| | | |
|-------------------------|---|--|
| General advice | : | Take the victim into fresh air. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended. |
| If inhaled | : | Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. |
| In case of skin contact | : | Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. If on clothes, remove clothes. |
| In case of eye contact | : | Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : None known.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry sand
Special powder against metal fire

Unsuitable extinguishing media : ABC powder
Carbon dioxide (CO₂)
Water
Foam
High volume water jet

Specific hazards during fire fighting : Contact with water liberates extremely flammable gas (hydrogen).

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Evacuate personnel to safe areas.
Avoid dust formation.
Avoid breathing dust.
Remove all sources of ignition.

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Do not use a vacuum cleaner.

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment.
During processing, dust may form explosive mixture in air.
Take measures to prevent the build up of electrostatic charge.
When transferring from one container to another apply earthing measures and use conductive hose material.

Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid creating dust.
Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
Store away from heat.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Earthing of containers and apparatuses is essential.
Reaction with water liberates extremely flammable gas (hydrogen)
Use explosion-proof equipment.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep away from sources of ignition - No smoking.
Keep container closed when not in use.
No smoking.
Keep container tightly closed in a dry and well-ventilated

STANDART PCA 9155 Aluminium Powder

Version 4.0 Revision Date: 06/26/2024 SDS Number: 102000000285 Date of last issue: 04/10/2024
 Date of first issue: 03/21/2018

place.
 Electrical installations / working materials must comply with the technological safety standards.

Technical measures/Precautions : Protect from humidity and water.

Materials to avoid : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : Keep in a dry place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|-------------------------------------|--|-----------|
| Aluminum | 7429-90-5 | TWA (total dust) | 50 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (Respirable) | 5 mg/m ³ | NIOSH REL |
| | | TWA (total dust) | 15 mg/m ³ | OSHA Z-3 |
| | | TWA (total) | 10 mg/m ³ | NIOSH REL |
| | | TWA (respirable fraction) | 5 mg/m ³ | OSHA Z-3 |
| | | TWA (respirable fraction) | 15 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (Respirable particulate matter) | 1 mg/m ³ | ACGIH |
| | | TWA (Aluminum) | 5 mg/m ³ | NIOSH REL |
| | | TWA (Total Aluminum) | 15 mg/m ³ | OSHA P0 |
| | | TWA (Respirable Aluminum) | 5 mg/m ³ | OSHA P0 |

STANDART PCA 9155 Aluminium Powder

Version 4.0 Revision Date: 06/26/2024 SDS Number: 102000000285 Date of last issue: 04/10/2024
 Date of first issue: 03/21/2018

| | | | | |
|--|--|-------------------------------------|---------------------|-----------|
| | | TWA (total dust) | 15 mg/m3 (Aluminum) | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 (Aluminum) | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 (Aluminum) | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 (Aluminum) | OSHA P0 |
| | | TWA (welding fumes) | 5 mg/m3 (Aluminum) | NIOSH REL |
| | | TWA (pyro powders) | 5 mg/m3 (Aluminum) | NIOSH REL |
| | | TWA (Respirable particulate matter) | 1 mg/m3 (Aluminum) | ACGIH |
| | | TWA (Fumes) | 5 mg/m3 | OSHA P0 |
| | | TWA (powder) | 5 mg/m3 (Aluminum) | OSHA P0 |

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 Breathing apparatus with filter.
 P1 filter

Hand protection
 Material : Leather
 Glove length : Long sleeve gloves

Remarks : Leather gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Face-shield
 Tightly fitting safety goggles

Skin and body protection : Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1; Anti-static safety shoes
 Dust impervious protective suit
 Choose body protection according to the amount and

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

Hygiene measures : concentration of the dangerous substance at the work place.
 : When using do not eat or drink.
 : When using do not smoke.
 : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|--|
| Appearance | : | powder |
| Color | : | silver |
| Odor | : | characteristic |
| Odor Threshold | : | No data available |
| pH | : | substance/mixture is non-soluble (in water) |
| Melting point/range | : | > 600 °C |
| Initial boiling point and boiling range | : | No data available |
| Flash point | : | No data available |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | The substance or mixture is a flammable solid with the category 1. |
| | | combustible dust |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | 30 g/m ³ |
| Vapor pressure | : | No data available |
| Relative density | : | No data available |
| Density | : | 2.5 g/cm ³ |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | 340 °C |
| Decomposition temperature | : | No data available |
| Viscosity | : | No data available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | No decomposition if stored and applied as directed. |
| Chemical stability | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | Contact with acids and alkalis may release hydrogen. No decomposition if stored and applied as directed. Dust may form explosive mixture in air. |

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Acids
Bases
Oxidizing agents
Water

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

IATA-DGR

| | |
|--|----------------------------|
| UN/ID No. | : UN 1309 |
| Proper shipping name | : Aluminium powder, coated |
| Class | : 4.1 |
| Packing group | : II |
| Labels | : Flammable Solid |
| Packing instruction (cargo aircraft) | : 448 |
| Packing instruction (passenger aircraft) | : 445 |

IMDG-Code

| | |
|----------------------|--|
| UN number | : UN 1309 |
| Proper shipping name | : ALUMINIUM POWDER, COATED |
| Class | : 4.1 |
| Packing group | : II |
| Labels | : 4.1 |
| EmS Code | : F-G, S-G |
| Marine pollutant | : no |
| Remarks | : IMDG Code segregation group 15 - Powdered metals |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| | | |
|-----------------------------|---|---|
| SARA 311/312 Hazards | : | Combustible dust Flammable (gases, aerosols, liquids, or solids) |
|-----------------------------|---|---|

| | | |
|-----------------|---|--|
| SARA 313 | : | The following components are subject to reporting levels established by SARA Title III, Section 313: |
|-----------------|---|--|

| | | |
|----------|-----------|----------------|
| Aluminum | 7429-90-5 | >= 70 - < 90 % |
|----------|-----------|----------------|

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

| | |
|----------|-----------|
| Aluminum | 7429-90-5 |
|----------|-----------|

Pennsylvania Right To Know

| | |
|----------|-----------|
| Aluminum | 7429-90-5 |
|----------|-----------|

| | |
|-----------------------------------|--------------|
| Kein gefährlicher Stoff laut GHS. | Not Assigned |
|-----------------------------------|--------------|

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

| | |
|----------|-----------|
| Aluminum | 7429-90-5 |
|----------|-----------|

California Permissible Exposure Limits for Chemical Contaminants

| | |
|----------|-----------|
| Aluminum | 7429-90-5 |
|----------|-----------|

The ingredients of this product are reported in the following inventories:

| | | |
|------|---|--|
| DSL | : | All components of this product are on the Canadian DSL |
| TSCA | : | All chemical substances in this product are either listed as |

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

| | | |
|-----------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA P0 | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |
| OSHA Z-3 / TWA | : | 8-hour time weighted average |

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for

STANDART PCA 9155 Aluminium Powder

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 04/10/2024 |
| 4.0 | 06/26/2024 | 102000000285 | Date of first issue: 03/21/2018 |

Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/26/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8