

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STANDART PCU 2000 Aluminium Powder  
Material number : 041242D60

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guntersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)  
Responsible/issuing person

#### 1.4 Emergency telephone number

**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

### SECTION 2: Hazards identification

**GHS Classification**

: Flammable solids, Category 1, H228

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

### Information concerning particular hazards for human and environment:

Please refer to our website for further important safety instructions for handling aluminium powder:  
[http://www.eckart.net/fileadmin/eckart/Service/GDA\\_Alupulver\\_Safety\\_engl.pdf](http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf)

### GHS-Labeling

Symbol(s) : 

Signal word : Danger

Hazard statements : H228: Flammable solid.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.  
P370 + P378 In case of fire: Use for extinction: Dry sand.

**Hazardous components which must be listed on the label**

## SECTION 3: Composition/information on ingredients

Substance No. :

**Hazardous components**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO<sub>2</sub>), Water, Foam**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Use personal protective equipment.  
Evacuate personnel to safe areas.  
Avoid dust formation.  
Remove all sources of ignition.**6.2 Environmental precautions**

General advice : The product should not be allowed to enter drains, water

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

courses or the soil.  
 Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform  
 respective authorities.

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
 Do not use a vacuum cleaner.  
 Contain spillage, and then collect with an electrically protected  
 vacuum cleaner or by wet-brushing and place in container for  
 disposal according to local regulations (see section 13).  
 Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage**
**7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be  
 instituted to ensure that dusts do not accumulate on surfaces.  
 Store away from heat.

For personal protection see section 8. Smoking, eating and  
 drinking should be prohibited in the application area. Open  
 drum carefully as content may be under pressure. Dispose of  
 rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Use explosion-proof equipment. During processing, dust may  
 form explosive mixture in air. Take measures to prevent the  
 build up of electrostatic charge. When transferring from one  
 container to another apply earthing measures and use  
 conductive hose material.

Provide appropriate exhaust ventilation at places where dust  
 is formed. Keep away from open flames, hot surfaces and

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : Keep in a dry place. No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

### Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
silicon dioxide	7631-86-9	AGW (Inhalable fraction)	4 mg/m <sup>3</sup>	2013-09-19	DE TRGS 900
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
aluminium	7429-90-5	TWA (total)	10 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

aluminium	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	2008-01-01	
aluminium	7429-90-5	TWA	5 mg/m <sup>3</sup>	2005-09-01	
aluminium	7429-90-5	TWA (Total)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (Respirable fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2011-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2011-07-01	
aluminium	7429-90-5	TWA (Total dust)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (welding fumes)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (pyro powders)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	2013-03-01	
aluminium	7429-90-5	TWA (Fumes)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	PEL (Welding fumes)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium	7429-90-5	PEL (Pyro powders)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium	7429-90-5	TWA (powder)	5 mg/m <sup>3</sup>	1989-01-19	
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot	2012-07-01	
silicon dioxide	7631-86-9	TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub>	2012-07-01	
silicon dioxide	7631-86-9	TWA	6 mg/m <sup>3</sup>	2013-10-08	



**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

silicon dioxide	7631-86-9	PEL	6 mg/m <sup>3</sup>	2014-11-26	
-----------------	-----------	-----	---------------------	------------	--

**8.2 Exposure controls**
**Personal protective equipment**

- Eye protection : Face-shield  
: Tightly fitting safety goggles
- Hand protection  
Material : Leather  
Glove length : Long sleeve gloves  
Remarks : Leather gloves  
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.  
: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes.  
: Dust impervious protective suit  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
Breathing apparatus with filter.  
P1 filter

**Environmental exposure controls**

- General advice : The product should not be allowed to enter drains, water courses or the soil.  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Melting point/freezing point	: > 600 °C
Boiling point/boiling range	: No data available
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: The substance or mixture is a flammable solid with the category 1.
Smoldering temperature	: > 230 °C
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: 30 g/m <sup>3</sup>
Vapour pressure	: No data available
Density	: 2,5 g/cm <sup>3</sup> (ca. )
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: 340 °C
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.

**10.5 Incompatible materials**Materials to avoid : Acids  
Bases  
Oxidizing agents  
Water

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

### 10.6 Hazardous decomposition products

Other information : No data available

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

#### Skin corrosion/irritation

No data available

#### Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitisation

No data available

#### Carcinogenicity

No data available

#### Toxicity to reproduction/fertility

No data available

#### Reprod.Tox./Development/Teratogenicity

No data available

#### STOT - single exposure

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

---

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product

No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : No data available

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information****14.1 UN number**

ADR : 1309  
TDG : 1309  
CFR : 1309  
IMDG : 1309  
IATA : 1309

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

**14.2 Proper shipping name**

<b>ADR</b>	: ALUMINIUM POWDER, COATED
<b>TDG</b>	: ALUMINUM POWDER, COATED
<b>CFR</b>	: ALUMINUM POWDER, COATED
<b>IMDG</b>	: ALUMINIUM POWDER, COATED
<b>IATA</b>	: ALUMINIUM POWDER, COATED

**14.3 Transport hazard class**

<b>ADR</b>	: 4.1
<b>TDG</b>	: 4.1
<b>CFR</b>	: 4.1
<b>IMDG</b>	: 4.1
<b>IATA</b>	: 4.1

**14.4 Packing group**

<b>ADR</b>	
Packaging group	: II
Classification Code	: F3
Hazard Identification Number	: 40
Labels	: 4.1
Tunnel restriction code	: (E)

<b>TDG</b>	
Packaging group	: II
Labels	: 4.1

<b>CFR</b>	
Packaging group	: II
Labels	: 4.1

**IMDG**

**STANDART PCU 2000 Aluminium Powder**

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

Packaging group : II  
 Labels : 4.1  
 EmS Code : F-G, S-G

**IATA**

Packing instruction (cargo aircraft) : 448  
 Packing instruction (passenger aircraft) : 445  
 Packing instruction (LQ) : Y441  
 Packaging group : II  
 Labels : 4.1

**14.5 Environmental hazards****14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 15 - Powdered metals

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable  
 REACH - List of substances subject to authorisation (Annex XIV) : Not applicable  
 Regulation (EC) No 1005/2009 on substances that : Not applicable



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STANDART PCU 2000 Aluminium Powder

Version 3.0

Revision Date 26.06.2024

Print Date 02.12.2024

deplete the ozone layer	
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	: Listed (aluminium powder (stabilised))
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (aluminium powder (stabilised))

### 15.2 Chemical safety assessment

No data available

## SECTION 16: Other information

### Full text of H-Statements

H228 : Flammable solid.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.