

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: STANDART Porenbeton RO 100 Aluminium Powder
Product code	: 040352F80
Substance name	: aluminium powder (stabilised)
EC-No.	: 231-072-3
Index-No.	: 013-002-00-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) Flammable solids, Category 1 H228: Flammable solid.

Information concerning particular hazards for human and environment:



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

Please refer to our website for further important safety instructions for handling aluminium powder:

http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

2.2 Label elements

Labelling (REGULATION (EC)	No 1272/2008)	
Hazard pictograms :		
Signal word :	Danger	
Hazard statements :	H228	Flammable solid.
Precautionary statements :	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P240	Ground and bond container and receiving equipment.
	P241	Use explosion-proof electrical/ventilating/ lighting equipment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Response:	
	P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
	P370 + P378	In case of fire: Use for extinction: Dry sand.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances		
Substance name	:	aluminium powder (stabilised)
Index-No.	:	013-002-00-1
EC-No.	:	231-072-3
Chemical nature	:	Pigment



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

Components

Chemical name	CAS-No. EC-No. Index-No.	Concentration (% w/w)	M-Factor, SCL, ATE
	Registration number		
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1	>= 50 - <= 100	
	01-2119529243-45		

SECTION 4: First aid measures

4.1 Description of first aid measures			
General advice	: Move the victim to fresh air.		
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.		
If inhaled	 Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. 		
In case of skin contact	: Wash off immediately with soap and plenty of water.		
	If on clothes, remove clothes.		
In case of eye contact	 Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 		
If swallowed	 Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 		

4.2 Most important symptoms and effects, both acute and delayed None known.



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	102000000281	Date of first issue: 02.01.2014

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	
		High volume water jet
5.2 Special hazards arising from Specific hazards during firefighting	the :	
5.3 Advice for firefightersSpecial protective equipment for firefightersFurther information	:	Wear self-contained breathing apparatus for firefighting if necessary. For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

• • •	 ve equipment and emergency procedures Use personal protective equipment. Evacuate personnel to safe areas. Avoid dust formation. Remove all sources of ignition.
6.2 Environmental precautions	
General advice	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment. Do not use a vacuum cleaner.

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	
Advice on safe handling :	Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Store away from heat. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against : fire and explosion	Use explosion-proof equipment. During processing, dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge. When transferring from one container to another apply earthing measures and use conductive hose material. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.
Hygiene measures :	Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	luding any incompatibilities
Requirements for storage : areas and containers	Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
	No smoking. Keep container tightly closed in a dry and well- ventilated place. Electrical installations / working materials must comply with the technological safety standards.



Vers 5.1	ion	Revision Date: 02.04.2024		DS Number: 2000000281	Print Date: 02.12.2024 Date of first issue: 02.01.2014
		information on e conditions	:	Protect from hum	idity and water.
Advice on common storage		:	 Do not store together with oxidizing and self-igniting product Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions 		
		information on e stability	:	Keep in a dry plac No decompositio	ce. n if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
		TWA (Respirable fraction)	4 mg/m3	GB EH40		
		TWA (inhalable dust)	10 mg/m3	GB EH40		
	when samplin MDHS14/4 G respirable, the substance ha concentration inhalable dus any dust will b levels. Some must comply particles of a particular par response that distinguishes and 'respirabl material that of available for of to the fraction definitions an contain comp	er information: For the purposes of these limits, respirable dust and able dust are those fractions of airborne dust which will be collected sampling is undertaken in accordance with the methods described in S14/4 General methods for sampling and gravimetric analysis or rable, thoracic and inhalable aerosols., The COSHH definition of a tance hazardous to health includes dust of any kind when present at a entration in air equal to or greater than 10 mg.m-3 8-hour TWA of able dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that lust will be subject to COSHH if people are exposed to dust above these comply with the appropriate limits., Most industrial dusts contain the appropriate limits., Most industrial dusts contain the soft a wide range of sizes. The behaviour, deposition and fate of any cular particle after entry into the human respiratory system, and the body onse that it elicits, depend on the nature and size of the particle. HSE guishes two size fractions for limit-setting purposes termed 'inhalable' respirable'., Inhalable dust approximates to the fraction of airborne rial that enters the nose and mouth during breathing and is therefore able for deposition in the respiratory tract. Respirable dust approximates a fraction that penetrates to the gas exchange region of the lung. Fuller itions and explanatory material are given in MDHS14/4., Where dusts and explanatory material are given in MDHS14/4., and the inters is listed be complied with., Where no specific short-term exposure limit is listed be complied with., Where no specific short-term exposure limit is listed and the particle with., where no specific short-term exposure limit is listed and the particle with., where no specific short-term exposure limit is listed and the particle with., where no specific short-term exposure limit is listed and the particle with., where no specific short-term exposure limit is listed and the particle with.				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



STANDART Porenbeton RO 100 Aluminium Powder

Version 5.1	Revision Date 02.04.2024					
		a figure three Further inform inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirable material that e available for o to the fraction definitions and contain comp	times the long TWA (Respire dust) nation: For the are those frace g is undertaken eneral method pracic and inhat zardous to hea in air equal to tor 4 mg.m-3 8 be subject to C dusts have bee with the approp wide range of icle after entry it elicits, depet two size fraction e'., Inhalable d enters the nose leposition in the that penetrate d explanatory r onents that have	able purpose ctions of n in ac s for se alable a alth incl or grea 8-hour OSHH en ass priate li sizes. into the ons for lust ap e and r he respi s to th materia ve thei	exposure limit should be use 4 mg/m3 ses of these limits, respirable of airborne dust which will be cordance with the methods ampling and gravimetric ana- terosols., The COSHH defir udes dust of any kind when ater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du igned specific WELs and ex- mits., Most industrial dusts The behaviour, deposition a- te human respiratory system the nature and size of the pa- limit-setting purposes terms proximates to the fraction of nouth during breathing and ratory tract. Respirable dus e gas exchange region of the l are given in MDHS14/4., Mar own assigned WEL, all the o specific short-term expose	GB EH40 e dust and e collected described in alysis or hition of a present at a TWA of s means that ust above these posure to these contain nd fate of any n, and the body article. HSE ed 'inhalable' f airborne is therefore t approximates he lung. Fuller Where dusts e relevant limits
					exposure limit should be use	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	
	Consumers	Oral	Long-term systemic	3.95 mg/kg
			effects	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective	equipment	
Eye/face protection	:	Face-shield
		Tightly fitting safety goggles
Hand protection		
Material	:	Leather
Glove length	:	Long sleeve gloves



Version 5.1	Revision Date: 02.04.2024	SDS Number: 10200000281	Print Date: 02.12.2024 Date of first issue: 02.01.2014			
R	emarks	only depend on and is different f	The choice of an appropriate glove does not its material but also on other quality features from one producer to the other. or a specific workplace should be discussed			
Skin and body protection		 with the producers of the protective gloves. Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes. Dust impervious protective suit Choose body protection according to the amount and 				
Resp	piratory protection	concentration of	the dangerous substance at the work place. eathing protection if workplace concentration			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	powder
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	> 600 °C
Boiling point/boiling range	:	No data available
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	30 g/m3
Flash point	:	No data available
Auto-ignition temperature	:	340 °C
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available

according to Regulation (EC) No. 1907/2006



STANDART Porenbeton RO 100 Aluminium Powder

Version 5.1	Revision Date: 02.04.2024		S Number: 2000000281	Print Date: 02.12.2024 Date of first issue: 02.01.2014
Wate	pility(ies) r solubility pility in other solvents	-	insoluble No data available	e
	ion coefficient: n- ol/water	:	No data available	9
	ur pressure	:	No data available	9
Relat	ive density	: No data available		9
Dens	ity	:	2.5 g/cm3	
Relat	ive vapour density	:	No data available	9
	cle characteristics article Size Distribution	:	No data available	e
	information			

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactio	ns
Hazardous reactions :	Contact with acids and alkalis may release hydrogen.
	No decomposition if stored and applied as directed.
	Dust may form explosive mixture in air.
10.4 Conditions to avoid	
Conditions to avoid :	Heat, flames and sparks.
10.5 Incompatible materials	
Materials to avoid :	Acids Bases Oxidizing agents Water

10.6 Hazardous decomposition products

This information is not available.



Version Revision Date: 5.1 02.04.2024

SDS Number: 10200000281 Print Date: 02.12.2024 Date of first issue: 02.01.2014

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	LC50 (Rat): > 888 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

11.2 Information on other hazards

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability No data available

12.3 Bioaccumulative potential No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological : No data available information

:

SECTION 13: Disposal considerations

European Waste Catalogue	:	10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances
13.1 Waste treatment methods Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.



Version 5.1	Revision Date: 02.04.2024		OS Number: 2000000281	Print Date: 02.12.2024 Date of first issue: 02.01.2014	
Conta	taminated packaging :		Empty remaining Dispose of as ur Do not re-use en Do not burn, or u	used product.	
SECTIO	N 14: Transport infor	ma	tion		
14.1 UN r	number or ID number				
ADR		:	UN 1309		
IMDO	3	:	UN 1309		
ΙΑΤΑ	L.	:	UN 1309		
14.2 UN p	proper shipping name				
ADR		:	ALUMINIUM PO	WDER, COATED	
IMDO	3	:	ALUMINIUM PO	WDER, COATED	
ΙΑΤΑ	L.	:	Aluminium powder, coated		
14.3 Tran	sport hazard class(es)				
			Class	Subsidiary risks	
ADR		:	4.1		
IMDO	3	:	4.1		
ΙΑΤΑ		:	4.1		
14.4 Pack	king group				
Class Haza Labe	ing group sification Code rd Identification Number Is el restriction code	: : : : : : : : : : : : : : : : : : : :	II F3 40 4.1 (E)		
Labe	ing group Is Code	:	II 4.1 F-G, S-G IMDG Code seg	regation group 15 - Powdered metals	
Pack aircra Pack	ing instruction (LQ) ing group	:	448 Y441 II 4.1		

according to Regulation (EC) No. 1907/2006



STANDART Porenbeton RO 100 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	102000000281	Date of first issue: 02.01.2014
1474	(Bassangar)		

IATA (Passenger)

Packing instruction	:	445
(passenger aircraft)		
Packing instruction (LQ)	:	Y441
Packing group	:	II
Labels	:	4.1

14.5 Environmental hazards

ADR

Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

:	Conditions of restriction for the following entries should be considered: Number on list 40 aluminium powder (stabilised) (Number on list 40)
:	Not applicable
:	Not applicable
:	Not applicable
:	aluminium powder (stabilised)
:	Not applicable



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

This product is regulated by Regulation (EU) 2019/1148: all aluminium powder (stabilised) suspicious transactions, and significant disappearances and thefts (ANNEX II) should be reported to the relevant national contact point.

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of other abbreviations

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
5.1	02.04.2024	10200000281	Date of first issue: 02.01.2014

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN