according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA ALUPOR RO 550 Aluminium Paste

Product code : 052169VV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

Additional Labelling

EUH210 Safety data sheet available on request.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | ClassificationREGUL | Concentration |
|-------------------------------|---------------------|----------------------|----------------|
| | EC-No. | ATION (EC) No | (% w/w) |
| | Index-No. | 1272/2008 | |
| | Registration number | | |
| aluminium powder (stabilised) | 7429-90-5 | Flam. Sol. 1; H228 | >= 50 - <= 100 |
| | 231-072-3 | | |
| | 013-002-00-1 | | |
| | 01-2119529243-45 | | |
| 2,2' -oxybisethanol | 111-46-6 | Acute Tox. 4; H302 | >= 25 - < 50 |
| | 203-872-2 | Acute toxicity | |
| | 603-140-00-6 | estimate | |
| | 01-2119457857-21 | | |
| | | Acute oral toxicity: | |
| | | 1,120 mg/kg | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

102000000245 Date of first issue: 13.01.2014 5.0 12.02.2023

Immediately flush eye(s) with plenty of water.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid dust formation.

> Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

The product should not be allowed to enter drains, water

courses or the soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

Further information on

storage conditions

: Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

No decomposition if stored and applied as directed.

CAS-No. Value type (Form | Control parameters | Basis

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-NO. | of exposure) | Control parameters | Dasis |
|-------------------------------|-----------|---------------------------|--------------------|---------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m3 | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | ' ' | | | |
| | | | · | |

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

| | | dust) | | |
|---------------------|---|-------|---------------------|---------|
| | Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| 2,2' -oxybisethanol | 111-46-6 | TWA | 23 ppm 101 mg/m3 | GB EH40 |
| | Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-------------------------------|-----------|-----------------|----------------------------|------------|
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 3.72 mg/m3 |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg |
| 2,2' -oxybisethanol | Workers | Inhalation | Long-term local effects | 60 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 43 mg/kg |
| | Consumers | Inhalation | Long-term local effects | 12 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 21 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 44 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m3 |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

| Substance name | Environmental Compartment | Value |
|-------------------------------|------------------------------|-------------|
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| 2,2' -oxybisethanol | Fresh water | 10 mg/l |
| | Marine water | 1 mg/l |
| | Water | 10 mg/l |
| | STP | 199.5 mg/l |
| | Fresh water sediment | 20.9 mg/kg |
| | Soil | 1.53 mg/kg |
| | Marine sediment | 2.09 mg/kg |
| | water (intermittent release) | 10 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection

Eye wash bottle with pure water

nd protection Material

: Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Pasty solid

Colour : silver

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : 146 °C

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Relative density : No data available

Density : No data available

Relative vapour density : No data available

Particle Size Distribution :

9.2 Other information

Explosives : Not explosive

Self-ignition : not auto-flammable

Miscibility with water : immiscible

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

2,2' -oxybisethanol:

Acute oral toxicity : LD50 (Humans): 1,120 mg/kg

Acute toxicity estimate: 1,120 mg/kg

Method: Calculation method

Acute inhalation toxicity : (Rat): > 4.6 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

aluminium powder (stabilised)

(Number on list 40)

2,2' -oxybisethanol (Number on list

3)

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid. H302 : Harmful if swallowed.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Flam. Sol. : Flammable solids

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship;

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR RO 550 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

5.0 12.02.2023 102000000245 Date of first issue: 13.01.2014

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN