according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	: STAI	PA METALLUX 212 Aluminium Paste
Product code	: 0575	05G60M1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	ECKART Suisse SA Route de la Brasserie 2 1963 Vétroz	
Telephone	: +410273454800	
Telefax	: +410273454859	
E-mail address of person responsible for the SDS	: msds.eckart@altana.com	1

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008) Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting Category 3 effects. 2.2 Label elements Labelling (REGULATION (EC) No 1272/2008) Hazard statements : H412 Harmful to aquatic life with long lasting effects. Prevention: Precautionary statements : P273 Avoid release to the environment. Disposal:

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Naphtha (petroleum),	64742-48-9	Asp. Tox. 1; H304	>= 10 - < 20
hydrotreated heavy; Low boiling			
point ydrogen treated naphtha	918-481-9		
	01-2119457273-39		
Solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 10 - < 20
arom.		STOT SE 3; H336	
	918-668-5	(Central nervous	
	01-2119455851-35	system)	
		STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General advice : Move the victim to fresh air. General advice : No hazards which require special first aid measures. If inhaled : If unconscious, place in recovery position and seek medical advice.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version 4.0	Revision Date: 09.01.2023	•	DS Number:)2000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018
			If symptoms pers	ist, call a physician.
In cas	e of skin contact	:	Wash off immedia	ately with soap and plenty of water.
In cas	se of eye contact	:	Immediately flush	eye(s) with plenty of water.
			Remove contact l	enses.
lf swa	llowed	:	Never give anythin	rract clear. or alcoholic beverages. ng by mouth to an unconscious person. ist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 I	Extinguishing media		
	Suitable extinguishing media	:	Dry sand Special powder against metal fire
	Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)
5.2 \$	Special hazards arising from	the	substance or mixture
-	Specific hazards during firefighting		Do not allow run-off from fire fighting to enter drains or water courses.
5.3	5.3 Advice for firefighters		
	-	:	Use personal protective equipment.
			Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

SECTION 6: Accidental release measures

• •	e equipment and emergency procedures Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Avoid dust formation.
6.2 Environmental precautions Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.
	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contai	nment and cleaning up

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
	Sweep up and shovel. Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Advice on protection against fire and explosion	:	Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.
		Normal measures for preventive fire protection.
Hygiene measures	:	General industrial hygiene practice.
7.2 Conditions for safe storage, i		

Requirements for storage : Store in original container. Keep containers tightly closed in a

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Versio 4.0		Revision Date: 09.01.2023		9S Number: 2000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018
areas and containers			cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking. Electrical installations / working materials must comply with the technological safety standards.		
	F unth an 1			0	
-	Further information on storage conditions		:	Protect from num	dity and water. Do not allow to dry.
/	Advice	on common storage	:	Never allow products storage. Keep away from the storage of the st	ther with oxidizing and self-igniting products. uct to get in contact with water during oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.
-		information on stability	:	No decomposition	n if stored and applied as directed.
7.3 S	pecific	end use(s)			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dus when samplir MDHS14/4 G respirable, the substance has concentration inhalable dus any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great tor 4 mg.m-3 8-hour be subject to COSHH dusts have been asses with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appenders the nose and	ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the part r limit-setting purposes terme oproximates to the fraction of mouth during breathing and irratory tract. Respirable dust	e collected described in lysis or nition of a present at a TWA of a means that ust above these posure to these contain nd fate of any n, and the body article. HSE ed 'inhalable' airborne is therefore

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version 4.0	Revision Date: 09.01.2023	SDS Number: 102000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018
	defir cont shou	nitions and explanatory m ain components that hav Ild be complied with., Wh ure three times the long	to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts we their own assigned WEL, all the relevant limits where no specific short-term exposure limit is liste term exposure limit should be used.
		TWA (Respira dust)	able 4 mg/m3 GB EH40
	inhal wher MDF resp subs cond inhal any level mus parti parti resp disti and mate avail to th defin cont shou	able dust are those fractions and explanations and explanation in the subject to CC is. Some dusts have been to comply with the approprices of a wide range of singuishes two size fractions in the nose able for deposition i	purposes of these limits, respirable dust and ctions of airborne dust which will be collected n in accordance with the methods described in s for sampling and gravimetric analysis or lable aerosols., The COSHH definition of a lith includes dust of any kind when present at a or greater than 10 mg.m-3 8-hour TWA of 8-hour TWA of respirable dust. This means that OSHH if people are exposed to dust above these en assigned specific WELs and exposure to these priate limits., Most industrial dusts contain sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body and on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' fust approximates to the fraction of airborne e and mouth during breathing and is therefore he respiratory tract. Respirable dust approximates is to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts we their own assigned WEL, all the relevant limits there no specific short-term exposure limit is liste 1-term exposure limit should be used.

		ang to nogalation	(20) 10. 130//2000.	
Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m3
· ·	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic effects	300 mg/kg
	Consumers	Skin contact	Long-term systemic effects	300 mg/kg

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Versi 4.0	ion Revision Date: 09.01.2023	SDS Nun 10200003		Print Date: 26.11.2024 Date of first issue: 01.10.2018
		Consumers	Inhalation	Long-term systemic 900 mg/m3 effects
	Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic 150 mg/m3 effects
		Workers	Skin cont	act Long-term systemic 25 mg/kg effects
		Consumers	Skin cont	act Long-term systemic 11 mg/kg effects
		Consumers	Inhalation	Long-term systemic 32 mg/m3 effects
		Consumers	Inhalation	Long-term local 11 mg/kg effects
		Consumers	Ingestion	Long-term systemic 11 mg/kg effects

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection Material	:	Safety glasses Solvent-resistant gloves
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective
Skin and body protection	:	gloves. Long sleeved clothing Safety shoes
Respiratory protection	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place. Use suitable breathing protection if workplace concentration requires.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	Not relevant
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm3
Relative vapour density	:	No data available
Particle characteristics Particle Size Distribution	:	D50 = 54 μm ± 5 μm

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version 4.0	Revision Date: 09.01.2023	SDS Number: 102000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018	
	r information losives	: Not explosive		
Self-ignition		: not auto-flamm	nable	
Miscibility with water		: immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reaction	ons
Hazardous reactions :	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.
10.4 Conditions to avoid	
Conditions to avoid :	Do not allow to dry.
	No data available
10.5 Incompatible materials	
Materials to avoid :	Acids Bases Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

rsion)	Revision Date: 09.01.2023	SDS Number: 102000030593			
Acute inhalation toxicity		: LC50 (Rat Exposure Test atmos			
-	tha (petroleum), hyd e oral toxicity	-	Low boiling point ydrogen treated naphtha:): > 5,000 mg/kg		
Acute	inhalation toxicity	Remarks: because n	: LC50 (Rat): Test atmosphere: vapour Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.		
Acute	e dermal toxicity	: LD50 (Rab	bit): > 5,000 mg/kg		
	ent naphtha (petroleu oral toxicity): 3,492 mg/kg		
Acute	e dermal toxicity	: LD50 (Rab	bit): > 3,160 mg/kg		
-	corrosion/irritation lassified based on ava	ilable information			
	us eye damage/eye i lassified based on ava				
Resp	iratory or skin sensit	isation			
•••••	sensitisation lassified based on ava	ilable information			
•	iratory sensitisation lassified based on ava	ilable information			
	cell mutagenicity assified based on ava	ilable information			
<u>Com</u>	oonents:				
Germ	tha (petroleum), hyd cell mutagenicity- ssment	: Classified	Low boiling point ydrogen treated naphtha: based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
Germ	ent naphtha (petroleu cell mutagenicity- ssment	: Classified	based on benzene content < 0.1% (Regulation (EC Annex VI, Part 3, Note P)		
Carci	nogenicity				

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

ersion .0	Revision Date: 09.01.2023	SDS Number: 102000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018
<u>Com</u>	oonents:		
Carcii	tha (petroleum), hyd nogenicity - ssment	: Classified base	v boiling point ydrogen treated naphtha: ed on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P)
	ent naphtha (petrole		
	nogenicity - ssment		ed on benzene content < 0.1% (Regulation (EC nex VI, Part 3, Note P)
-	oductive toxicity lassified based on av	ailable information.	
	- single exposure lassified based on av	ailable information.	
<u>Com</u>	oonents:		
	e nt naphtha (petrole ssment		piratory irritation., May cause drowsiness or
	- repeated exposur lassified based on av		
-	ation toxicity lassified based on av	ailable information.	
<u>Com</u>	oonents:		
-	tha (petroleum), hyd oe fatal if swallowed a	• •	v boiling point ydrogen treated naphtha:
	ent naphtha (petrole be fatal if swallowed a		
1.2 Infor	mation on other haz	ards	
Furth	er information		
Prod	uct:		
<u>1100</u>			

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

SECTION 12: Ecological information

12.1 Toxicity

Components:

Solvent naphtha (petroleum), light arom .:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

Components:

Naphtha (petroleum),	hydrotreated	heavy; Low boiling point ydrogen treated naphtha:
Additional ecological	: No	o data available
information		

SECTION 13: Disposal considerations

European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles
European Waste Catalogue	:	10 03 21 - other particulates and dust (including ball-mill dust)
		containing hazardous substances

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version 4.0	Revision Date: 09.01.2023		S Number: 2000030593	Print Date: 26.11.2024 Date of first issue: 01.10.2018		
3.1 Wast Produ	e treatment method : uct	s	courses or the			
Contaminated packaging		:	In accordance with local and national regulations. In accordance with local and national regulations.			
SECTIO	N 14: Transport inf	ormat	ion			
4.1 UN n	umber or ID number					
ADR		:	Not regulated a	as a dangerous good		
IMDG	ì	:	Not regulated a	as a dangerous good		
ΙΑΤΑ		:	Not regulated a	as a dangerous good		
4.2 UN p	roper shipping nam	e				
ADR		:	Not regulated a	as a dangerous good		
IMDG	ì	:	Not regulated a	as a dangerous good		
ΙΑΤΑ		:	Not regulated a	as a dangerous good		
14.3 Trans	sport hazard class(e	s)				
ADR		:	Not regulated a	as a dangerous good		
IMDG	ì	:	Not regulated a	as a dangerous good		
ΙΑΤΑ		:	Not regulated a	as a dangerous good		
14.4 Pack	ing group					
ADR		:	Not regulated a	as a dangerous good		
IMDG	ì	:	Not regulated a	as a dangerous good		
ΙΑΤΑ	(Cargo)	:	Not regulated a	as a dangerous good		
ΙΑΤΑ	(Passenger)	:	Not regulated a	as a dangerous good		
	ronmental hazards egulated as a dangerd	ous goo	od			
14.6 Spec Rema	arks	iser :	Not classified a regulations.	as dangerous in the meaning of transport		

14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha (Number on list 3) Solvent naphtha (petroleum), light arom. (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226 H228 H304 H335 H336 H411	:	Flammable liquid and vapour. Flammable solid. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.			
Full text of other abbreviations					
Aquatic Chronic Asp. Tox. Flam. Liq. Flam. Sol. STOT SE GB EH40		Long-term (chronic) aquatic hazard Aspiration hazard Flammable liquids Flammable solids Specific target organ toxicity - single exposure UK. EH40 WEL - Workplace Exposure Limits			
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -



STAPA METALLUX 212 Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
4.0	09.01.2023	102000030593	Date of first issue: 01.10.2018

Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture:

H412

Aquatic Chronic 3

Classification procedure:	
Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN