

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

SECTION 1. IDENTIFICATION

Product name : METALSTAR HEATSET 05-4873 GOLD
Product code : 046745A30

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation
Address : 830 East Erie Street
Painesville OH 44077
Telephone : 866-458-7837
(440) 954-7600
Telefax : (440) 354-6224
e-mail adresse : info.eckart.america.oh@altana.com
Emergency telephone : **CHEMTREC:** 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC)
US: +1 866 928 0789 (Toll free)
Canada: +1 800 579 7421 (Toll Free)
Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Oral) : Category 4
Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal Word : Warning
Hazard Statements : H302 Harmful if swallowed.
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

P280 product.
Wear eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

Copper

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Copper	7440-50-8	≥ 20 - < 30
Linseed oil	8001-26-1	≥ 10 - < 20
White mineral oil (petroleum)	8042-47-5	≥ 5 - < 10
Zinc	7440-66-6	≥ 5 - < 10
Distillates (petroleum), hydrotreated light	64742-47-8	≥ 5 - < 10
Castor oil, oxidized	68187-84-8	≥ 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Take the victim into fresh air. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.
If inhaled	: Symptoms of poisoning may appear several hours later. If unconscious, place in recovery position and seek medical advice.

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

In case of skin contact	:	If symptoms persist, call a physician. Wash off immediately with soap and plenty of water.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Harmful if swallowed. Causes serious eye irritation.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Special powder against metal fire Dry sand ABC powder
Unsuitable extinguishing media	:	Water High volume water jet Carbon dioxide (CO ₂)
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Ensure adequate ventilation.
General advice	:	The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

- Environmental precautions : respective authorities.
The product should not be allowed to enter drains, water courses or the soil.
- Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for : Use mechanical handling equipment.
containment and cleaning up
- Pick up and transfer to properly labeled containers.
Do not flush with water.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against : Keep away from heat and sources of ignition.
fire and explosion No smoking.
- Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep away from sources of ignition - No smoking.
Do not store near combustible materials.
Keep containers tightly closed in a cool, well-ventilated place.
To maintain product quality, do not store in heat or direct sunlight.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Electrical installations / working materials must comply with the technological safety standards.

Technical measures/Precautions : Protect from humidity and water.

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Copper	7440-50-8	TWA	1 mg/m3 (Copper)	ACGIH
		TWA (dust and mists)	1 mg/m3 (Copper)	NIOSH REL
		TWA	1 mg/m3 (Copper)	OSHA P0
		TWA	0.2 mg/m3 (Copper)	ACGIH
		TWA	0.1 mg/m3 (Copper)	OSHA P0
		TWA (Dust and mist)	1 mg/m3 (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m3 (Copper)	ACGIH
		TWA (Dust)	1 mg/m3 (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m3 (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m3 (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3 (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3 (Copper)	OSHA P0
		TWA (Dust and mist)	1 mg/m3 (Copper)	OSHA P0
Linseed oil	8001-26-1	TWA (mist -	10 mg/m3	NIOSH REL

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

		total)		
		TWA (mist - respirable)	5 mg/m3	NIOSH REL
White mineral oil (petroleum)	8042-47-5	TWA	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Zinc	7440-66-6	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Castor oil, oxidized	68187-84-8	TWA (mist - total)	10 mg/m3	NIOSH REL
		TWA (mist - respirable)	5 mg/m3	NIOSH REL

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Remarks	: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Safety glasses Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: General industrial hygiene practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: gold
Odor	: characteristic
Odor Threshold	: No data available
pH	: substance/mixture is non-soluble (in water)
Melting point/freezing point	: No data available
Boiling point/boiling range	: > 100 °C
Flash point	: > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Relative density	:	No data available
Density	:	1.4 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 21 mm ² /s (40 °C)
Total Volatile organic compounds (VOC) content	:	10.00 - 20.00 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No decomposition if stored and applied as directed.
Conditions to avoid	:	Do not allow evaporation to dryness. No data available

Hazardous decomposition products

Thermal decomposition	:	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
-----------------------	---	--

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if swallowed.

Components:**Copper:**

Acute oral toxicity	:	Assessment: The component/mixture is moderately toxic after single ingestion.
---------------------	---	---

Zinc:

Acute oral toxicity	:	(Rat): > 2,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 5.41 mg/l Exposure time: 4 h

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Components:**Copper:**

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Copper:**

Result: Eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light:**

May be fatal if swallowed and enters airways.

Further information**Components:****Copper:**

Remarks: No data available

Zinc:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Copper:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Zinc:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:**Copper:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

White mineral oil (petroleum):

Additional ecological information : No data available

Zinc:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. In accordance with local and national regulations.

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

IATA-DGR

UN/ID No.	: UN 3082
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (Copper metal powder)
Class	: 9
Packing group	: III
Labels	: Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

IMDG-Code

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper metal powder)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Remarks : For single packagings $\leq 5\text{L} / 5\text{ kg}$, or combination packagings containing inner packagings $\leq 5\text{L} / 5\text{ kg}$ net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)
------------	---------	--------------------

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Copper	7440-50-8	5000
Zinc	7440-66-6	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Copper	7440-50-8	>= 20 - < 30 %
Zinc	7440-66-6	>= 5 - < 10 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

White mineral oil (petroleum)	8042-47-5	>= 5 - < 10 %
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10 %

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Copper	7440-50-8	28.0437 %
Zinc	7440-66-6	6.37 %

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Copper	7440-50-8	28.0437 %
--------	-----------	-----------

METALSTAR HEATSET 05-4873 GOLD

Version 4.1	Revision Date: 03/25/2025	SDS Number: 102000026712	Date of last issue: 06/19/2024 Date of first issue: 03/26/2018
----------------	------------------------------	-----------------------------	---

Zinc	7440-66-6	6.37 %
------	-----------	--------

US State Regulations**Massachusetts Right To Know**

Copper	7440-50-8
White mineral oil (petroleum)	8042-47-5
Zinc	7440-66-6
Distillates (petroleum), hydrotreated light	64742-47-8

Pennsylvania Right To Know

Copper	7440-50-8
Distillates (petroleum), steam-cracked, polymd.	68131-77-1
Linseed oil	8001-26-1
White mineral oil (petroleum)	8042-47-5
Kein gefährlicher Stoff oder gefährliches Gemisch gemäß dem Global Harmonisierten System (GHS).	Not Assigned
Zinc	7440-66-6
Distillates (petroleum), hydrotreated light	64742-47-8
Soybean oil	8001-22-7
Castor oil, oxidized	68187-84-8
Aluminum	7429-90-5

California Prop. 65

WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



WARNING: This product can expose you to chemicals including Distillates (petroleum), hydrotreated light, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Copper	7440-50-8
--------	-----------

METALSTAR HEATSET 05-4873 GOLD

Version 4.1	Revision Date: 03/25/2025	SDS Number: 102000026712	Date of last issue: 06/19/2024 Date of first issue: 03/26/2018
----------------	------------------------------	-----------------------------	---

White mineral oil (petroleum)	8042-47-5
Zinc	7440-66-6
Distillates (petroleum), hydrotreated light	64742-47-8

California Permissible Exposure Limits for Chemical Contaminants

Copper	7440-50-8
Linseed oil	8001-26-1
White mineral oil (petroleum)	8042-47-5
Zinc	7440-66-6
Distillates (petroleum), hydrotreated light	64742-47-8

The ingredients of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
TSCA	: All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
Zinc 7440-66-6

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3

METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/25/2025

SAFETY DATA SHEET



METALSTAR HEATSET 05-4873 GOLD

Version	Revision Date:	SDS Number:	Date of last issue: 06/19/2024
4.1	03/25/2025	102000026712	Date of first issue: 03/26/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8