according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	STANDART PCR 212 Aluminium Powder
Product code	:	000239D70
1.2 Relevant identified uses o Use of the Substance/Mixture	of the s :	ubstance or mixture and uses advised against Colouring agents, pigments
1.3 Details of the supplier of t	the safe	ety data sheet
Company	•	ECKART Suisse SA

Company	: ECKART Suisse SA Route de la Brasserie 2 1963 Vétroz
Telephone	: +410273454800
Telefax	: +410273454859
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)Flammable solids, Category 1H228: Flammable solid.

Information concerning particular hazards for human and environment: Please refer to our website for further important safety instructions for handling aluminium powder:

http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version 3.2	Revision Date: 20.06.2024	-	DS Number: 02000000283	Print Date: 26.11.2024 Date of first issue: 03.01.2014
Hazard pictograms		:		
Sign	al word	:	Danger	
Haza	ard statements	:	H228	Flammable solid.
Prec	autionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P240	Ground and bond container and receiving equipment.
			P241	Use explosion-proof electrical/ventilating/ lighting equipment.
			P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
			Response: P370 + P378	' In case of fire: Use for extinction: Special powder for metal fires.
			P370 + P378	In case of fire: Use for extinction: Dry sand.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 50 - <= 100

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

SECTION 4: First aid measures

4.1 Description of first aid measures					
General advice	:	Move the victim to fresh air.			
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.			
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.			
In case of skin contact	:	Wash off immediately with soap and plenty of water.			
		If on clothes, remove clothes.			
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.			
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.			

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	ABC powder Carbon dioxide (CO2) Water Foam
		High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during	:	Contact with water liberates extremely flammable gas
-------------------------	---	--

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Versi 3.2	ion	Revision Date: 20.06.2024		OS Number: 2000000283	Print Date: 26.11.2024 Date of first issue: 03.01.2014
1	firefigh	ting		(hydrogen).	
;	5.3 Advice for firefighters Special protective equipment for firefighters		:	Wear self-contair necessary.	ned breathing apparatus for firefighting if
Further information		:	For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions Use personal protective equipment. : Evacuate personnel to safe areas. Avoid dust formation. Remove all sources of ignition. 6.2 Environmental precautions General advice The product should not be allowed to enter drains, water : courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. 6.3 Methods and material for containment and cleaning up Methods for cleaning up : Use mechanical handling equipment. Do not use a vacuum cleaner. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid creating dust.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Vers 3.2	sion	Revision Date: 20.06.2024		9S Number: 2000000283	Print Date: 26.11.2024 Date of first issue: 03.01.2014
	Advice on protection against fire and explosion		:	dusts do not accu Store away from H For personal prot Smoking, eating a application area. Open drum carefu Dispose of rinse w regulations. Use explosion-pro form explosive mi build up of electro container to anoth conductive hose r	ection see section 8. and drinking should be prohibited in the ully as content may be under pressure. water in accordance with local and national oof equipment. During processing, dust may ixture in air. Take measures to prevent the ostatic charge. When transferring from one her apply earthing measures and use material. ate exhaust ventilation at places where dust way from open flames, hot surfaces and
	Hygien	e measures	:	C C	pre breaks and at the end of workday.
7.2 (Require	ons for safe storage, ements for storage and containers	incl :	Earthing of conta with water liberate explosion-proof e containers tightly	iners and apparatuses is essential. Reaction es extremely flammable gas (hydrogen) Use equipment. Store in original container. Keep closed in a cool, well-ventilated place. Keep es of ignition - No smoking. Keep container
				No smoking. Kee ventilated place.	p container tightly closed in a dry and well- Electrical installations / working materials the technological safety standards.
		information on e conditions	:	Protect from hum	idity and water.
	Advice	on common storage	:	Never allow production storage. Keep away from the storage of the	ther with oxidizing and self-igniting products. uct to get in contact with water during oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.
		ninformation on e stability	:	Keep in a dry plac No decomposition	ce. n if stored and applied as directed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions and contain comp should be cor	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great tor 4 mg.m-3 8-hour be subject to COSHH dusts have been ass with the appropriate wide range of sizes. ticle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appendent that penetrates to the deposition in the resp that penetrates to the dexplanatory material onents that have the mplied with., Where r	ses of these limits, respirable of airborne dust which will be ccordance with the methods sampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition a he human respiratory system the nature and size of the pa- r limit-setting purposes terme oproximates to the fraction of mouth during breathing and biratory tract. Respirable dus he gas exchange region of the al are given in MDHS14/4., N ir own assigned WEL, all the no specific short-term exposi- exposure limit should be use 4 mg/m3	e collected described in lysis or nition of a present at a TWA of s means that ust above these posure to these contain nd fate of any n, and the body article. HSE ed 'inhalable' airborne is therefore t approximates he lung. Fuller Where dusts e relevant limits ure limit is listed,
	Further inform	dust)	ses of these limits, respirable	e dust and
	inhalable dust when samplin MDHS14/4 G respirable, the substance has concentration inhalable dust any dust will b	t are those fractions of is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or gre t or 4 mg.m-3 8-hour be subject to COSH	of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This I if people are exposed to dus signed specific WELs and ex	e collected described in lysis or nition of a present at a TWA of s means that ust above these

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version Revision Dat 3.2 20.06.2024				int Date: 26.11.2024 ate of first issue: 03.01.2014	
		particles of a particular part response that distinguishes and 'respirable material that e available for d to the fraction definitions and contain comp should be com	wide range of sizes. icle after entry into t it elicits, depend on two size fractions for e'., Inhalable dust ap enters the nose and leposition in the resp that penetrates to the d explanatory materi onents that have the nplied with., Where	limits., Most industrial dusts The behaviour, deposition he human respiratory syste the nature and size of the p or limit-setting purposes term oproximates to the fraction of mouth during breathing and biratory tract. Respirable due he gas exchange region of t al are given in MDHS14/4., fir own assigned WEL, all the no specific short-term exposi- exposure limit should be us	and fate of any m, and the body particle. HSE ned 'inhalable' of airborne is therefore st approximates he lung. Fuller Where dusts e relevant limits sure limit is listed,
silicor	n dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some of must comply of particles of a v particular part response that distinguishes and 'respirable material that e available for d to the fraction definitions and contain comp should be com	are those fractions ig is undertaken in a eneral methods for s pracic and inhalable zardous to health ind in air equal to or great or 4 mg.m-3 8-hour be subject to COSHF dusts have been as with the appropriate wide range of sizes. icle after entry into t it elicits, depend on two size fractions for e'., Inhalable dust appropriate that penetrates to the that penetrates to the constition in the resp that penetrates to the dexplanatory matering onents that have the inplied with., Where	bses of these limits, respirab of airborne dust which will b ccordance with the methods sampling and gravimetric an aerosols., The COSHH def cludes dust of any kind when eater than 10 mg.m-3 8-hou TWA of respirable dust. The dif people are exposed to d signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition he human respiratory syste the nature and size of the p or limit-setting purposes term oproximates to the fraction of mouth during breathing and biratory tract. Respirable dur- ne gas exchange region of t al are given in MDHS14/4., fr own assigned WEL, all the no specific short-term expose exposure limit should be us 2.4 mg/m3	be collected s described in alysis or inition of a n present at a r TWA of is means that lust above these scontain and fate of any m, and the body barticle. HSE ned 'inhalable' of airborne is therefore st approximates the lung. Fuller Where dusts e relevant limits sure limit is listed,
		Further inform	dust)	Sees of these limits, respirab	
		inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some	are those fractions of is undertaken in a eneral methods for so pracic and inhalable zardous to health ind in air equal to or great or 4 mg.m-3 8-hou be subject to COSH dusts have been as	of airborne dust which will b ccordance with the methods sampling and gravimetric an aerosols., The COSHH def cludes dust of any kind where eater than 10 mg.m-3 8-hou TWA of respirable dust. The H if people are exposed to de signed specific WELs and ex- limits., Most industrial dusts	be collected a described in alysis or inition of a n present at a r TWA of is means that lust above these xposure to these

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date: 20.06.2024	SDS Number:	Print Date: 26.11.2024
3.2		102000000283	Date of first issue: 03.01.2014
	partic respo distin and 'r mater availa to the defini conta shoul	ular particle after entry nse that it elicits, depending guishes two size fracti espirable'., Inhalable of ial that enters the nose ble for deposition in the fraction that penetrate tions and explanatory in components that ha d be complied with., W	sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body end on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' dust approximates to the fraction of airborne e and mouth during breathing and is therefore he respiratory tract. Respirable dust approximates as to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts ve their own assigned WEL, all the relevant limits /here no specific short-term exposure limit is listed, g-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment							
Eye/face protection	Face-shield						
Lland protection	Tightly fitting safety goggles						
Hand protection							
	Leather						
Glove length	Long sleeve gloves						
Remarks	 Leather gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The suitability for a specific workplace should be discussed with the producers of the protective gloves. 						
Skin and body protection	 Anti-static and fire resistant protective clothing. DIN EN 11612; EN 533; EN 1149-1. Anti-static safety shoes. Dust impervious protective suit Choose body protection according to the amount and concentration of the dangerous substance at the work place. 						
Respiratory protection	Use suitable breathing protection if workplace concentration requires. Breathing apparatus with filter.						

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Versio 3.2	n Revision Date: 20.06.2024		S Number: 000000283	Print Date: 26.11.2024 Date of first issue: 03.01.2014					
			P1 filter						
SECT	SECTION 9: Physical and chemical properties								
9.1 Inf	formation on basic physica	ıl an	d chemical prope	erties					
F	orm	:	powder						
С	olour	:	silver						
0	dour	:	characteristic						
0	dour Threshold	:	No data available	9					
Μ	lelting point/range	:	> 600 °C						
В	oiling point/boiling range	:	No data available	9					
F	lammability	:	The substance o category 1.	r mixture is a flammable solid with the					
	pper explosion limit / Upper ammability limit	:	No data available	9					
	ower explosion limit / Lower ammability limit	:	30 g/m3						
F	lash point	:	No data available	9					
A	uto-ignition temperature	:	340 °C						
D	ecomposition temperature	:	No data available	9					
р	н	:	substance/mixtu	re is non-soluble (in water)					
V	iscosity, kinematic	:	No data available	9					
V	olubility(ies) /ater solubility olubility in other solvents	:	insoluble No data available	9					
0	artition coefficient: n- ctanol/water apour pressure	:	No data available						
	elative density	•	No data available						
	vensity		2.5 g/cm3	-					
	elative vapour density		No data available	2					
		•		·					

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

Particle characteristics Particle Size Distribution : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Contact with acids and alkalis may release hydrogen.
		No decomposition if stored and applied as directed.
		Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid

: Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid

: Acids Bases Oxidizing agents Water

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological	•	No data available
information		

SECTION 13: Disposal considerations

European Waste Catalogue	:	10 03 21* - Aluminum thermal metallurgy wastes, other particles and dust (including ball mill dust) containing hazardous substances
13.1 Waste treatment methods		
Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADK	•	014 1309
IMDG	:	UN 1309
ΙΑΤΑ	:	UN 1309

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version 3.2	Revision Date: 20.06.2024		OS Number: 2000000283	Print Date: 26.11.2024 Date of first issue: 03.01.2014
ADR			ALUMINIUM	POWDER, COATED
IMDG	ì	: ALUMINIUM POWDER, COATED		
IATA		:	Aluminium po	
14.3 Tran	sport hazard class(es)			
			Class	Subsidiary risks
ADR			4.1	
IMDG	ì	•	4.1	
ΙΑΤΑ		:	4.1	
	ing group			
ADR				
Pack Class Haza Label	ing group ification Code rd Identification Number s el restriction code	:	II F3 40 4.1 (E)	
Label	ing group s Code	:	ll 4.1 F-G, S-G IMDG Code s	egregation group 15 - Powdered metals
	(Cargo) ing instruction (cargo ft)	:	448	
	ing instruction (LQ) ing group	:	Y441 II 4.1	
IATA Packi (pass Packi	(Passenger) ing instruction enger aircraft) ing instruction (LQ) ing group	:	445 Y441 II	
Label	S	:	4.1	
14.5 Envi	ronmental hazards			
ADR Envir	onmentally hazardous	:	no	
IMDG Marin	e pollutant	:	no	

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	aluminium powder (stabilised)
UK REACH List of substances subject to authorisation	:	Not applicable
(Annex XIV) Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		
This product is regulated by Regulation (EU) 2019/1148: suspicious transactions, and significant disappearances a		aluminium powder (stabilised) thefts (ANNEX II)

should be reported to the relevant national contact point.

15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

SECTION 16: Other information

Flammable solid.
;
Flammable solids
UK. EH40 WEL - Workplace Exposure Limits
Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by



Commission Regulation (EU) 2020/878

STANDART PCR 212 Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 26.11.2024
3.2	20.06.2024	10200000283	Date of first issue: 03.01.2014

Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information Classification of the mixture:

H228

Classification procedure:

Flam. Sol. 1

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN