

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SILVERSHINE S 1100  
Product code : 052491JD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Coloring agents, pigments

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART Suisse SA  
Route de la Brasserie 2  
1963 Vétroz  
Telephone : +410273454800  
Telefax : +410273454859  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard,	H411: Toxic to aquatic life with long lasting effects.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

Category 2

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H226      Flammable liquid and vapor. H304      May be fatal if swallowed and enters airways. H335      May cause respiratory irritation. H336      May cause drowsiness or dizziness. H411      Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066      Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273      Avoid release to the environment. <b>Response:</b> P301 + P310      IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331      Do NOT induce vomiting. P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391      Collect spillage.

#### Hazardous ingredients which must be listed on the label:

Solvent naphtha (petroleum), light arom.  
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
---------------	---------	---------------------	---------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

	EC-No. Index-No. Registration number	ATION (EC) No 1272/2008	(% w/w)
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5  01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 50
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1  01-2119529243-45	Flam. Sol. 1; H228 Note T	>= 25 - < 50
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 918-481-9  01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 10 - < 20

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Take the victim into fresh air.  
Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)  
  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

Use personal protective equipment.  
Remove all sources of ignition.  
Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.

### 6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.  
Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : Wash hands before breaks and at the end of workday.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

	<p>particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
	<table border="1"> <tr> <td>TWA (Respirable dust)</td> <td>4 mg/m<sup>3</sup></td> <td>GB EH40</td> </tr> </table>	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40		
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	837.5 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1286.4 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	1066.67 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	12.5 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version  
5.1

Revision Date:  
24.02.2026

SDS Number:  
102000002374

Print Date: 26.02.2026  
Date of first issue: 03.01.2014

	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Inhalation	Long-term local effects	178.57 mg/m3
	Consumers	Inhalation	Acute systemic effects	1152 mg/m3
	Consumers	Inhalation	Acute local effects	640 mg/m3
	Consumers	Dermal	Long-term systemic effects	7.5 mg/kg
	Consumers	Dermal	Acute systemic effects	11 mg/kg
	Consumers	Oral	Long-term systemic effects	7.5 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	Workers	Inhalation	Acute systemic effects	1500 mg/m3
	Workers	Dermal	Long-term systemic effects	300 mg/kg
	Consumers	Oral	Long-term systemic effects	300 mg/kg
	Consumers	Dermal	Long-term systemic effects	300 mg/kg
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Tightly fitting safety goggles  
Hand protection : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use suitable breathing protection if workplace concentration requires.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Form	:	liquid
Color	:	silver
Odor	:	characteristic
Odor Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	140 - 200 °C
Flammability	:	No data available
Flammability (liquids)	:	Flammable liquids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	41 °C
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : No data available

Flow time : > 100 s  
Cross section: 6 mm  
Method: ISO 2431

Solubility(ies)  
Water solubility : insoluble  
Solubility in other solvents : No data available

Partition coefficient: n-  
octanol/water : No data available  
Vapor pressure : No data available

Vapor Pressure for Components:  
Solvent naphtha : 2 hPa (20 °C)  
(petroleum), light arom.  
Naphtha (petroleum), : 0.05 kPa (20 °C)  
hydrotreated heavy; Low  
boiling point ydrogen  
treated naphtha

Relative density : No data available

Density : 1.3 - 2.0 g/cm<sup>3</sup>

Relative vapor density : No data available

### Particle characteristics

Particle Size Distribution : No data available

### 9.2 Other information

Explosives : Not explosive

Self-ignition : not auto-flammable

Miscibility with water : immiscible

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapor/air-mixtures are explosive at intense warming.  
No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.  
  
No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Components:

##### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

##### **aluminium powder (stabilised):**

Acute inhalation toxicity :

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapor  
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

Acute dermal toxicity                   : LD50 (Rabbit): > 5,000 mg/kg

### Skin corrosion/irritation

#### Components:

##### **Solvent naphtha (petroleum), light arom.:**

Result                                   : Repeated exposure may cause skin dryness or cracking.

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Result                                   : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

#### Product:

Remarks                               : Product dust may be irritating to eyes, skin and respiratory system.

### Germ cell mutagenicity

#### Components:

##### **Solvent naphtha (petroleum), light arom.:**

Germ cell mutagenicity-  
Assessment                           : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Germ cell mutagenicity-  
Assessment                           : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

#### Components:

##### **Solvent naphtha (petroleum), light arom.:**

Carcinogenicity -  
Assessment                           : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Carcinogenicity -  
Assessment                           : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

### STOT-single exposure

#### Components:

#### **Solvent naphtha (petroleum), light arom.:**

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

### Aspiration toxicity

#### Components:

#### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **Solvent naphtha (petroleum), light arom.:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

**Components:**

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalog : 10 03 21\* - Waste from thermal aluminium metallurgy, other particles and dust (including ball mill dust) containing hazardous substances.

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1263

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version 5.1      Revision Date: 24.02.2026      SDS Number: 102000002374      Print Date: 26.02.2026  
Date of first issue: 03.01.2014

---

**IMDG** : UN 1263  
**IATA** : UN 1263

### 14.2 UN proper shipping name

**ADR** : PAINT  
**IMDG** : PAINT  
(Solvent naphtha)  
**IATA** : Paint

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADR</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered:  Number on list 3 Banned and/or restricted
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

### 15.2 Chemical Safety Assessment

No data available

---

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapor.
H228	:	Flammable solid.
H304	:	May be fatal if swallowed and enters airways.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

### Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
Note T	:	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3.
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336

#### Classification procedure:

Based on product data or assessment
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## SILVERSHINE S 1100

Version	Revision Date:	SDS Number:	Print Date: 26.02.2026
5.1	24.02.2026	102000002374	Date of first issue: 03.01.2014

---

STOT SE 3	H335	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN