

ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

SECTION 1. IDENTIFICATION

Product name : ROTOSTAR UV FX 68-41002 SRNK SILVER US

Product code : 045641ER0

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation

Address : 830 East Erie Street

Painesville OH 44077

Telephone : 866-458-7837

(440) 954-7600

Telefax : (440) 354-6224

e-mail adresse : info.eckart.america.oh@altana.com

Emergency telephone : **CHEMTREC**: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be

allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 Take off contaminated clothing and wash

before reuse.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label:

2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester

Low viscosity acrylic oligomer

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
2-Propenoic acid, (5-ethyl-1,3-dioxan-5-	66492-51-1	>= 30 - < 50
yl)methyl ester		
Low viscosity acrylic oligomer	Not Assigned	>= 30 - < 50
Aluminum	7429-90-5	>= 5 - < 10



ROTOSTAR UV FX 68-41002 SRNK SILVER US

Version Revision Date: SDS Number: Date of last issue: 03/01/2023 6.0 11/06/2024 102000027050 Date of first issue: 03/26/2018

ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate	84434-11-7	>= 5 - < 10
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega[(1-oxo-2-propen-1-yl)oxy]-	52408-84-1	>= 1 - < 5
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate	55818-57-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice Take the victim into fresh air.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

If inhaled If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Wash off immediately with soap and plenty of water. In case of skin contact

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

Causes skin irritation.

and effects, both acute and

May cause an allergic skin reaction.

delayed Causes serious eye damage.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Dry sand

ABC powder

Foam

courses.

Unsuitable extinguishing

media

High volume water jet

Carbon dioxide (CO2)

Specific hazards during fire

Do not allow run-off from fire fighting to enter drains or water

fighting



ROTOSTAR UV FX 68-41002 SRNK SILVER US

Version Revision Date: SDS Number: Date of last issue: 03/01/2023 11/06/2024 6.0 102000027050 Date of first issue: 03/26/2018

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Evacuate personnel to safe areas. Use personal protective equipment.

General advice The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

The product should not be allowed to enter drains, water Environmental precautions

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Earthing of containers and apparatuses is essential.

Reaction with water liberates extremely flammable gas

(hydrogen)

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from sources of ignition - No smoking.

Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Protect from humidity and water.

Electrical installations / working materials must comply with

the technological safety standards.

Technical

measures/Precautions

Materials to avoid

: Do not store near acids.

Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA	5 mg/m3	NIOSH REL



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

I	(Respirable)	Ī	1
	TWA (total	15 mg/m3	OSHA Z-3
	dust)		
	TWA (total)	10 mg/m3	NIOSH REL
	TWA	5 mg/m3	OSHA Z-3
	(respirable fraction)		
	TWA	15 Million	OSHA Z-3
	(respirable fraction)	particles per cubic foot	
	TWA	1 mg/m3	ACGIH
	(Respirable particulate matter)		
	TWA	5 mg/m3 (Aluminum)	NIOSH REL
	TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
	TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
	TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
	TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
	TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
	TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
	TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
	TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
	TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
	TWA (Fumes)	5 mg/m3	OSHA P0
	TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Eye protection : Goggles

Safety glasses

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid Color : silver

Odor : characteristic
Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/range : Not applicable Boiling point/boiling range : > 100 °C

Flash point : > 100 °C

Evaporation rate : No data available Flammability (solid, gas) : No data available Flammability (liquids) : Will not burn



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available Relative density : No data available

Density : 1.1 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Conditions to avoid : Do not allow evaporation to dryness.

No data available

Incompatible materials : Acids

Bases

Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Acute oral toxicity : (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

Version 6.0

Revision Date: 11/06/2024

SDS Number: 102000027050

Date of last issue: 03/01/2023 Date of first issue: 03/26/2018

Components:

2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester:

Result: Skin irritation

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Low viscosity acrylic oligomer:

Result: Corrosive

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Vapors may cause irritation to the eyes, respiratory system and the skin.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: Eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester:

Result: The product is a skin sensitizer, sub-category 1B.

Low viscosity acrylic oligomer:

Result: May cause sensitization by skin contact.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Result: May cause sensitization by skin contact.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: May cause sensitization by skin contact.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

Version 6.0

Revision Date: 11/06/2024

SDS Number: 102000027050

Date of last issue: 03/01/2023 Date of first issue: 03/26/2018

Further information

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Low viscosity acrylic oligomer:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-

oxo-2-propen-1-yl)oxy]-:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate)

Class : 9 Packing group : III

Labels : Miscellaneous Dangerous Goods

Packing instruction (cargo

aircraft)

: 964

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate)

Class : 9
Packing group : III
Labels : 9



ROTOSTAR UV FX 68-41002 SRNK SILVER US

Version Revision Date: SDS Number: Date of last issue: 03/01/2023 6.0 11/06/2024 102000027050 Date of first issue: 03/26/2018

EmS Code : F-A, S-F Marine pollutant : yes

Remarks : For single packagings <=5L / 5 kg, or combination

packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197

IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know CERCLA Reportable Quantity

Components	CAS-No.	Component RQ
		(lbs)
2-Propenoic acid	79-10-7	5000
Acetic acid ethyl ester	141-78-6	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Aluminum 7429-90-5 >= 5 - < 10 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Massachusetts Right To Know

Aluminum 7429-90-5

Pennsylvania Right To Know

2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester

Low viscosity acrylic oligomer

Acrylic monomer

Aluminum

7429-90-5

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

84434-11-7

2-Propenoic acid

79-10-7

Acetic acid ethyl ester

141-78-6

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Aluminum 7429-90-5

California Permissible Exposure Limits for Chemical Contaminants

Aluminum 7429-90-5

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL nor NDSL.

TSCA : All chemical substances in this product are either listed as



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration: n.o.s. - Not Otherwise Specified: NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for



ROTOSTAR UV FX 68-41002 SRNK SILVER US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/01/2023

 6.0
 11/06/2024
 102000027050
 Date of first issue: 03/26/2018

Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/06/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8