

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : eConduct Copper 420500  
Material number : 010350GK2

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Acute toxicity, Category 4, Oral, H302  
Serious eye damage/eye irritation, Category 2A, H319  
Short-term (acute) aquatic hazard, Category 1, H400

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

Long-term (chronic) aquatic hazard, Category 1, H410

**GHS-Labeling**

Symbol(s)



Signal word

: Warning

Hazard statements

 : H302: Harmful if swallowed.  
 H319: Causes serious eye irritation.  
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

 : **Prevention:**  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P273 Avoid release to the environment.  
 P280 Wear eye protection/ face protection.  
**Response:**  
 P301 + P317 + P330 IF SWALLOWED: Get medical help.  
 Rinse mouth.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with  
 water for several minutes. Remove contact lenses, if present  
 and easy to do. Continue rinsing.  
 P337 + P317 If eye irritation persists: Get medical help.  
 P391 Collect spillage.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste  
 disposal plant.

**Hazardous components which must be listed on the label**

 Identification  
 copper

 CAS-No.  
 7440-50-8

**Other hazards which do not result in classification**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## eConduct Copper 420500

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

Combustible Solids

### SECTION 3: Composition/information on ingredients

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	50 - 100
silver	7440-22-4 231-131-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder
- Unsuitable extinguishing media : Water, High volume water jet, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

- Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.  
Evacuate personnel to safe areas.  
Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.

**6.2 Environmental precautions**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Pick up and transfer to properly labelled containers.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

instituted to ensure that dusts do not accumulate on surfaces.

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : General industrial hygiene practice. Do not smoke. Wash hands before breaks and at the end of workday. Keep away from food and drink. Keep away from tobacco products.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards.

Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
- Dampness : Keep in a dry, cool and well-ventilated place.
- Other data : Keep in a dry place. No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	AGW (inhalable fraction)	1 mg/m <sup>3</sup>		DE TRGS 900
silver	7440-22-4	TWA	0,1 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information		Indicative			
silver	7440-22-4	AGW (Inhalable fraction)	0,1 mg/m <sup>3</sup>	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)		8;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)			
silver	7440-22-4	TWA	0,01 mg/m <sup>3</sup>	2006-02-09	2006/15/EC

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## eConduct Copper 420500

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

Further information	Indicative
---------------------	------------

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	TWA	1 mg/m <sup>3</sup>	2008-01-01	
copper	7440-50-8	TWA (dust and mists)	1 mg/m <sup>3</sup>	2005-09-01	
copper	7440-50-8	TWA	1 mg/m <sup>3</sup>	1989-01-19	
copper	7440-50-8	TWA	0,2 mg/m <sup>3</sup>	2008-01-01	
copper	7440-50-8	TWA	0,1 mg/m <sup>3</sup>	1989-01-19	
copper	7440-50-8	TWA (Dust and mist)	1 mg/m <sup>3</sup>	2010-03-01	
copper	7440-50-8	TWA (Fumes)	0,2 mg/m <sup>3</sup>	2010-03-01	
copper	7440-50-8	TWA (Dust)	1 mg/m <sup>3</sup>	2013-10-08	
copper	7440-50-8	TWA (Mist)	1 mg/m <sup>3</sup>	2013-10-08	
copper	7440-50-8	TWA (dusts and mists)	1 mg/m <sup>3</sup>	2011-07-01	
copper	7440-50-8	TWA (Fumes)	0,1 mg/m <sup>3</sup>	2011-07-01	
copper	7440-50-8	PEL (Fumes)	0,1 mg/m <sup>3</sup>	2014-11-26	
copper	7440-50-8	TWA (Fumes)	0,1 mg/m <sup>3</sup>	1989-01-19	
copper	7440-50-8	TWA (Dust and mist)	1 mg/m <sup>3</sup>	1989-01-19	
silver	7440-22-4	TWA	0,1 mg/m <sup>3</sup>	2008-01-01	
silver	7440-22-4	TWA (Dust)	0,01 mg/m <sup>3</sup>	2005-09-01	
silver	7440-22-4	TWA	0,01 mg/m <sup>3</sup>	1989-01-19	
silver	7440-22-4	TWA	0,01 mg/m <sup>3</sup>	1989-01-19	
silver	7440-22-4	TWA	0,01 mg/m <sup>3</sup>	2011-07-01	
silver	7440-22-4	TWA (Dust and fume)	0,1 mg/m <sup>3</sup>	2013-03-01	
silver	7440-22-4	TWA (Dust)	0,01 mg/m <sup>3</sup>	2013-10-08	
silver	7440-22-4	PEL	0,01 mg/m <sup>3</sup>	2014-11-26	

### 8.2 Exposure controls

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**Personal protective equipment**

- Eye protection : Safety glasses  
 : Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.
- Hand protection  
 Material : Leather  
 Remarks : Leather gloves  
 The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.  
 The exact break through time can be obtained from the protective glove producer and this has to be observed.  
 Recommended preventive skin protection  
 : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Long sleeved clothing  
 Safety shoes  
 : Dust impervious protective suit  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
 Respirator with a dust filter  
 P1 filter

**Environmental exposure controls**

- General advice : The product should not be allowed to enter drains, water courses or the soil.  
 : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

respective authorities.

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: copper
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Melting point/range	: 900 - 1 000 °C
Boiling point/boiling range	: Not applicable
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 8,5 - 9,5 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

Viscosity, dynamic : No data available  
Viscosity, kinematic : No data available  
Flow time : No data available

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions., No hazards  
to be specially mentioned.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

**10.4 Conditions to avoid**

Conditions to avoid : No data available

**10.5 Incompatible materials**

Materials to avoid : No data available

**10.6 Hazardous decomposition products**

Other information : No data available

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****copper :**

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## eConduct Copper 420500

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

### Reprod.Tox./Development/Teratogenicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product

No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **copper (7440-50-8) :**

M-Factor : 10

#### **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

#### **silver (7440-22-4) :**

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

---

M-Factor : 10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations**

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**13.1 Waste treatment methods**

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**SECTION 14: Transport information****14.1 UN number****ADR** : 3077**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 3077**IATA** : 3077**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(paint related material )**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
 N.O.S.  
 (,paint related material )  
 (paint related material)

**14.3 Transport hazard class**

**ADR** : 9

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 9

**IATA** : 9

**14.4 Packing group**
**ADR**

Packaging group : III

Classification Code : M7

Hazard Identification Number : 90

Labels : 9

Tunnel restriction code : (-)

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Packaging group : III

Labels : 9

EmS Code : F-A, S-F

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

**IATA**

Packing instruction (cargo aircraft) : 956

Packing instruction (passenger aircraft) : 956

Packing instruction (LQ) : Y956

Packaging group : III

Labels : 9

**14.5 Environmental hazards****IMDG** : Marine pollutant**ADR** : Environmentally hazardous**14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 7 - Heavy metals and their salts

For single packagings  $\leq 5L / 5 \text{ kg}$ , or combination packagings containing inner packagings  $\leq 5L / 5 \text{ kg}$  net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## eConduct Copper 420500

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Not applicable

### 15.2 Chemical safety assessment

No data available

## SECTION 16: Other information

### Full text of H-Statements

H302	: Harmful if swallowed.
H319	: Causes serious eye irritation.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**eConduct Copper 420500**

Version 2.0

Revision Date 04.04.2024

Print Date 30.11.2024

---