

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : METALURE L-54894 IA

Product code : 056254IA0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART Suisse SA  
Route de la Brasserie 2  
1963 Vétroz

Telephone : +410273454800

Telefax : +410273454859

E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |   |
|--|---|
| Flammable liquids, Category 2  | H225: Highly flammable liquid and vapour. |
| Eye irritation, Category 2   | H319: Causes serious eye irritation.      |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.  |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

Version 3.2      Revision Date: 03.04.2024      SDS Number: 102000000652      Print Date: 26.11.2024  
Date of first issue: 12.05.2014

|                                |   |  |
|--------------------------------|---|--|
| Hazard pictograms              | : |    |
| Signal word                    | : | Danger   |
| Hazard statements              | : | H225      Highly flammable liquid and vapour.<br>H319      Causes serious eye irritation.<br>H336      May cause drowsiness or dizziness.  |
| Supplemental Hazard Statements | : | EUH066      Repeated exposure may cause skin dryness or cracking.  |
| Precautionary statements       | : | <b>Prevention:</b><br>P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P233      Keep container tightly closed.<br>P261      Avoid breathing mist or vapours.<br>P280      Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><b>Response:</b><br>P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.<br>P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

### Hazardous components which must be listed on the label:

isopropyl acetate  
acetone

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

| Chemical name     | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | ClassificationREGULATION (EC) No 1272/2008                  | Concentration (% w/w) |
|-------------------|---|---|-----------------------|
| isopropyl acetate | 108-21-4<br>203-561-1<br>607-024-00-6                 | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336 | >= 50 - <= 100        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

Version 3.2      Revision Date: 03.04.2024      SDS Number: 102000000652      Print Date: 26.11.2024  
Date of first issue: 12.05.2014

|                               |  |   |                  |
|-------------------------------|--|---|------------------|
|                               | 01-2119537214-46   | (Central nervous system)<br>EUH066  |                  |
| aluminium powder (stabilised) | 7429-90-5<br>231-072-3<br>013-002-00-1<br><br>01-2119529243-45 | Flam. Sol. 1; H228  | $\geq 10 - < 20$ |
| acetone                       | 67-64-1<br>200-662-2<br>606-001-00-8<br><br>01-2119471330-49   | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>(Central nervous system)<br>EUH066 | $\geq 1 - < 10$  |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
ABC powder  
Foam

Unsuitable extinguishing media : High volume water jet  
Carbon dioxide (CO<sub>2</sub>)

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.  
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components   | CAS-No.   | Value type (Form of exposure) | Control parameters               | Basis   |
|--|-----------|-------------------------------|----------------------------------|---------|
| isopropyl acetate  | 108-21-4  | STEL                          | 200 ppm<br>849 mg/m <sup>3</sup> | GB EH40 |
| aluminium powder (stabilised)  | 7429-90-5 | TWA (Inhalable)               | 10 mg/m <sup>3</sup>             | GB EH40 |
|  |           | TWA (Respirable fraction)     | 4 mg/m <sup>3</sup>              | GB EH40 |
|  |           | TWA (inhalable dust)          | 10 mg/m <sup>3</sup>             | GB EH40 |
| Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any |           |                               |                                  |         |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

Version  
3.2

Revision Date:  
03.04.2024

SDS Number:  
102000000652

Print Date: 26.11.2024  
Date of first issue: 12.05.2014

|         |   |                       |                                      |            |
|---------|---|-----------------------|--------------------------------------|------------|
|         | <p>particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>  |                       |                                      |            |
|         |   | TWA (Respirable dust) | 4 mg/m <sup>3</sup>                  | GB EH40    |
|         | <p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p> |                       |                                      |            |
| acetone | 67-64-1   | TWA                   | 500 ppm<br>1,210 mg/m <sup>3</sup>   | 2000/39/EC |
|         | Further information: Indicative   |                       |                                      |            |
|         |   | TWA                   | 500 ppm<br>1,210 mg/m <sup>3</sup>   | GB EH40    |
|         |   | STEL                  | 1,500 ppm<br>3,620 mg/m <sup>3</sup> | GB EH40    |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name    | End Use   | Exposure routes | Potential health effects   | Value    |
|-------------------|-----------|-----------------|----------------------------|----------|
| isopropyl acetate | Consumers | Oral            | Long-term systemic effects | 26 mg/kg |
|                   | Consumers | Dermal          | Long-term systemic effects | 26 mg/kg |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

Version  
3.2

Revision Date:  
03.04.2024

SDS Number:  
102000000652

Print Date: 26.11.2024  
Date of first issue: 12.05.2014

|                               |           |            |                            |            |
|-------------------------------|-----------|------------|----------------------------|------------|
|                               | Workers   | Dermal     | Long-term systemic effects | 43 mg/kg   |
|                               | Consumers | Inhalation | Long-term systemic effects | 252 mg/m3  |
|                               | Workers   | Inhalation | Long-term systemic effects | 420 mg/m3  |
| aluminium powder (stabilised) | Workers   | Inhalation | Long-term systemic effects | 3.72 mg/m3 |
|                               | Workers   | Inhalation | Long-term local effects    | 3.72 mg/m3 |
|                               | Consumers | Oral       | Long-term systemic effects | 3.95 mg/kg |
| acetone                       | Workers   | Inhalation | Long-term systemic effects | 1210 mg/m3 |
|                               | Workers   | Inhalation | Acute local effects        | 2420 mg/m3 |
|                               | Workers   | Inhalation | Acute systemic effects     | 1210 mg/m3 |
|                               | Workers   | Dermal     | Long-term systemic effects | 186 mg/kg  |
|                               | Consumers | Inhalation | Long-term systemic effects | 200 mg/m3  |
|                               | Consumers | Dermal     | Long-term systemic effects | 62 mg/kg   |
|                               | Consumers | Oral       | Long-term systemic effects | 62 mg/kg   |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name                | Environmental Compartment | Value       |
|-------------------------------|---------------------------|-------------|
| isopropyl acetate             | Fresh water               | 0.22 mg/l   |
|                               | Marine water              | 0.022 mg/l  |
|                               | Soil                      | 0.35 mg/kg  |
|                               | Fresh water sediment      | 1.25 mg/kg  |
|                               | Marine sediment           | 0.125 mg/kg |
| aluminium powder (stabilised) | Fresh water               | 0.0749 mg/l |
|                               | clarification plant       | 20 mg/l     |
| acetone                       | Fresh water               | 10.6 mg/l   |
|                               | Marine water              | 1.06 mg/l   |
|                               | Fresh water sediment      | 30.4 mg/kg  |
|                               | Marine sediment           | 3.04 mg/kg  |
|                               | STP                       | 100 mg/l    |
|                               | Soil                      | 29.5 mg/kg  |
|                               | periodical release        | 21 mg/l     |

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Form : liquid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 88 °C

Flammability : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 2 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

### Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

### Vapor Pressure for Components:

1-methoxy-2-propanol : 11.3 hPa (20 °C)

ethyl acetate : 98.4 hPa (20 °C)

Relative density : No data available

Density : 0.87 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

### Particle characteristics

Particle Size Distribution : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### isopropyl acetate:

|                           |   |
|---------------------------|---|
| Acute oral toxicity       | : LD50 (Rat): 6,750 mg/kg   |
| Acute inhalation toxicity | : LC50 (Rat): 32 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour<br>Assessment: The substance or mixture has no acute inhalation toxicity |
| Acute dermal toxicity     | : LD50 (Rabbit): > 17,436 mg/kg<br>Target Organs: Skin  |

##### aluminium powder (stabilised):

|                           |  |
|---------------------------|--|
| Acute inhalation toxicity | : LC50 (Rat): > 5 mg/l<br>Exposure time: 4 h<br>Test atmosphere: dust/mist |
|---------------------------|--|

##### acetone:

|                           |  |
|---------------------------|--|
| Acute oral toxicity       | : LD50 (Rabbit): 4,700 - 5,800 mg/kg<br><br>(Mouse): 3,000 mg/kg<br><br>(Rat): 9,800 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat): 76 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour                     |
| Acute dermal toxicity     | : LD50 (Rabbit): > 2,000 mg/kg   |

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### **Product:**

Remarks : May cause skin irritation in susceptible persons.

#### **Components:**

##### **acetone:**

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Remarks : May cause irreversible eye damage.

#### **Components:**

##### **isopropyl acetate:**

Result : Eye irritation

##### **acetone:**

Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

### Components:

#### **isopropyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **acetone:**

Assessment : May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

#### **Further information**

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **isopropyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 400 mg/l  
Exposure time: 96 h

#### **acetone:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

|      |           |
|------|-----------|
| ADR  | : UN 1263 |
| IMDG | : UN 1263 |
| IATA | : UN 1263 |

### 14.2 UN proper shipping name

|      |  |
|------|--|
| ADR  | : PAINT  |
| IMDG | : PAINT, CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE |

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

**IATA** : Paint, classified according to 3.3.3.1 IATA-DGR

### 14.3 Transport hazard class(es)

|             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADR</b>  | : 3   |                  |
| <b>IMDG</b> | : 3   |                  |
| <b>IATA</b> | : 3   |                  |

### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (E)

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : 3

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

|  |   |  |
|--|---|--|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : | Conditions of restriction for the following entries should be considered:<br>Number on list 3<br>isopropyl acetate (Number on list 3)<br>aluminium powder (stabilised) (Number on list 40)<br>acetone (Number on list 3)<br>2-ethylhexan-1-ol (Number on list 3)<br>propan-2-ol (Number on list 3) |
|--|---|--|

|   |   |                |
|---|---|----------------|
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : | Not applicable |
|---|---|----------------|

|   |   |         |
|---|---|---------|
| Regulation (EU) 2019/1148 on the marketing and use of explosives precursors | : | acetone |
|---|---|---------|

|  |   |                |
|--|---|----------------|
| UK REACH List of substances subject to authorisation (Annex XIV) | : | Not applicable |
|--|---|----------------|

|   |   |  |
|---|---|--|
| Regulation (EU) 2019/1148 on the marketing and use of explosives precursors | : |  |
|---|---|--|

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

#### 15.2 Chemical safety assessment

No data available

### SECTION 16: Other information

#### Full text of H-Statements

|        |   |   |
|--------|---|---|
| H225   | : | Highly flammable liquid and vapour.                   |
| H228   | : | Flammable solid.                                      |
| H319   | : | Causes serious eye irritation.                        |
| H336   | : | May cause drowsiness or dizziness.                    |
| EUH066 | : | Repeated exposure may cause skin dryness or cracking. |

#### Full text of other abbreviations

|            |   |  |
|------------|---|--|
| Eye Irrit. | : | Eye irritation   |
| Flam. Liq. | : | Flammable liquids  |
| Flam. Sol. | : | Flammable solids   |
| STOT SE    | : | Specific target organ toxicity - single exposure             |
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

|                  |  |
|------------------|--|
|                  | list of indicative occupational exposure limit values    |
| GB EH40          | : UK. EH40 WEL - Workplace Exposure Limits               |
| 2000/39/EC / TWA | : Limit Value - eight hours                              |
| GB EH40 / TWA    | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL   | : Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|              |      |
|--------------|------|
| Flam. Liq. 2 | H225 |
| Eye Irrit. 2 | H319 |
| STOT SE 3    | H336 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE L-54894 IA

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 26.11.2024          |
| 3.2     | 03.04.2024     | 102000000652 | Date of first issue: 12.05.2014 |

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN