according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.1	29.02.2024	10200000738	Date of first issue: 26.02.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier			
Trade name	:	PLATINVARIO	AE-82002

Product code : 053175JD0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 Eye irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Central nervous system H228: Flammable solid.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Versior 3.1	Revision Date: 29.02.2024		DS Number: 02000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
Ha	zard pictograms	:		!
Sig	gnal word	:	Danger	•
Ha	zard statements	:	H228 H319 H336	Flammable solid. Causes serious eye irritation. May cause drowsiness or dizziness.
	pplemental Hazard atements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Pre	ecautionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P261 P280	Avoid breathing dust. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
			Response: P304 + P340 + I	P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
			P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
			P370 + P378	In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No.	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
	Registration number		
ethyl acetate	141-78-6	Flam. Liq. 2; H225	>= 50 - <= 100
	205-500-4	Eye Irrit. 2; H319	
	607-022-00-5	STOT SE 3; H336	

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000000738	Print Date: 02.12.2024 Date of first issue: 26.02.20	14
		01-2119475	(Central nervous 5103-46 system) EUH066	
alum	ninium powder (stabilisec) 7429-90-5 231-072-3 013-002-00	-1	>= 10 - < 20
		01-2119529		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move the victim to fresh air.				
	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.				
If inhaled	 Remove to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. 				
In case of skin contact	: Wash off immediately with soap and plenty of water.				
	If on clothes, remove clothes.				
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 				
If swallowed	 Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 				
4.2 Most important symptoms and	4.2 Most important symptoms and effects, both acute and delayed				
Risks	: Causes serious eye irritation. May cause drowsiness or dizziness.				

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed This information is not available.

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.1	29.02.2024	10200000738	Date of first issue: 26.02.2014

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media : Dry sand Special powder against metal fire Unsuitable extinguishing Carbon dioxide (CO2) ABC powder media Water Foam High volume water jet 5.2 Special hazards arising from the substance or mixture Specific hazards during Contact with water liberates extremely flammable gas : firefighting (hydrogen). 5.3 Advice for firefighters Special protective equipment : Wear self-contained breathing apparatus for firefighting if for firefighters necessary. Use personal protective equipment. For safety reasons in case of fire, cans should be stored Further information separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Evacuate personnel to safe areas. Use personal protective equipment. Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Remove all sources of ignition.
----------------------	---	--

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
6.3 Metho	ds and material for o	containment and clea	aning up
Metho	ods for cleaning up	Soak up with i	al handling equipment. nert absorbent material (e.g. sand, silica gel, niversal binder, sawdust).
		vacuum cleane disposal acco	ge, and then collect with an electrically protected er or by wet-brushing and place in container for rding to local regulations (see section 13). le, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Advice on protection against : fire and explosion	 Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.
	at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.
Hygiene measures :	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	luding any incompatibilities
Requirements for storage : areas and containers	Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.
	No smoking. Keep container tightly closed in a dry and well- ventilated place. Observe label precautions. Electrical installations / working materials must comply with the

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Ver 3.1	sion	Revision Date: 29.02.2024		9S Number: 2000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
				technological saf	ety standards.
		r information on e conditions	:	Protect from hum	idity and water. Do not allow to dry.
Advice on common storage		:	Never allow prod storage. Keep away from	ether with oxidizing and self-igniting products. uct to get in contact with water during oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.	
		r information on e stability	:	No decompositio	n if stored and applied as directed.
7.2 Specific and $uco(c)$					

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis				
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m3	GB EH40				
		STEL	400 ppm 1,468 mg/m3	GB EH40				
		STEL	400 ppm 1,468 mg/m3	2017/164/EU				
	Further inform	hation: Indicative						
		TWA	200 ppm 734 mg/m3	2017/164/EU				
	Further information: Indicative							
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40				
		TWA (Respirable fraction)	4 mg/m3	GB EH40				
		TWA (inhalable dust)	10 mg/m3	GB EH40				
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain							

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000000738	Print Date: 02 Date of first is	2.12.2024 ssue: 26.02.2014	
	respo disting and 'r mater availa to the defini conta should	ular particle after entry nse that it elicits, depe- guishes two size fracti espirable'., Inhalable of ial that enters the nose ble for deposition in the fraction that penetrate tions and explanatory in components that ha d be complied with., W re three times the long	and on the nature ons for limit-settin lust approximates and mouth durin re respiratory traces to the gas exclo- material are given we their own assi where no specific l-term exposure limits.	and size of the part of purposes terme is to the fraction of ing breathing and is the Respirable dust hange region of th n in MDHS14/4., V gned WEL, all the short-term exposit	article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed, d.
	inhala when MDHS respir subst conce inhala any d levels must partic partic respo disting and 'r mater availa to the defini conta should	TWA (Respir dust) er information: For the ble dust are those frace sampling is undertake 514/4 General method able, thoracic and inha ance hazardous to hea entration in air equal to ble dust or 4 mg.m-3 ust will be subject to C . Some dusts have be comply with the appro- les of a wide range of ular particle after entry nse that it elicits, depending guishes two size fraction espirable'., Inhalable of ial that enters the nose ble for deposition in the fraction that penetrate tions and explanatory in components that ha d be complied with., We re three times the long	purposes of these ctions of airborne n in accordance s for sampling ar lable aerosols., alth includes dust or greater than 1 8-hour TWA of re OSHH if people en assigned spec priate limits., Mos sizes. The behav into the human n end on the nature ons for limit-settin lust approximates e and mouth durin he respiratory trace s to the gas excl material are given ve their own assi /here no specific	dust which will be with the methods of ad gravimetric anal The COSHH defin of any kind when 0 mg.m-3 8-hour spirable dust. This are exposed to du cific WELs and exp st industrial dusts of iour, deposition ar respiratory system and size of the par ing purposes terme s to the fraction of ng breathing and i the Respirable dust hange region of th n in MDHS14/4., V gned WEL, all the short-term expose	e collected described in lysis or ition of a present at a TWA of a means that st above these posure to these contain nd fate of any and the body article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Where dusts relevant limits ure limit is listed,

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	()		()	
Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

ersion 1	Revision Date: 29.02.2024	SDS Nur 1020000		Print Date: 02.12.2024 Date of first issue: 26.02.2014	
		Consumers	Inhalation	Long-term local effects	367 mg/m3
		Consumers	Inhalation	Acute systemic effects	734 mg/m3
		Consumers	Inhalation	Acute local effects	734 mg/m3
		Consumers	Dermal	Long-term systemic effects	37 mg/kg
		Workers	Dermal	Long-term local effects	63 mg/kg
		Consumers	Oral	Long-term systemic effects	4.5 mg/kg
	nium powder lised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
		Workers	Inhalation	Long-term local effects	3.72 mg/m3
		Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	STP	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipme Eye/face protection Hand protection		Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Material	:	Solvent-resistant gloves (butyl-rubber)
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace

PLATINVARIO AE-82002

according to Regulation (EC) No. 1907/2006





Version **Revision Date:** SDS Number: Print Date: 02.12.2024 3.1 29.02.2024 10200000738 Date of first issue: 26.02.2014 should be discussed with the producers of the protective gloves. Long sleeved clothing Skin and body protection : Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Use suitable breathing protection if workplace concentration Respiratory protection : requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	Pasty solid
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	77 °C
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	-4 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n- octanol/water	:	No data available

according to Regulation (EC) No. 1907/2006

PLATINVARIO AE-82002



Ver 3.1	sion	Revision Date: 29.02.2024	-	S Number: 2000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
	Vapou	pressure	:	No data available	9
		Pressure for Compone acetate	ents: :	98.4 hPa (20 °C)
	Relative	e density	:	No data available)
	Density	/	:	0.9 g/cm3 (20 °C)
	Relative	e vapour density	:	No data available)
		e characteristics icle Size Distribution	:	No data available)
9.2	Other in	nformation			
	Explos	ives	:	Not explosive Vapours may for	m explosive mixture with air.
	Self-ig	nition	:	not auto-flammal	ble
	Miscibi	lity with water	:	immiscible	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
10.4 Conditions to avoid		
Conditions to avoid	:	Do not allow to dry.
		Heat, flames and sparks.
10.5 Incompatible materials		
Materials to avoid	:	Acids Bases Oxidizing agents Highly halogenated compounds

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.1	29.02.2024	10200000738	Date of first issue: 26.02.2014

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

ethyl	acetate:
-------	----------

Acute oral toxicity	:	(Rat): 5,620 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 56 mg/l Exposure time: 4 h Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks

: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks

: May cause irreversible eye damage.

Components:

ethyl acetate: Result : Eye

: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024		S Number: 000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
-	iratory sensitisation lassified based on ava	ilable ir	nformation.	
	cell mutagenicity lassified based on ava	ailable ir	nformation.	
	nogenicity lassified based on ava	ailable ir	nformation.	
-	oductive toxicity lassified based on ava	ailable ir	nformation.	
	- single exposure cause drowsiness or d	izziness	5.	
<u>Com</u> p	oonents:			
-	acetate: ssment	:	May cause dro	wsiness or dizziness.
	- repeated exposure lassified based on ava		nformation.	
-	ation toxicity lassified based on ava	ailable ir	nformation.	
11.2 Infor	mation on other haza	ards		
Furth	er information			
<u>Produ</u> Rema			tiredness, naus Concentrations narcotic effects	overexposure may be headache, dizziness, sea and vomiting. s substantially above the TLV value may cause s. degrease the skin.
SECTIO	N 12: Ecological inf	ormat	ion	
12.1 Toxic	city			
<u>Com</u> p	oonents:			
ethyl	acetate:			

12.2 Persistence and degradability

No data available

aquatic invertebrates

12.3 Bioaccumulative potential

No data available

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014			
	i lity in soil ata available					
12.5 Resu	Its of PBT and vPvB a	assessment				
<u>Prod</u> Asse	<u>uct:</u> ssment	to be either very persist	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.			
	ocrine disrupting prop ata available	erties				
12.7 Othe	r adverse effects					
	uct: ional ecological nation	: No data ava	ilable			
SECTIO	N 13: Disposal cons	derations				
Europ	bean Waste Catalogue		ther particulates and dust (including ball-mill dust) azardous substances			
13.1 Wast Produ	e treatment methods uct	Do not cont chemical or	ose of waste into sewer. aminate ponds, waterways or ditches with used container. censed waste management company.			
Conta	aminated packaging	Dispose of Do not re-us	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.			
SECTIO	N 14: Transport info	rmation				
14.1 UN n	umber or ID number					
ADR		: UN 1325	: UN 1325			
IMDG	ì	: UN 1325	: UN 1325			
ΙΑΤΑ		: UN 1325	: UN 1325			
14.2 UN p	roper shipping name					
ADR			E SOLID, ORGANIC, N.O.S. pigment paste)			

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024)S Number: 2000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
IMDG		:	FLAMMABLE S (Aluminium pigr	OLID, ORGANIC, N.O.S. nent paste)
ΙΑΤΑ		:	Flammable solid, organic, n.o.s. (Aluminium pigment paste)	
14.3 Transp	oort hazard class(es)			
			Class	Subsidiary risks
ADR		:	4.1	
IMDG		:	4.1	
ΙΑΤΑ		:	4.1	
14.4 Packin	ig group			
Classif Hazard Labels	g group ication Code Identification Number restriction code	:	II F1 40 4.1 (E)	
IMDG Packing Labels EmS C Remark		::	II 4.1 F-G, S-G IMDG Code seg	regation group 15 - Powdered metals
aircraft Packing	g instruction (cargo	:	448 Y441 II 4.1	
Packing (passed Packing	Passenger) g instruction nger aircraft) g instruction (LQ) g group	:	445 Y441 II 4.1	
	nmental hazards			
IMDG	nmentally hazardous pollutant	:	no	
14.6 Specia	I precautions for use	r		

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.1	29.02.2024	102000000738	Date of first issue: 26.02.2014

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: ethyl acetate (Number on list 3) aluminium powder (stabilised) (Number on list 40)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements				
H225	:	Highly flammable liquid and vapour.		
H228	:	Flammable solid.		
H319	:	Causes serious eye irritation.		
H336	:	May cause drowsiness or dizziness.		
EUH066	:	Repeated exposure may cause skin dryness or cracking.		
Full text of other abbreviations				
Eye Irrit.	:	Eye irritation		
Flam. Liq.	:	Flammable liquids		
Flam. Sol.	:	Flammable solids		
STOT SE	:	Specific target organ toxicity - single exposure		
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values		
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits		

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version 3.1	Revision Date: 29.02.2024	SDS Number: 102000000738	Print Date: 02.12.2024 Date of first issue: 26.02.2014
2017/ ⁻	164/EU / STEL 164/EU / TWA	: Short term ex : Limit Value - e	eight hours
-	H40 / TWA H40 / STEL		oosure limit (8-hour TWA reference period) posure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixtu	re:	Classification procedure:
Flam. Sol. 1	H228	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

according to Regulation (EC) No. 1907/2006



PLATINVARIO AE-82002

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.1	29.02.2024	10200000738	Date of first issue: 26.02.2014

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN