

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---

### SECTION 1. IDENTIFICATION

Product name : METALURE A-61010 MB  
 Product code : 027500IA0

#### Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation  
 Address : 830 East Erie Street  
 Painesville OH 44077  
 Telephone : 866-458-7837  
 Telefax : (440) 354-6224  
 Emergency telephone : **CHEMTREC:** 800-424-9300  
**CHEMTREC:** 1-703-527-3387 (International)

#### NCEC:

(contract no. ECKART29003-NCEC)  
 US: +1 866 928 0789 (Toll free)  
 Canada: +1 800 579 7421 (Toll Free)  
 Mexico: +52 55 5004 8763

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2  
 Eye irritation : Category 2A

#### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
 H319 Causes serious eye irritation.

Precautionary Statements :

#### Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
1-Butanol, 3-methoxy-3-methyl-	56539-66-3	>= 70 - < 90
Aluminum	7429-90-5	>= 10 - < 20
2-Propanone	67-64-1	>= 1 - < 5

---

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---

		advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Causes serious eye irritation.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

---

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Do not flush with water.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3

## METALURE A-61010 MB

Version  
2.0Revision Date:  
12/05/2019SDS Number:  
102000000663Date of last issue: -  
Date of first issue: 03/29/2018

		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	1 mg/m3	ACGIH
		TWA	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m3 (Aluminum)	ACGIH
		TWA (Fumes)	5 mg/m3	OSHA P0
2-Propanone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL

## METALURE A-61010 MB

Version 2.0      Revision Date: 12/05/2019      SDS Number: 102000000663      Date of last issue: -  
 Date of first issue: 03/29/2018

		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0

**Hazardous components without workplace control parameters**

Components	CAS-No.
1-Butanol, 3-methoxy-3-methyl-	56539-66-3

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Personal protective equipment**

Hand protection

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : viscous
- Color : silver
- Odor : characteristic
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling : 174 °C

## METALURE A-61010 MB

Version 2.0      Revision Date: 12/05/2019      SDS Number: 102000000663      Date of last issue: -  
Date of first issue: 03/29/2018

---

range  
Flash point : 15 °C

Evaporation rate : No data available  
Flammability (solid, gas) : No data available  
Upper explosion limit / Upper flammability limit : No data available  
Lower explosion limit / Lower flammability limit : No data available  
Vapor pressure : No data available  
Relative density : No data available  
Density : 1.11 g/cm<sup>3</sup>

Solubility(ies) : No data available  
Partition coefficient: n-octanol/water : No data available  
Autoignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.  
Chemical stability : No decomposition if stored and applied as directed.  
Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****2-Propanone:**

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg  
(Mouse): 3,000 mg/kg  
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

---

**METALURE A-61010 MB**

Version 2.0      Revision Date: 12/05/2019      SDS Number: 102000000663      Date of last issue: -  
Date of first issue: 03/29/2018

---

Acute dermal toxicity                   :   LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****2-Propanone:**

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****2-Propanone:**

Remarks: Severe eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.



**METALURE A-61010 MB**

Version      Revision Date:      SDS Number:      Date of last issue: -  
2.0          12/05/2019          102000000663      Date of first issue: 03/29/2018

---

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****2-Propanone:**

Toxicity to daphnia and other : (Daphnia magna (Water flea)): 21,600 mg/l  
aquatic invertebrates

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****Domestic regulation**

49 CFR

## METALURE A-61010 MB

Version      Revision Date:      SDS Number:      Date of last issue: -  
 2.0            12/05/2019            102000000663      Date of first issue: 03/29/2018

---

UN/ID/NA number            : UN 1263  
 Proper shipping name        : Paint  
 Class                         : 3  
 Packing group                : III  
 Labels                        : Class 3 - Flammable liquids  
 ERG Code                     : 128  
 Marine pollutant             : no

**International Regulations****IATA-DGR**

UN/ID No.                     : UN 1263  
 Proper shipping name        : Paint classified according to 3.3.3.1 IATA-DGR  
 Class                         : 3  
 Packing group                : III  
 Labels                        : Class 3 - Flammable liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number                    : UN 1263  
 Proper shipping name        : PAINT CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE  
 Class                         : 3  
 Packing group                : III  
 Labels                        : 3  
 EmS Code                     : F-E, S-E  
 Marine pollutant             : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

---

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
2-Propanone	67-64-1	5000

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

---

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	>= 10 - < 20 %
----------	-----------	----------------

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

2-Propanone	67-64-1	4 %
-------------	---------	-----

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

**US State Regulations****Massachusetts Right To Know**

1-Butanol, 3-methoxy-3-methyl-	56539-66-3
Aluminum	7429-90-5
2-Propanone	67-64-1

**Pennsylvania Right To Know**

1-Butanol, 3-methoxy-3-methyl-	56539-66-3
Aluminum	7429-90-5
2-Propanone	67-64-1

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California List of Hazardous Substances**

Aluminum	7429-90-5
2-Propanone	67-64-1

**California Permissible Exposure Limits for Chemical Contaminants**

Aluminum	7429-90-5
2-Propanone	67-64-1

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x%

## METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/05/2019	102000000663	Date of first issue: 03/29/2018

---

growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/05/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8