according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date:	SDS Number:	Print Date: 29.11.2024
4.0	13.02.2023	102000024879	Date of first issue: 04.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	STAPA ALUPOR N 313
Product code	:	022544PX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	: ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	: +499152770
Telefax	: +499152777008
E-mail address of person responsible for the SDS	: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

Additional Labelling

EUH210	Safety data sheet available on request.
EUH208	Contains Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl)

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date:	SDS Number:	Print Date: 29.11.2024
4.0	13.02.2023	102000024879	Date of first issue: 04.08.2016

esters. May produce an allergic reaction.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No.	ClassificationREGUL ATION (EC) No	Concentration (% w/w)
	Index-No. Registration number	1272/2008	
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3 013-002-00-1		
	01-2119529243-45		
2,2' -oxybisethanol	111-46-6	Acute Tox. 4; H302	>= 25 - < 50
	203-872-2	Acute toxicity	
	603-140-00-6 01-2119457857-21	estimate	
		Acute oral toxicity: 1,120 mg/kg	
dodecylbenzenesulphonic acid, compound with isopropylamine	26264-05-1	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
(1:1)	247-556-2		
Phosphoric acid, mono- and bis(C16-20-branched and linear	97468-33-2	Skin Sens. 1B; H317 Aquatic Chronic 4;	>= 0.1 - < 0.25
alkyl) esters	946-101-1	H413	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move the victim to fresh air.
		No hazards which require special first aid measures.
If inhaled	:	If unconscious, place in recovery position and seek medical

according to Regulation (EC) No. 1907/2006

STAPA ALUPOR N 313



Version 4.0	Revision Date: 13.02.2023	SDS Number: 102000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016	
		advice. If symptoms	s persist, call a physician.	
In cas	se of skin contact	: Wash off im	mediately with soap and plenty of water.	
		lf on skin, rir	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.	
In cas	se of eye contact	: Immediately	flush eye(s) with plenty of water.	
		Remove cor	with water as a precaution. ntact lenses. de open while rinsing.	
lf swa	allowed	Do not give Never give a	atory tract clear. milk or alcoholic beverages. anything by mouth to an unconscious person. a persist, call a physician.	

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	Water Foam ABC powder Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters Special protective equipment for firefighters	:	Use personal protective equipment.
		Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date:	SDS Number:	Print Date: 29.11.2024
4.0	13.02.2023	102000024879	Date of first issue: 04.08.2016

SECTION 6: Accidental release measures

• •	e equipment and emergency procedures Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition. Use personal protective equipment. Avoid dust formation.					
6.2 Environmental precautions Environmental precautions :	The product should not be allowed to enter drains, water courses or the soil.					
	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.					
6.3 Methods and material for containment and cleaning up						

Methods for cleaning up	: Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
	Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Advice on protection against fire and explosion	:	Dispose of rinse water in accordance with local and national regulations. Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential. Avoid dust formation.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Versio 4.0	on	Revision Date: 13.02.2023	-	0S Number: 2000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016
Н	lygiene	e measures	:	-	ot eat or drink. When using do not smoke. re breaks and at the end of workday.
7.2 Co	onditio	ons for safe storage,	incl	luding any incom	patibilities
	•	ements for storage nd containers	:	cool, well-ventilate	ontainer. Keep containers tightly closed in a ed place. Keep container closed when not in rom sources of ignition - No smoking.
				place. Electrical in	ghtly closed in a dry and well-ventilated nstallations / working materials must comply gical safety standards.
-		information on conditions	:	Protect from hum	dity and water. Do not allow to dry.
A	Advice	on common storage	:	Never allow productors storage. Keep away from the storage of the	ther with oxidizing and self-igniting products. Let to get in contact with water during oxidizing agents, strongly alkaline and erials in order to avoid exothermic reactions.
-		information on stability	:	No decomposition	n if stored and applied as directed.
7.3 Sp	pecific	end use(s)			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40		
		TWA (Respirable fraction)	4 mg/m3	GB EH40		
		TWA (inhalable dust)	10 mg/m3	GB EH40		
	inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some	dust) rmation: For the purposes of these limits, respirable dust and ust are those fractions of airborne dust which will be collected ling is undertaken in accordance with the methods described in General methods for sampling and gravimetric analysis or horacic and inhalable aerosols., The COSHH definition of a nazardous to health includes dust of any kind when present at a on in air equal to or greater than 10 mg.m-3 8-hour TWA of ust or 4 mg.m-3 8-hour TWA of respirable dust. This means that I be subject to COSHH if people are exposed to dust above these e dusts have been assigned specific WELs and exposure to these y with the appropriate limits., Most industrial dusts contain				

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version 4.0	Revision Date 13.02.2023		Number: 00024879	Print Date: 29.11. Date of first issue		
		particular part response that distinguishes and 'respirabl material that e available for o to the fraction definitions and contain comp should be con	ticle after entry in it elicits, depend two size fraction e'., Inhalable dus enters the nose a deposition in the r o that penetrates t d explanatory ma onents that have mplied with., Whe	es. The behaviour, to the human resp on the nature and s for limit-setting p t approximates to nd mouth during b espiratory tract. Re to the gas exchang terial are given in their own assigned re no specific sho erm exposure limit	iratory system size of the pa urposes terme the fraction of reathing and i espirable dust ge region of th MDHS14/4., V d WEL, all the rt-term exposit	and the body article. HSE d'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed,
			TWA (Respirab dust)			GB EH40
2,2' -0>	kybisethanol	inhalable dus when samplir MDHS14/4 G respirable, the substance has concentration inhalable dus any dust will b levels. Some must comply particles of a particular part response that distinguishes and 'respirabl material that e available for of to the fraction definitions an contain comp should be con	t are those fraction of is undertaken i eneral methods f pracic and inhalat zardous to health in air equal to or t or 4 mg.m-3 8-h be subject to COS dusts have been with the appropria wide range of siz ticle after entry in t elicits, depend two size fraction e'., Inhalable dus enters the nose a deposition in the r o that penetrates the d explanatory ma onents that have mplied with., Whe	arposes of these lin ons of airborne dus in accordance with or sampling and gr ole aerosols., The includes dust of a greater than 10 m our TWA of respire SHH if people are of assigned specific ate limits., Most ind es. The behaviour, to the human resp on the nature and s for limit-setting p t approximates to nd mouth during b espiratory tract. Re o the gas exchang terial are given in a their own assigned re no specific sho re no specific sho re no specific sho re approximates to a the gas exchang terial are given in a their own assigned re no specific sho re no specific sho	at which will be the methods of ravimetric anal COSHH defin any kind when g.m-3 8-hour able dust. This exposed to du WELs and exp dustrial dusts dustrial dusts dustrial dusts dustrial dusts dustrial dusts dustrial dusts dustrial dusts dustrial dust dustrial dust dustrial dust dustrial dust dustrial dust dustrial dust dustrial dust dustrial dust dust dustrial dust dust dust dust dust dust dust dust	collected described in ysis or ition of a present at a TWA of means that st above these cosure to these cosure to these contain of fate of any , and the body article. HSE ed 'inhalable' airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed,
				specific short-tern n exposure limit sh		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Versio 4.0	n Revision Date: 13.02.2023	SDS Number: 102000024879		Print Date: 29.11.2024 Date of first issue: 04.08.2016		
2,	2' -oxybisethanol	Workers	Inhalation	Long-term local effects	60 mg/m3	
		Workers	Vorkers Skin contact		emic 43 mg/kg	
		Consumers	Inhalation	Long-term local effects	12 mg/m3	
		Consumers	Skin cont	act Long-term syste effects	emic 21 mg/kg	
		Workers	Inhalation	Long-term syste effects	emic 44 mg/m3	
		Consumers	Inhalation	Long-term syste effects	emic 12 mg/m3	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
2,2' -oxybisethanol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Water	10 mg/l
	STP	199.5 mg/l
	Fresh water sediment	20.9 mg/kg
	Soil	1.53 mg/kg
	Marine sediment 2.09 mg/k	
	water (intermittent release)	10 mg/l

8.2 Exposure controls

Personal protective equipmentEye/face protection:Hand protection:Material:		Safety glasses Solvent-resistant gloves		
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.		
Skin and body protection	:	Long sleeved clothing Safety shoes Choose body protection according to the amount and		

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date: 13.02.2023	SDS Number:	Print Date: 29.11.2024
4.0		102000024879	Date of first issue: 04.08.2016
Resp	iratory protection	Choose body concentration	of the dangerous substance at the work place. protection according to the amount and of the dangerous substance at the work place. reathing protection if workplace concentration

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

1	Physical state	an :	Pasty solid
	Colour	:	silver
	Odour	:	characteristic
	Odour Threshold	:	No data available
	Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability	:	Combustible Solids
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	No data available
	Auto-ignition temperature	:	Not relevant
	Decomposition temperature	:	No data available
	рН	:	substance/mixture is non-soluble (in water)
	Viscosity, kinematic	:	No data available
	Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	No data available
	Relative density	:	No data available
	Density	:	No data available

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Versio 4.0	n Revision Date: 13.02.2023	SDS Number: 102000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016	
R	elative vapour density	: No data availa	ble	
	Particle Size Distribution	:		
	her information xplosives	: Not explosive		
S	elf-ignition	: not auto-flamn not auto-flamn		
Ν	liscibility with water	: immiscible		

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.
10.4 Conditions to avoid	
Conditions to avoid	Do not allow to dry.
	No data available
10.5 Incompatible materials	
Materials to avoid	Acids Bases Oxidizing agents Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

rsion)	Revision Date: 13.02.2023	SDS Number: 102000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016
	N 11: Toxicologica	Iinformation	
.1 Infori	mation on hazard cla	asses as defined in	Regulation (EC) No 1272/2008
	e toxicity assified based on ava	ailable information.	
Produ	uct:		
	oral toxicity		y estimate: > 2,000 mg/kg culation method
<u>Comp</u>	oonents:		
alumi	inium powder (stabi	lised):	
Acute	inhalation toxicity	: LC50 (Rat): : Exposure tim Test atmosp	
	oxybisethanol:		
Acute	oral toxicity	: LD50 (Huma	ns): 1,120 mg/kg
			y estimate: 1,120 mg/kg culation method
Acute	inhalation toxicity	: (Rat): > 4.6 Exposure tim	
Acute	dermal toxicity	: LD50 (Rabbi	t): 13,300 mg/kg
dode	cylbenzenesulphoni	c acid, compound v	with isopropylamine (1:1):
Acute	oral toxicity	: LD50 (Rat): :	> 2,000 mg/kg
-	corrosion/irritation assified based on ava	ailable information.	
<u>Produ</u>	uct:		
Rema	rks	: May cause s	kin irritation and/or dermatitis.
<u>Comp</u>	oonents:		
dode	cylbenzenesulphoni	c acid, compound v	with isopropylamine (1:1):
Resul	t	: Skin irritation	
Phos Resul		and bis(C16-20-bran : No skin irritat	ched and linear alkyl) esters:

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

0	Revision Date: 13.02.2023	SDS Number: 102000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016				
	us eye damage/eye assified based on av						
<u>Produ</u> Rema		: Product dust m system.	ay be irritating to eyes, skin and respirato				
<u>Com</u> p	oonents:						
dode Resul		c acid, compound with : Eye irritation	th isopropylamine (1:1):				
Respi	ratory or skin sensi	tisation					
	sensitisation assified based on av	ailable information.					
-	ratory sensitisation assified based on av						
<u>Com</u> p	Components:						
Phos Resul	•	•	ed and linear alkyl) esters: a skin sensitiser, sub-category 1B.				
	cell mutagenicity assified based on ava	ailable information.					
	n ogenicity assified based on ava	ailable information.					
-	oductive toxicity assified based on av	ailable information.					
	• single exposure assified based on av	ailable information.					
	- repeated exposur assified based on av						
-	ation toxicity assified based on ava	ailable information.					
.2 Infor	mation on other haz	ards					
Furth	er information						

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version 4.0	Revision Date: 13.02.2023	SDS Number: 102000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016
	10.02.12.02.0		
		•	

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological : No data available information

SECTION 13: Disposal considerations

European Waste Catalogue European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances
13.1 Waste treatment methods Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.

according to Regulation (EC) No. 1907/2006

STAPA ALUPOR N 313



Version 4.0	Revision Date: 13.02.2023		OS Number: 2000024879	Print Date: 29.11.2024 Date of first issue: 04.08.2016
Cont	aminated packaging	:	Empty remaining Dispose of as un Do not re-use em In accordance wit	used product.
SECTIO	N 14: Transport info	rmat	tion	
14.1 UN	number or ID number			
ADR		:	Not regulated as	a dangerous good
IMD	G	:	Not regulated as	a dangerous good
IATA	N Contraction of the second seco	:	Not regulated as	a dangerous good
14.2 UN	proper shipping name			
ADR		:	Not regulated as	a dangerous good
IMD	G	:	Not regulated as	a dangerous good
IATA	N	:	Not regulated as	a dangerous good
14.3 Trar	sport hazard class(es))		
ADR		:	Not regulated as	a dangerous good
IMD	G	:	Not regulated as	a dangerous good
IATA	N	:	Not regulated as	a dangerous good
14.4 Pac	king group			
ADR		:	Not regulated as	a dangerous good
IMD	G	:	Not regulated as	a dangerous good
IATA	(Cargo)	:	Not regulated as	a dangerous good
IATA	(Passenger)	:	Not regulated as	a dangerous good
-	ironmental hazards regulated as a dangerou	is go	od	
-	cial precautions for us	er		
Rem	arks	:	Not classified as regulations.	dangerous in the meaning of transport

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date:	SDS Number:	Print Date: 29.11.2024
4.0	13.02.2023	102000024879	Date of first issue: 04.08.2016

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) 2,2' -oxybisethanol (Number on list 3) dodecylbenzenesulphonic acid, compound with isopropylamine (1:1) (Number on list 3) Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters (Number on list 3) 2,2'-iminodiethanol (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements				
H228	:	Flammable solid.		
H302	:	Harmful if swallowed.		
H315	:	Causes skin irritation.		
H317	:	May cause an allergic skin reaction.		
H319	:	Causes serious eye irritation.		
H413	:	May cause long lasting harmful effects to aquatic life.		
Full text of other abbreviations				
Acute Tox.	:	Acute toxicity		
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Eye Irrit.	:	Eye irritation		
Flam. Sol.	:	Flammable solids		
Skin Irrit.	:	Skin irritation		
Skin Sens.	:	Skin sensitisation		
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits		
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)		

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 313

Version	Revision Date:	SDS Number:	Print Date: 29.11.2024
4.0	13.02.2023	102000024879	Date of first issue: 04.08.2016

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN