

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SILVERSHINE 418 Aluminiumpaste  
Material number : 022324G60

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guntersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

### SECTION 2: Hazards identification

**GHS Classification**

: Long-term (chronic) aquatic hazard, Category 3, H412

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

**GHS-Labeling**

Hazard statements : H412: Harmful to aquatic life with long lasting effects.

 Precautionary statements : **Prevention:**  
 P273 Avoid release to the environment.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**
**Other hazards which do not result in classification**

Combustible Solids

**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

| Chemical name  | CAS-No.<br>EINECS-No.   | Classification and labelling   | Concentration[%] |
|--|-------------------------|--|------------------|
| aluminium powder (stabilised)  | 7429-90-5<br>231-072-3  | Flam. Sol.;1;H228  | 50 - 100         |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha | 64742-48-9<br>918-481-9 | Flam. Liq.;4;H227<br>Asp. Tox.;1;H304  | 20 - 25          |
| Solvent naphtha (petroleum), light arom.   | 64742-95-6<br>918-668-5 | Flam. Liq.;3;H226<br>Acute Tox.;5;H303<br>Acute Tox.;5;H313<br>STOT SE;3;H335,<br>H336<br>Asp. Tox.;1;H304 | 2,5 - 10         |

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

|  |  |                           |  |
|--|--|---------------------------|--|
|  |  | Aquatic<br>Chronic;2;H411 |  |
|--|--|---------------------------|--|

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

|                         |   |
|-------------------------|---|
| General advice          | : Move the victim to fresh air.<br>Do not leave the victim unattended.<br>No hazards which require special first aid measures.  |
| If inhaled              | : If unconscious, place in recovery position and seek medical advice.<br>If symptoms persist, call a physician.   |
| In case of skin contact | : Wash off immediately with soap and plenty of water.   |
| In case of eye contact  | : Immediately flush eye(s) with plenty of water.<br>Remove contact lenses.<br>If eye irritation persists, consult a specialist.   |
| If swallowed            | : Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician. |

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and materials for containment and cleaning up**

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Methods for cleaning up : Use mechanical handling equipment.  
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Sweep up and shovel.  
 Do not flush with water.  
 Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage**
**7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Germany:

| Components  | CAS-No.    | Value type<br>(Form of exposure) | Control parameters     | Update     | Basis       |
|---|------------|----------------------------------|------------------------|------------|-------------|
| aluminium powder (stabilised)   | 7429-90-5  | AGW (Inhalable fraction)         | 10 mg/m <sup>3</sup>   | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                                     |            | 2;(II)                           |                        |            |             |
| aluminium powder (stabilised)   | 7429-90-5  | AGW (Alveolate fraction)         | 1,25 mg/m <sup>3</sup> | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                                     |            | 2;(II)                           |                        |            |             |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated | 64742-48-9 | AGW                              | 300 mg/m <sup>3</sup>  | 2017-11-30 | DE TRGS 900 |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

|  |  |     |                       |            |             |
|--|--|-----|-----------------------|------------|-------------|
| naphtha                                  |  |     |                       |            |             |
| Peak-limit: excursion factor (category)  | 2;(II)   |     |                       |            |             |
| Further information                      | Group exposure limit for hydrocarbon solvent mixtures<br>Commission for dangerous substances<br>See also No. 2.9 of the TRGS 900 |     |                       |            |             |
| Solvent naphtha (petroleum), light arom. | 64742-95-6   | AGW | 100 mg/m <sup>3</sup> | 2009-02-16 | DE TRGS 900 |
| Peak-limit: excursion factor (category)  | 2;(II)   |     |                       |            |             |
| Further information                      | Group exposure limit for hydrocarbon solvent mixtures<br>Commission for dangerous substances<br>See also No. 2.9 of the TRGS 900 |     |                       |            |             |

### United States of America (USA):

| Components                    | CAS-No.   | Value type (Form of exposure) | Control parameters                  | Update     | Basis |
|-------------------------------|-----------|-------------------------------|-------------------------------------|------------|-------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)              | 50 Million particles per cubic foot | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable)              | 5 mg/m <sup>3</sup>                 | 2013-10-08 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)              | 15 mg/m <sup>3</sup>                | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total)                   | 10 mg/m <sup>3</sup>                | 2013-10-08 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)     | 5 mg/m <sup>3</sup>                 | 2012-07-01 |       |
| aluminium powder              | 7429-90-5 | TWA (respirable fraction)     | 15 Million particles per cubic foot | 2012-07-01 |       |

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

|                               |           |                                     |                      |            |  |
|-------------------------------|-----------|-------------------------------------|----------------------|------------|--|
| (stabilised)                  |           |                                     |                      |            |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Total dust)                    | 10 mg/m <sup>3</sup> | 2014-11-26 |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (respirable dust fraction)      | 5 mg/m <sup>3</sup>  | 2014-11-26 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m <sup>3</sup>  | 2008-01-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA                                 | 5 mg/m <sup>3</sup>  | 2005-09-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total)                         | 15 mg/m <sup>3</sup> | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction)           | 5 mg/m <sup>3</sup>  | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)                    | 15 mg/m <sup>3</sup> | 2011-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)           | 5 mg/m <sup>3</sup>  | 2011-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total dust)                    | 15 mg/m <sup>3</sup> | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable dust fraction)      | 5 mg/m <sup>3</sup>  | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (welding fumes)                 | 5 mg/m <sup>3</sup>  | 2013-10-08 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (pyro powders)                  | 5 mg/m <sup>3</sup>  | 2013-10-08 |  |
| aluminium                     | 7429-90-5 | TWA                                 | 1 mg/m <sup>3</sup>  | 2013-03-01 |  |



**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

|                                     |           |                                       |                     |            |  |
|-------------------------------------|-----------|---------------------------------------|---------------------|------------|--|
| powder<br>(stabilised)              |           | (Respirable<br>particulate<br>matter) |                     |            |  |
| aluminium<br>powder<br>(stabilised) | 7429-90-5 | TWA (Fumes)                           | 5 mg/m <sup>3</sup> | 1989-01-19 |  |
| aluminium<br>powder<br>(stabilised) | 7429-90-5 | PEL (Welding<br>fumes)                | 5 mg/m <sup>3</sup> | 2017-10-02 |  |
| aluminium<br>powder<br>(stabilised) | 7429-90-5 | PEL (Pyro<br>powders)                 | 5 mg/m <sup>3</sup> | 2017-10-02 |  |

**8.2 Exposure controls**
**Personal protective equipment**

- Eye protection : Safety glasses
- Hand protection
- Material : Solvent-resistant gloves
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
 The exact break through time can be obtained from the protective glove producer and this has to be observed.  
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
 Recommended preventive skin protection  
 Skin should be washed after contact.  
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Long sleeved clothing

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Safety shoes  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

**Environmental exposure controls**

General advice :  
 : Prevent product from entering drains.  
 If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.  
 :

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid

Colour : silver

Odour : characteristic

pH : substance/mixture is non-soluble (in water)

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Bulk density : No data available

Flammability (solid, gas) : Combustible Solids

Auto-flammability : not auto-flammable

Upper explosion limit : No data available

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

|  |                               |
|--|-------------------------------|
| Lower explosion limit                  | : No data available           |
| Vapour pressure                        | : No data available           |
| Density                                | : 1,3 - 2,0 g/cm <sup>3</sup> |
| Solubility(ies)                        |                               |
| Water solubility                       | : insoluble                   |
| Miscibility with water                 | : immiscible                  |
| Solubility in other solvents           | : No data available           |
| Partition coefficient: n-octanol/water | : No data available           |
| Ignition temperature                   | : No data available           |
| Thermal decomposition                  | : No data available           |
| Viscosity, dynamic                     | : No data available           |
| Viscosity, kinematic                   | : No data available           |
| Flow time                              | : No data available           |
| Explosive properties                   | : Not explosive               |

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Mixture reacts slowly with water resulting in evolution of hydrogen.

Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.  
No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

### 10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Components:

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

**Solvent naphtha (petroleum), light arom. :**

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

---

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product

No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

Solvent naphtha (petroleum), light arom. (64742-95-6) :

#### Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

---

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

No data available

### 12.6 Other adverse effects

**Product:**

Additional ecological  
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
In accordance with local and national regulations.

Contaminated packaging : In accordance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

### 14.2 Proper shipping name

**ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

### 14.3 Transport hazard class

**ADR**

Not dangerous goods

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods



Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

### **IMDG**

Not dangerous goods

### **IATA**

Not dangerous goods

### **14.4 Packing group**

#### **ADR**

Not dangerous goods

#### **TDG**

Not dangerous goods

#### **CFR**

Not dangerous goods

### **IMDG**

Not dangerous goods

### **IATA**

Not dangerous goods

### **14.5 Environmental hazards**

### **14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

### **14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVERSHINE 418 Aluminiumpaste

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

|  |  |
|--|--|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).  | : Not applicable   |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer  | : Not applicable   |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast)  | : Not applicable   |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) | : Banned and/or restricted<br>(aluminium powder (stabilised))<br>(Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha)<br>(Solvent naphtha (petroleum), light arom.) |

#### 15.2 Chemical safety assessment

No data available

### SECTION 16: Other information

#### Full text of H-Statements

|      |  |
|------|--|
| H226 | : Flammable liquid and vapour.                     |
| H227 | : Combustible liquid.                              |
| H228 | : Flammable solid.                                 |
| H303 | : May be harmful if swallowed.                     |
| H304 | : May be fatal if swallowed and enters airways.    |
| H313 | : May be harmful in contact with skin.             |
| H335 | : May cause respiratory irritation.                |
| H336 | : May cause drowsiness or dizziness.               |
| H411 | : Toxic to aquatic life with long lasting effects. |

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**SILVERSHINE 418 Aluminiumpaste**

Version 3.0

Revision Date 18.05.2022

Print Date 30.11.2024

H412 : Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.