according to Regulation (EC) No. 1907/2006



## STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA ALUPOR N 513 Aluminium Paste

Product code : 024901PX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

## 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

# **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl)

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

esters. May produce an allergic reaction.

#### 2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3 013-002-00-1 01-2119529243-45		
2,2' -oxybisethanol	111-46-6	Acute Tox. 4; H302	>= 25 - < 50
	203-872-2 603-140-00-6 01-2119457857-21	Acute toxicity estimate  Acute oral toxicity: 1,120 mg/kg	
dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)	26264-05-1 247-556-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
Dhaarbaria asid mana and	07400 00 0	Olda Onan AD: 11047	0.4 0.05
Phosphoric acid, mono- and bis(C16-20-branched and linear	97468-33-2	Skin Sens. 1B; H317 Aquatic Chronic 4;	>= 0.1 - < 0.25
alkyl) esters	946-101-1	H413	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : Move the victim to fresh air.

No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

102000031786 Date of first issue: 01.08.2019 3.0 12.02.2023

advice.

If symptoms persist, call a physician.

In case of skin contact Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

Immediately flush eye(s) with plenty of water. In case of eye contact

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

None known.

## 4.3 Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Drv sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

## 5.2 Special hazards arising from the substance or mixture

This information is not available.

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment: Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use personal protective equipment. Remove all sources of ignition.
Use personal protective equipment.

Avoid dust formation.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on storage conditions

Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these			

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 02.12.2024

 3.0
 12.02.2023
 102000031786
 Date of first issue:
 01.08.2019

must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle, HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. GB EH40 TWA (Respirable 4 mg/m3 dust) Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. 2,2' -oxybisethanol 111-46-6 TWA 23 ppm GB EH40 101 mg/m3 Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health	Value
			effects	
aluminium powder	Workers	Inhalation	Long-term systemic	3.72 mg/m3
(stabilised)			effects	
	Workers	Inhalation	Long-term local	3.72 mg/m3
			effects	
	Consumers	Oral	Long-term systemic	3.95 mg/kg

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

			effects	
2,2' -oxybisethanol	Workers	Inhalation	Long-term local effects	60 mg/m3
	Workers	Skin contact	Long-term systemic effects	43 mg/kg
	Consumers	Inhalation	Long-term local effects	12 mg/m3
	Consumers	Skin contact	Long-term systemic effects	21 mg/kg
	Workers	Inhalation	Long-term systemic effects	44 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
2,2' -oxybisethanol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Water	10 mg/l
	STP	199.5 mg/l
	Fresh water sediment	20.9 mg/kg
	Soil	1.53 mg/kg
	Marine sediment	2.09 mg/kg
	water (intermittent release)	10 mg/l

### 8.2 Exposure controls

Personal protective equipment

Eye/face protection

Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local

conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

according to Regulation (EC) No. 1907/2006



## STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Relative density : No data available

Density : No data available

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

Relative vapour density : No data available

Particle Size Distribution :

9.2 Other information

Explosives : Not explosive

Flammable solids

Burning number : 1

Self-ignition : not auto-flammable

Miscibility with water : immiscible

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

## 10.6 Hazardous decomposition products

This information is not available.

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

**Components:** 

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

2,2' -oxybisethanol:

Acute oral toxicity : LD50 (Humans): 1,120 mg/kg

Acute toxicity estimate: 1,120 mg/kg

Method: Calculation method

Acute inhalation toxicity : (Rat): > 4.6 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

dodecylbenzenesulphonic acid, compound with isopropylamine (1:1):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

**Components:** 

dodecylbenzenesulphonic acid, compound with isopropylamine (1:1):

Result : Skin irritation

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

Result : No skin irritation

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

## Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks : Product dust may be irritating to eyes, skin and respiratory

system.

## **Components:**

## dodecylbenzenesulphonic acid, compound with isopropylamine (1:1):

Result : Eye irritation

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

#### **Components:**

#### Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

Result : The product is a skin sensitiser, sub-category 1B.

## Germ cell mutagenicity

Not classified based on available information.

# Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Further information**

**Product:** 

Remarks : No data available

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

## **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Components:**

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

## 12.7 Other adverse effects

**Product:** 

Additional ecological

information

: No data available

# **SECTION 13: Disposal considerations**

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

# 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

2,2' -oxybisethanol (Number on list

3)

dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)

(Number on list 3)

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters (Number on list 3) 2,2'-iminodiethanol (Number on list

3)

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

: Not applicable

#### 15.2 Chemical safety assessment

No data available

#### **SECTION 16: Other information**

#### Full text of H-Statements

H228 : Flammable solid.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

according to Regulation (EC) No. 1907/2006



# STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 02.12.2024

3.0 12.02.2023 102000031786 Date of first issue: 01.08.2019

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory: TRGS - Technical Rule for Hazardous Substances: TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN