

Date of impression 23.04.2025/14:31:10
page/of 1/1

edition 23.04.2025

material denomination **HYDROSHINE WS 4001**
material-no. 053471AN0
material description Effect pigment dispersion based on highly brilliant
PVD-aluminium-pigments with a heavy metal free encapsulation
The solvent contained is isopropanol / butylglykol
Pigmentcomposition:

material specification

| insp. characteristic | specification | unit |
|--|----------------------|-------------|
| TI00004 pigment content / non volatile | 8,5 - 11,5 | % |
| TI00004 volatile content | 88,5 - 91,5 | % |
| TI00270 wire rod draw down | pass | |
| TI00489 D 50 | 9,0 - 12,0 | µm |
| TI00538 wire rod draw down | pass | |
| total shelf life in month: 24 | | |

EC-safety data sheet-no. 053471AN0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.
The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.
We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

| | | |
|--------------------|------------|-----------------|
| Draft | Approval | Release |
| Technical services | Production | Quality control |
| 23.04.2025 | 23.04.2025 | 23.04.2025 |

This document has been printed automatically and will not be signed.