

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : STAPA NDF 130 Aluminium Paste  
Material number : 052112G60

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Skin corrosion/irritation, Category 2, H315  
Specific target organ toxicity - single exposure, Category 3,  
Central nervous system, H336

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

Short-term (acute) aquatic hazard, Category 3, H402  
Long-term (chronic) aquatic hazard, Category 3, H412

**GHS-Labeling**

Symbol(s)

:



Signal word

:

Warning

Hazard statements

:

H315: Causes skin irritation.  
H336: May cause drowsiness or dizziness.  
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

:

**Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.  
**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**

Identification

CAS-No.

Distillates (petroleum), hydrotreated light

64742-47-8

Solvent naphtha (petroleum), light arom.

64742-95-6

**Other hazards which do not result in classification**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

Combustible Solids

**SECTION 3: Composition/information on ingredients**

Substance name : AL-PASTE NDF 130 (EAL)

Substance No. :

**Hazardous components**

| Chemical name   | CAS-No.<br>EINECS-No.   | Classification and<br>labelling   | Concentration[%] |
|---|-------------------------|---|------------------|
| aluminium powder (stabilised)   | 7429-90-5<br>231-072-3  | Flam. Sol.;1;H228   | 50 - 100         |
| Distillates (petroleum), hydro-<br>treated light; Kerosine —<br>unspecified | 64742-47-8<br>265-149-8 | Flam. Liq.;4;H227<br>;2;H315<br>STOT SE;3;H336<br>Asp. Tox.;1;H304<br>Aquatic Acute;3;H402<br>Aquatic<br>Chronic;3;H412 | 20 - 25          |
| Solvent naphtha (petroleum),<br>light arom.                                 | 64742-95-6              | Flam. Liq.;3;H226<br>STOT SE;3;H335,<br>H336<br>Asp. Tox.;1;H304<br>Aquatic Acute;2;H401<br>Aquatic<br>Chronic;2;H411   | 2,5 - 10         |
| 1,2,4-trimethylbenzene  | 95-63-6<br>202-436-9    | Flam. Liq.;3;H226<br>Acute Tox.;4;H332<br>Skin Irrit.;2;H315<br>Eye Irrit.;2B;H320                                      | 1 - 2,5          |

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|  |                         |   |        |
|--|-------------------------|---|--------|
|  |                         | STOT SE;3;H335<br>Aquatic<br>Chronic;2;H411 |        |
| Fatty acids, C14-18 and C16-18-unsatd. | 67701-06-8<br>266-930-6 | Acute Tox.;5;H313                           | 1 - 10 |


For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

|                         |  |
|-------------------------|--|
| General advice          | : Move the victim to fresh air.<br>Do not leave the victim unattended.<br>Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.  |
| If inhaled              | : Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.   |
| In case of skin contact | : Wash off immediately with soap and plenty of water.<br>If skin irritation persists, call a physician.<br>If on skin, rinse well with water.<br>If on clothes, remove clothes.                                |
| In case of eye contact  | : Immediately flush eye(s) with plenty of water.<br>Flush eyes with water as a precaution.<br>Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
| If swallowed            | : Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.                                |

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

|             |              |   |
|-------------|--------------|---|
| Page 4 / 23 | 102000001203 | A member of  <b>ALTANA</b> |
|-------------|--------------|---|

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust  
formation. Ensure adequate ventilation.

Avoid formation of respirable particles. Do not breathe  
vapours/dust. Avoid exposure - obtain special instructions  
before use. Avoid contact with skin and eyes. For personal  
protection see section 8. Smoking, eating and drinking should  
be prohibited in the application area. Provide sufficient air  
exchange and/or exhaust in work rooms. Dispose of rinse  
water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of  
ignition. Earthing of containers and apparatuses is essential.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

**Germany:**

| Components   | CAS-No.  | Value type<br>(Form of exposure) | Control parameters     | Update     | Basis       |
|--|--|----------------------------------|------------------------|------------|-------------|
| aluminium powder (stabilised)  | 7429-90-5  | AGW (Inhalable fraction)         | 10 mg/m <sup>3</sup>   | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                              | 2;(II)   |                                  |                        |            |             |
| Further information  | Commission for dangerous substances Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). |                                  |                        |            |             |
| aluminium powder (stabilised)  | 7429-90-5  | AGW (Alveolate fraction)         | 1,25 mg/m <sup>3</sup> | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                              | 2;(II)   |                                  |                        |            |             |
| Further information  | Commission for dangerous substances Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). |                                  |                        |            |             |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8   | AGW                              | 300 mg/m <sup>3</sup>  | 2017-11-30 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                              | 2;(II)   |                                  |                        |            |             |
| Further information  | Group exposure limit for hydrocarbon solvent mixtures Commission for dangerous substances See also No. 2.9 of the TRGS 900                     |                                  |                        |            |             |
| Solvent naphtha (petroleum), light arom.                             | 64742-95-6   | AGW                              | 100 mg/m <sup>3</sup>  | 2009-02-16 | DE TRGS 900 |
| Peak-limit: excursion factor (category)                              | 2;(II)   |                                  |                        |            |             |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|  |            |   |                                 |            |             |
|--|------------|---|---------------------------------|------------|-------------|
| Further information                      |            | Group exposure limit for hydrocarbon solvent mixtures<br>Commission for dangerous substances<br>See also No. 2.9 of the TRGS 900  |                                 |            |             |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | AGW   | 100 mg/m <sup>3</sup>           | 2009-02-16 | DE TRGS 900 |
| Peak-limit: excursion factor (category)  |            | 2;(II)  |                                 |            |             |
| Further information                      |            | Group exposure limit for hydrocarbon solvent mixtures<br>Commission for dangerous substances<br>See also No. 2.9 of the TRGS 900  |                                 |            |             |
| 1,2,4-trimethylbenzene                   | 95-63-6    | TWA   | 20 ppm<br>100 mg/m <sup>3</sup> | 2000-06-16 | 2000/39/EC  |
| Further information                      |            | Indicative  |                                 |            |             |
| 1,2,4-trimethylbenzene                   | 95-63-6    | AGW   | 20 ppm<br>100 mg/m <sup>3</sup> | 2006-01-01 | DE TRGS 900 |
| Peak-limit: excursion factor (category)  |            | 2;(II)  |                                 |            |             |
| Further information                      |            | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).<br>European Union (The EU has established a limit value: deviations in value and peak limit are possible)<br>When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                                 |            |             |
| 1,2,4-trimethylbenzene                   | 95-63-6    | AGW   | 50 mg/m <sup>3</sup>            | 2017-11-30 | DE TRGS 900 |
| Peak-limit: excursion factor (category)  |            | 2;(II)  |                                 |            |             |
| Further information                      |            | Group exposure limit for hydrocarbon solvent mixtures<br>Commission for dangerous substances<br>See also No. 2.9 of the TRGS 900  |                                 |            |             |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

### United States of America (USA):

| Components                    | CAS-No.   | Value type<br>(Form of exposure) | Control parameters                  | Update     | Basis |
|-------------------------------|-----------|----------------------------------|-------------------------------------|------------|-------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)                 | 50 Million particles per cubic foot | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable)                 | 5 mg/m3                             | 2013-10-08 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)                 | 15 mg/m3                            | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total)                      | 10 mg/m3                            | 2013-10-08 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)        | 5 mg/m3                             | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)        | 15 Million particles per cubic foot | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Total dust)                 | 10 mg/m3                            | 2014-11-26 |       |
| aluminium powder (stabilised) | 7429-90-5 | PEL (respirable dust fraction)   | 5 mg/m3                             | 2014-11-26 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction)        | 1 mg/m3                             | 2008-01-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA                              | 5 mg/m3                             | 2005-09-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total)                      | 15 mg/m3                            | 1989-01-19 |       |
| aluminium                     | 7429-90-5 | TWA                              | 5 mg/m3                             | 1989-01-19 |       |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|  |            |                                |                                    |            |  |
|--|------------|--------------------------------|------------------------------------|------------|--|
| powder (stabilised)  |            | (Respirable fraction)          |                                    |            |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (total dust)               | 15 mg/m <sup>3</sup>               | 2011-07-01 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (respirable fraction)      | 5 mg/m <sup>3</sup>                | 2011-07-01 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (Total dust)               | 15 mg/m <sup>3</sup>               | 1989-01-19 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (respirable dust fraction) | 5 mg/m <sup>3</sup>                | 1989-01-19 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (welding fumes)            | 5 mg/m <sup>3</sup>                | 2013-10-08 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (pyro powders)             | 5 mg/m <sup>3</sup>                | 2013-10-08 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (Respirable fraction)      | 1 mg/m <sup>3</sup>                | 2013-03-01 |  |
| aluminium powder (stabilised)  | 7429-90-5  | TWA (Fumes)                    | 5 mg/m <sup>3</sup>                | 1989-01-19 |  |
| aluminium powder (stabilised)  | 7429-90-5  | PEL (Welding fumes)            | 5 mg/m <sup>3</sup>                | 2017-10-02 |  |
| aluminium powder (stabilised)  | 7429-90-5  | PEL (Pyro powders)             | 5 mg/m <sup>3</sup>                | 2017-10-02 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA                            | 500 ppm<br>2 000 mg/m <sup>3</sup> | 2007-01-01 |  |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|  |            |                   |                                    |            |  |
|--|------------|-------------------|------------------------------------|------------|--|
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA               | 200 mg/m <sup>3</sup>              | 2010-03-01 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA               | 400 ppm<br>1 600 mg/m <sup>3</sup> | 1989-01-19 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA (Mist)        | 5 mg/m <sup>3</sup>                | 2011-07-01 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA (Mist)        | 5 mg/m <sup>3</sup>                | 1989-01-19 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | TWA (Mist)        | 5 mg/m <sup>3</sup>                | 2013-10-08 |  |
| Distillates (petroleum), hydro-treated light; Kerosine — unspecified | 64742-47-8 | ST (Mist)         | 10 mg/m <sup>3</sup>               | 2013-10-08 |  |
| Distillates (petroleum), hydro-                                      | 64742-47-8 | PEL (particulate) | 5 mg/m <sup>3</sup>                | 2014-11-26 |  |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|   |            |     |                                    |            |  |
|---|------------|-----|------------------------------------|------------|--|
| treated light;<br>Kerosine —<br>unspecified       |            |     |                                    |            |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 500 ppm<br>2 000 mg/m <sup>3</sup> | 2007-01-01 |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 500 ppm<br>2 000 mg/m <sup>3</sup> | 2007-01-01 |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 200 mg/m <sup>3</sup>              | 2010-03-01 |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 200 mg/m <sup>3</sup>              | 2010-03-01 |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 400 ppm<br>1 600 mg/m <sup>3</sup> | 1989-01-19 |  |
| Solvent<br>naphtha<br>(petroleum),<br>light arom. | 64742-95-6 | TWA | 400 ppm<br>1 600 mg/m <sup>3</sup> | 1989-01-19 |  |
| 1,2,4-<br>trimethylbenz<br>ene                    | 95-63-6    | TWA | 25 ppm<br>125 mg/m <sup>3</sup>    | 2013-10-08 |  |
| 1,2,4-<br>trimethylbenz<br>ene                    | 95-63-6    | TWA | 25 ppm                             | 2014-03-01 |  |
| 1,2,4-<br>trimethylbenz<br>ene                    | 95-63-6    | TWA | 25 ppm<br>125 mg/m <sup>3</sup>    | 1989-01-19 |  |
| 1,2,4-<br>trimethylbenz                           | 95-63-6    | PEL | 25 ppm<br>125 mg/m <sup>3</sup>    | 2014-11-26 |  |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA NDF 130 Aluminium Paste

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|     |  |  |  |  |  |
|-----|--|--|--|--|--|
| ene |  |  |  |  |  |
|-----|--|--|--|--|--|

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

: In the case of dust or aerosol formation use respirator with an approved filter.

**Environmental exposure controls**

General advice :  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.  
:

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid

Colour : silver

Odour : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : 170 °C

Flash point : No data available

Bulk density : No data available

Flammability (solid, gas) : Combustible Solids

Auto-flammability : not auto-flammable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|  |                     |
|--|---------------------|
| Density                                | : No data available |
| Water solubility                       | : No data available |
| Miscibility with water                 | : No data available |
| Solubility in other solvents           | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature                   | : 240 °C            |
| Thermal decomposition                  | : No data available |
| Viscosity, dynamic                     | : No data available |
| Viscosity, kinematic                   | : No data available |
| Flow time                              | : No data available |
| Explosive properties                   | : Not explosive     |

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.



**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.  
Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****1,2,4-trimethylbenzene :**

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

**Fatty acids, C14-18 and C16-18-unsatd. :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 46 mg/l

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Rabbit: &gt; 3 160 mg/kg

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

Product dust may be irritating to eyes, skin and respiratory system.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****Distillates (petroleum), hydrotreated light (64742-47-8) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**Solvent naphtha (petroleum), light arom. (64742-95-6) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

hazard

**1,2,4-trimethylbenzene (95-63-6) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|                        |  |
|------------------------|--|
| Product                | : The product should not be allowed to enter drains, water courses or the soil.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company.<br>In accordance with local and national regulations. |
| Contaminated packaging | : Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum.<br>In accordance with local and national regulations.   |

**SECTION 14: Transport information****14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group****14.5 Environmental hazards****14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

|   |                  |
|---|------------------|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer                   | : Not applicable |
| Regulation (EC) No 850/2004 on persistent organic pollutants                              | : Not applicable |

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

|      |  |
|------|--|
| H226 | : Flammable liquid and vapour.                       |
| H227 | : Combustible liquid.                                |
| H228 | : Flammable solid.                                   |
| H304 | : May be fatal if swallowed and enters airways.      |
| H313 | : May be harmful in contact with skin.               |
| H315 | : Causes skin irritation.                            |
| H320 | : Causes eye irritation.                             |
| H332 | : Harmful if inhaled.                                |
| H335 | : May cause respiratory irritation.                  |
| H336 | : May cause drowsiness or dizziness.                 |
| H401 | : Toxic to aquatic life.                             |
| H402 | : Harmful to aquatic life.                           |
| H411 | : Toxic to aquatic life with long lasting effects.   |
| H412 | : Harmful to aquatic life with long lasting effects. |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## **STAPA NDF 130 Aluminium Paste**

Version 3.0

Revision Date 05.12.2019

Print Date 03.12.2024

---