

Date of impression 09.12.2024/07:01:20
page/of 1/1

edition 24.11.2023

material denomination **Ti6Al4V ASTM Gd5 powder < 25 µm**
material-no. 031256UD0
material description spherical powder, atomized with inert gas

material specification

insp. characteristic	specification	unit
TI00000 Al	5,50 - 6,75	%
TI00000 C	<= 0,08	%
TI00000 Fe	<= 0,40	%
TI00000 H2	<= 0,015	%
TI00000 N2	<= 0,05	%
TI00000 O2	<= 0,20	%
TI00000 Ti		%
TI00000 V	3,5 - 4,5	%
TI00000 Other elements, each	<= 0,1	%
TI00000 Other elements, total	<= 0,4	%
TI00526 bulk density, ASTM B703	>= 1,9	g/cm3
TI00009 D10	7 - 10	µm
TI00009 D50	13 - 18	µm
TI00009 D90	23 - 30	µm

total shelf life in month: 120

EC-safety data sheet-no. 031256UD0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.
The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.
We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
24.11.2023	24.11.2023	24.11.2023

This document has been printed automatically and will not be signed.