

METALSTAR UV SELECT 21-2077 SILVER

Version Revision Date: SDS Number: Date of last issue: 02/20/2025 5.0 02/27/2025 102000026882 Date of first issue: 03/26/2018

SECTION 1. IDENTIFICATION

Product name METALSTAR UV SELECT 21-2077 SILVER

Product code 046439EF0

Manufacturer or supplier's details

Company name of supplier **ECKART America Corporation**

830 East Erie Street Address

Painesville OH 44077

Telephone 866-458-7837

(440) 954-7600

Telefax (440) 354-6224

e-mail adresse info.eckart.america.oh@altana.com

Emergency telephone **CHEMTREC**: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Eye irritation Category 2A

Skin sensitization Category 1

Specific target organ toxicity : Category 2 (Kidney)

- repeated exposure

GHS label elements

Hazard pictograms





Signal Word Warning

Hazard Statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction.



METALSTAR UV SELECT 21-2077 SILVER

Version Revision Date: 5.0 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

H319 Causes serious eye irritation.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

Precautionary Statements

Prevention:

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be

allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

> for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel

unwell.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash

before reuse.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-

ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1oxo-2-propen-1-vI)oxvI-

Phosphonic acid, P-dodecyl-

Phenol, 4-methoxy-

Other hazards

None known.



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Aluminum | 7429-90-5 | >= 10 - < 20 |
| ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate | 84434-11-7 | >= 5 - < 10 |
| Poly(oxy-1,2-ethanediyl), .alphahydroomega[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) | 28961-43-5 | >= 5 - < 10 |
| 2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester | 42978-66-5 | >= 1 - < 5 |
| Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega[(1-oxo-2-propen-1-yl)oxy]- | 52408-84-1 | >= 1 - < 5 |
| Phosphonic acid, P-dodecyl- | 5137-70-2 | >= 1 - < 5 |
| Phenol, 4-methoxy- | 150-76-5 | >= 0.1 - < 1 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Take the victim into fresh air.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

If inhaled : Remove to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms : Causes skin irritation.

and effects, both acute and May cause an allergic skin reaction.



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

delayed Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry sand

ABC powder

Foam

Unsuitable extinguishing

media

High volume water jet

Carbon dioxide (CO2)

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Use personal protective equipment.

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

Methods and materials for containment and cleaning up Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling

: Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma. allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

Conditions for safe storage

Earthing of containers and apparatuses is essential.

Reaction with water liberates extremely flammable gas

(hydrogen)

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from sources of ignition - No smoking.

Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards. Protect from humidity and water.

Technical

measures/Precautions

Materials to avoid

Do not store near acids.

Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|--|--|-----------|
| Aluminum | 7429-90-5 | TWA (total dust) | 50 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (Respirable) | 5 mg/m3 | NIOSH REL |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-3 |
| | | TWA (total) | 10 mg/m3 | NIOSH REL |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-3 |
| | | TWA (respirable fraction) | 15 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (Respirable particulate matter) | 1 mg/m3 | ACGIH |
| | | TWA | 5 mg/m3 (Aluminum) | NIOSH REL |
| | | TWA (Total) | 15 mg/m3 (Aluminum) | OSHA P0 |
| | | TWA (Respirable fraction) | 5 mg/m3 (Aluminum) | OSHA P0 |
| | | TWA (total dust) | 15 mg/m3 (Aluminum) | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 (Aluminum) | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 (Aluminum) | OSHA P0 |



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

| | | TWA (respirable dust fraction) | 5 mg/m3 (Aluminum) | OSHA P0 |
|--------------------|----------|--|-----------------------|-----------|
| | | TWA (welding fumes) | 5 mg/m3 (Aluminum) | NIOSH REL |
| | | TWA (pyro powders) | 5 mg/m3 (Aluminum) | NIOSH REL |
| | | TWA (Respirable particulate matter) | 1 mg/m3 (Aluminum) | ACGIH |
| | | TWA (Fumes) | 5 mg/m3 | OSHA P0 |
| | | TWA (powder) | 5 mg/m3 (Aluminum) | OSHA P0 |
| Phenol, 4-methoxy- | 150-76-5 | TWA | 5 mg/m3 | ACGIH |
| | | TWA | 5 mg/m3 | NIOSH REL |
| | | TWA | 5 mg/m3 | OSHA P0 |

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Eye protection : Goggles

Tightly fitting safety goggles



METALSTAR UV SELECT 21-2077 SILVER

Version Revision Date: SDS Number: Date of last issue: 02/20/2025 5.0 02/27/2025 102000026882 Date of first issue: 03/26/2018

Skin and body protection Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance viscous liquid

Color silver

Odor characteristic Odor Threshold No data available

pΗ substance/mixture is non-soluble (in water)

Melting point/ range Not applicable

> 100 °C Boiling point/boiling range

Flash point > 100 °C

Evaporation rate No data available Flammability (solid, gas) No data available Upper explosion limit / Upper No data available

flammability limit

Lower explosion limit / Lower

flammability limit

Vapor pressure No data available Relative density No data available

Density 1.1 g/cm3

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-No data available

octanol/water

No data available Autoignition temperature Decomposition temperature No data available Viscosity No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Chemical stability Contact with acids and alkalis may release hydrogen. Possibility of hazardous

No data available

No decomposition if stored and applied as directed. reactions

Conditions to avoid Do not allow evaporation to dryness.

No data available

Acids Incompatible materials

Bases

Oxidizing agents



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Acute oral toxicity : (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Acute oral toxicity : (Rat): 2,000 mg/kg

Acute inhalation toxicity : (Rat): 0.000545 mg/l

Exposure time: 7 h
Test atmosphere: vapor

Acute dermal toxicity : (Rabbit): 2,000 mg/kg

Method: OECD Test Guideline 402

Phenol, 4-methoxy-:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

Skin corrosion/irritation

Causes skin irritation. Causes skin irritation.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: May cause skin irritation and/or dermatitis.

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Result: Skin irritation

Phosphonic acid, P-dodecyl-:

Result: Corrosive after 3 minutes to 1 hour of exposure



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

Serious eye damage/eye irritation

Causes serious eye irritation. Causes serious eye irritation.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Vapors may cause irritation to the eyes, respiratory system and the skin.

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: Irritating to eyes.

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Result: Eye irritation

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: Eye irritation

Phenol, 4-methoxy-:

Result: Eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Respiratory sensitization

Not classified due to lack of data.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Result: May cause sensitization by skin contact.



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: May cause sensitization by skin contact.

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Assessment: May cause sensitization by skin contact.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: May cause sensitization by skin contact.

Phenol, 4-methoxy-:

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.

Not classified due to lack of data.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Not classified due to lack of data.

STOT-single exposure

Not classified based on available information.

Not classified due to lack of data.



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

Components:

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure. May cause damage to organs (Kidney) through prolonged or repeated exposure.

Components:

Phosphonic acid, P-dodecyl-:

Target Organs: Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Not classified due to lack of data.

Further information

Components:

Phosphonic acid, P-dodecyl-:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



METALSTAR UV SELECT 21-2077 SILVER

Version Revi

Revision Date: SDS Number: 02/27/2025 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Phosphonic acid, P-dodecyl-: Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Additional ecological

: An environmental hazard cannot be excluded in the event of

information unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-

oxo-2-propen-1-yl)oxy]-:

Additional ecological

: No data available

information

information

Phosphonic acid, P-dodecyl-:

Additional ecological

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR

Not regulated as a dangerous good

49 CFR : Not classified as dangerous in the meaning of transport

regulations.

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Remarks : Not classified as dangerous in the meaning of transport

regulations.

ADR : Not classified as dangerous in the meaning of transport

regulations.

IATA-DGR : Not classified as dangerous in the meaning of transport

regulations.

IMDG-Code : Not classified as dangerous in the meaning of transport

regulations.

Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.



METALSTAR UV SELECT 21-2077 SILVER

Version 5.0

Revision Date: 02/27/2025

SDS Number: 102000026882

Date of last issue: 02/20/2025 Date of first issue: 03/26/2018

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Aluminum 7429-90-5 >= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Aluminum 7429-90-5

Pennsylvania Right To Know

Soybean oil, epoxidized, acrylate 91722-14-4

Aluminum 7429-90-5

Kein gefährlicher Stoff oder gefährliches Gemisch gemäß dem Not Assigned Global Harmonisierten System (GHS).



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-28961-43-5

propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-

propanediol (3:1)

2-Propenoic acid, 1,1'-[(1-methyl-1,2- 42978-66-5

ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''- 52408-84-1

1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Aluminum 7429-90-5

California Permissible Exposure Limits for Chemical Contaminants

Aluminum 7429-90-5

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL nor NDSL.

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule: 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2067275-86-7 oxirane, 4-(dimethylamino)benzoate

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2067275-86-7

oxirane, 4-(dimethylamino)benzoate

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/27/2025



METALSTAR UV SELECT 21-2077 SILVER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/20/2025

 5.0
 02/27/2025
 102000026882
 Date of first issue: 03/26/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8