

## **PLATINVARIO AE-82002**

Version Revision Date: SDS Number: Date of last issue: 12/05/2019 2.1 01/24/2023 102000000738 Date of first issue: 03/21/2018

#### **SECTION 1. IDENTIFICATION**

Product name : PLATINVARIO AE-82002

Product code 053175JD0

Manufacturer or supplier's details

Company name of supplier **ECKART America Corporation** 

830 East Erie Street Address

Painesville OH 44077

Telephone 866-458-7837

(440) 954-7600

**Telefax** (440) 354-6224

e-mail adresse info.eckart.america.oh@altana.com

Emergency telephone **CHEMTREC**: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable solids : Category 1

Eye irritation Category 2A

- single exposure

Specific target organ toxicity : Category 3 (Central nervous system)

**GHS** label elements

Hazard pictograms





Signal Word Danger

Hazard Statements H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

Precautionary Statements :

Prevention:

P210 Keep away from heat/ sparks/ open flames/

hot surfaces. No smoking.

P240 Ground/bond container and receiving

equipment.

P241 Use explosion-proof electrical/ ventilating/

lighting/ equipment.

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P370 + P378 In case of fire: Use for extinction: Special

powder for metal fires.

P370 + P378 In case of fire: Use for extinction: Dry sand.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label: Acetic acid ethyl ester

Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Acetic acid ethyl ester	141-78-6	>= 70 - < 90



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Take the victim into fresh air.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Wash off immediately with soap and plenty of water.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

Causes serious eye irritation.

May cause drowsiness or dizziness.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

Carbon dioxide (CO2)

ABC powder

Specific hazards during fire

fighting

Contact with water liberates extremely flammable gas

(hydrogen).

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for fire-fighters

Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
Use personal protective equipment.
Use personal protective equipment.

Avoid dust formation.

Remove all sources of ignition.

Environmental precautions

The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against:

fire and explosion

Earthing of containers and apparatuses is essential.

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Avoid dust formation.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national



## **PLATINVARIO AE-82002**

Version Revision Date: SDS Number: Date of last issue: 12/05/2019 2.1 01/24/2023 102000000738 Date of first issue: 03/21/2018

regulations.

Conditions for safe storage Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Keep container closed when not in use.

Keep away from sources of ignition - No smoking.

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Protect from humidity and water. Technical

measures/Precautions

Do not allow to dry. Materials to avoid Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

No decomposition if stored and applied as directed.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetic acid ethyl ester	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m3	NIOSH REL
		TWA	400 ppm 1,400 mg/m3	OSHA Z-1
		TWA	400 ppm 1,400 mg/m3	OSHA P0
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-3



# **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

(respirable fraction)		
TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
TWA (Respirable particulate matter)	1 mg/m3	ACGIH
TWA	5 mg/m3 (Aluminum)	NIOSH REL
TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
TWA (Fumes)	5 mg/m3	OSHA P0
TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0

### Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection



## **PLATINVARIO AE-82002**

Version Revision Date: SDS Number: Date of last issue: 12/05/2019 2.1 01/24/2023 102000000738 Date of first issue: 03/21/2018

Material Solvent-resistant gloves (butyl-rubber)

Remarks Take note of the information given by the producer

> concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Eye protection Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

When using do not eat or drink. Hygiene measures

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance Pasty solid Color silver

Odor characteristic Odor Threshold No data available

substance/mixture is non-soluble (in water)

Melting point/freezing point No data available

Boiling point/boiling range : 76 °C

Flash point -4 °C

Evaporation rate No data available Flammability (solid, gas) No data available Auto-flammability not auto-flammable No data available

Upper explosion limit / Upper

flammability limit

Lower explosion limit / Lower No data available



## **PLATINVARIO AE-82002**

Version Revision Date: SDS Number: Date of last issue: 12/05/2019 2.1 01/24/2023 102000000738 Date of first issue: 03/21/2018

flammability limit

Vapor pressure No data available Relative density No data available Solubility(ies) No data available Partition coefficient: n-No data available

octanol/water

No data available Autoignition temperature Decomposition temperature No data available Viscosity No data available

Explosive properties Not explosive Vapors may form explosive mixture with air.

#### **SECTION 10. STABILITY AND REACTIVITY**

No decomposition if stored and applied as directed. Reactivity No decomposition if stored and applied as directed. Chemical stability Reacts with alkalis, acids, halogenes and oxidizing agents.

Possibility of hazardous

reactions

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapors may form explosive mixture with air. Stable under recommended storage conditions.

Conditions to avoid Do not allow to dry.

Heat, flames and sparks.

Acids Incompatible materials

Bases

Oxidizing agents

Highly halogenated compounds

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Acute toxicity

Not classified based on available information.

#### **Components:**

Acetic acid ethyl ester:

Acute oral toxicity (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l

> Exposure time: 4 h Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.



## **PLATINVARIO AE-82002**

Version 2.1

Revision Date: 01/24/2023

SDS Number: 102000000738

Date of last issue: 12/05/2019 Date of first issue: 03/21/2018

#### Serious eye damage/eye irritation

Causes serious eye irritation.

### **Components:**

## Acetic acid ethyl ester:

Result: Eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause drowsiness or dizziness.

### **Components:**

## Acetic acid ethyl ester:

Assessment: May cause drowsiness or dizziness.

## STOT-repeated exposure

Not classified based on available information.



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

#### Aspiration toxicity

Not classified based on available information.

**Further information** 

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

### Acetic acid ethyl ester:

Toxicity to daphnia and other :

aquatic invertebrates

(Daphnia): 717 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 1325

Proper shipping name : Flammable solids, organic, n.o.s.

(Aluminum pigment paste)

Class : 4.1 Packing group : II

Labels : FLAMMABLE SOLID



## **PLATINVARIO AE-82002**

Version Revision Date: SDS Number: Date of last issue: 12/05/2019 01/24/2023 2.1 102000000738 Date of first issue: 03/21/2018

**ERG Code** 133 Marine pollutant no

**International Regulations** 

**IATA-DGR** 

UN 1325 UN/ID No.

Proper shipping name Flammable solid, organic, n.o.s.

(Aluminium pigment paste)

Class 4.1 Packing group Ш

Labels Flammable Solid

Packing instruction (cargo 448

aircraft)

Packing instruction 445

(passenger aircraft)

**IMDG-Code** 

UN number UN 1325

Proper shipping name FLAMMABLE SOLID, ORGANIC, N.O.S.

(Aluminium pigment paste)

Class 4.1 Packing group Ш Labels 4.1 EmS Code F-G S-G

Marine pollutant no

Remarks IMDG Code segregation group 15 - Powdered metals

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
Acetic acid ethyl ester	141-78-6	5000
Phosphoric acid	7664-38-2	5000

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



## **PLATINVARIO AE-82002**

Version 2.1 Revision Date: 01/24/2023

SDS Number: 102000000738

Date of last issue: 12/05/2019 Date of first issue: 03/21/2018

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Aluminum 7429-90-5 >= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Acetic acid ethyl ester 141-78-6

%

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Phosphoric acid

7664-38-2

%

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Phosphoric acid

7664-38-2

%

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations** 

Massachusetts Right To Know

Acetic acid ethyl ester 141-78-6

Aluminum 7429-90-5

Pennsylvania Right To Know

Acetic acid ethyl ester 141-78-6



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

Aluminum 7429-90-5

### California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### California List of Hazardous Substances

Acetic acid ethyl ester 141-78-6

Aluminum 7429-90-5

#### California Permissible Exposure Limits for Chemical Contaminants

Acetic acid ethyl ester 141-78-6

Aluminum 7429-90-5

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average



## **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature: SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/24/2023

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



# **PLATINVARIO AE-82002**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/05/2019

 2.1
 01/24/2023
 102000000738
 Date of first issue: 03/21/2018

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8