

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

SECTION 1. IDENTIFICATION

Product name : TOPSTAR G2 UV LED 21-0200 Bright Silver
Product code : 046787EF0M1

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation
Address : 830 East Erie Street
Painesville OH 44077
Telephone : 866-458-7837
(440) 954-7600
Telefax : (440) 354-6224
e-mail adresse : info.eckart.america.oh@altana.com
Emergency telephone : **CHEMTREC:** 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC)
US: +1 866 928 0789 (Toll free)
Canada: +1 800 579 7421 (Toll Free)
Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Eye irritation : Category 2A
Skin sensitization : Category 1
Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Precautionary Statements

:

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous ingredients which must be listed on the label:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.,.alpha."-1,2,3-propanetriyltris[.omega.-{(1-oxo-2-propen-1-yl)oxy}-

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-{(1-oxo-2-propen-1-yl)oxy}-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

2-Propenoic acid, 1,1'-[2-ethyl-2-[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-

Other hazards

None known.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-	52408-84-1	>= 30 - < 50
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5	>= 20 - < 30
Aluminum	7429-90-5	>= 5 - < 10
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	84434-11-7	>= 1 - < 5
2-Propenoic acid, 1,1'-[2-ethyl-2-[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester	15625-89-5	>= 0.1 - < 1
2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-	7078-98-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on skin, rinse well with water.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May cause an allergic skin reaction.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Causes serious eye irritation.
Suspected of causing cancer.

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|--|
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment. |
| General advice | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Environmental precautions | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal. |
-

SECTION 7. HANDLING AND STORAGE

- | | | |
|---|---|--|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| Advice on safe handling | : | Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes. |
-

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m3	OSHA P0

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version
7.1Revision Date:
02/20/2025SDS Number:
102000027250Date of last issue: 02/23/2023
Date of first issue: 03/26/2018

			(Aluminum)	
		TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
		TWA (Fumes)	5 mg/m3	OSHA P0
		TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0
2-Propenoic acid, 1,1'-[2-ethyl- 2-[[[(1-oxo-2-propen-1- yl)oxy]methyl]-1,3-propanediyl] ester	15625-89-5	TWA	1 mg/m3	US WEEL

Personal protective equipment

Hand protection

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	silver
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	Not applicable
Boiling point/boiling range	:	> 100 °C
Flash point	:	> 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	1.0 - 1.2 g/cm ³
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	No data available

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.
Not classified due to lack of data.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Components:**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Acute oral toxicity : (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Not classified due to lack of data.

Components:**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Remarks: May cause skin irritation and/or dermatitis.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Causes serious eye irritation.

Components:**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.,.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-]:**

Result: Eye irritation

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: Irritating to eyes.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Vapors may cause irritation to the eyes, respiratory system and the skin.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Eye irritation

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Respiratory sensitization

Not classified due to lack of data.

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-]:

Result: May cause sensitization by skin contact.

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: May cause sensitization by skin contact.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Result: May cause sensitization by skin contact.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: May cause sensitization by skin contact.

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-:

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Suspected of causing cancer.

Components:

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Carcinogenicity - : Limited evidence of carcinogenicity in animal studies

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Assessment

IARC

Group 2B: Possibly carcinogenic to humans

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester 15625-89-5

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.
Not classified due to lack of data.

STOT-single exposure

Not classified based on available information.
Not classified due to lack of data.

STOT-repeated exposure

Not classified based on available information.
Not classified due to lack of data.

Aspiration toxicity

Not classified based on available information.
Not classified due to lack of data.

Further information

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-:**Ecotoxicology Assessment**

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:**

Additional ecological information : No data available

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**Domestic regulation****49 CFR**

Not regulated as a dangerous good

International Regulations**UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Remarks : For single packagings $\leq 5L / 5 \text{ kg}$, or combination
packagings containing inner packagings $\leq 5L / 5 \text{ kg}$ net per
inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197
IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Carcinogenicity
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels
established by SARA Title III, Section 313:

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

Aluminum	7429-90-5	>= 5 - < 10 %
----------	-----------	---------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations**Massachusetts Right To Know**

Aluminum	7429-90-5
----------	-----------

Pennsylvania Right To Know

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.,.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-	52408-84-1
Kein gefährlicher Stoff laut GHS.	Not Assigned
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5
Aluminum	7429-90-5
Kein gefährlicher Stoff oder gefährliches Gemisch gemäß dem Global Harmonisierten System (GHS).	Not Assigned
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	84434-11-7

California Prop. 65

WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018



WARNING: This product can expose you to chemicals including 2-Propenoic acid, 1,1'-[2-ethyl-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Aluminum	7429-90-5
----------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Aluminum	7429-90-5
----------	-----------

The ingredients of this product are reported in the following inventories:

DSL	: This product contains one or several components that are not on the Canadian DSL nor NDSL.
TSCA	: All substances listed as active on the TSCA inventory
EINECS	: On the inventory, or in compliance with the inventory

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with oxirane, 4-(dimethylamino)benzoate	2067275-86-7
--	--------------

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with oxirane, 4-(dimethylamino)benzoate	2067275-86-7
--	--------------

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	: 8-hour time weighted average

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version	Revision Date:	SDS Number:	Date of last issue: 02/23/2023
7.1	02/20/2025	102000027250	Date of first issue: 03/26/2018

OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/20/2025

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TOPSTAR G2 UV LED 21-0200 Bright Silver

Version
7.1

Revision Date:
02/20/2025

SDS Number:
102000027250

Date of last issue: 02/23/2023
Date of first issue: 03/26/2018

US / Z8