

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version 3.0      Revision Date: 06/26/2023      SDS Number: 102000030979      Date of last issue: 12/09/2019  
Date of first issue: 12/12/2018

---

**SECTION 1. IDENTIFICATION**

Product name : METALSTAR UV 21-8050 NL SILVER PMS 10077  
Product code : 045939EF0

**Manufacturer or supplier's details**

Company name of supplier : ECKART America Corporation  
Address : 830 East Erie Street  
Painesville OH 44077  
Telephone : 866-458-7837  
(440) 954-7600  
Telefax : (440) 354-6224  
e-mail adresse : info.eckart.america.oh@altana.com  
Emergency telephone : **CHEMTREC:** 800-424-9300  
**CHEMTREC:** 1-703-527-3387 (International)

**NCEC:**

(contract no. ECKART29003-NCEC)  
US: +1 866 928 0789 (Toll free)  
Canada: +1 800 579 7421 (Toll Free)  
Mexico: +52 55 5004 8763

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Eye irritation : Category 2A

Skin sensitization : Category 1

**GHS label elements**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**

---

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.

**Disposal:**

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous ingredients which must be listed on the label:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)  
 Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate  
 2-Propenoic acid, 1,1'-[2-[[3-hydroxy-2,2-bis[[[(1-oxo-2-propen-1-yl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester  
 2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5	>= 20 - < 30
Poly[oxy(methyl-1,2-	52408-84-1	>= 10 - < 20

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-		
Aluminum	7429-90-5	>= 10 - < 20
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	84434-11-7	>= 5 - < 10
2-Propenoic acid, 1,1'-[2-[[3-hydroxy-2,2-bis[[[(1-oxo-2-propen-1-yl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester	60506-81-2	>= 1 - < 5
Silica	7631-86-9	>= 1 - < 5
2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-	7078-98-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Take the victim into fresh air.  
Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes serious eye irritation.

**SECTION 5. FIRE-FIGHTING MEASURES**

# METALSTAR UV 21-8050 NL SILVER PMS 10077

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

Suitable extinguishing media	:	Dry sand ABC powder Foam
Unsuitable extinguishing media	:	High volume water jet Carbon dioxide (CO <sub>2</sub> )
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas. Use personal protective equipment.
Environmental precautions	:	The product should not be allowed to enter drains, water courses or the soil.  Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Do not flush with water. Keep in suitable, closed containers for disposal.

---

## SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Do not breathe vapors/dust.

---

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

- Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Earthing of containers and apparatuses is essential.  
 Reaction with water liberates extremely flammable gas (hydrogen)  
 Take measures to prevent the build up of electrostatic charge.  
 Use explosion-proof equipment.  
 Store in original container.  
 Keep containers tightly closed in a cool, well-ventilated place.  
 Keep away from sources of ignition - No smoking.  
 Keep container closed when not in use.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Electrical installations / working materials must comply with the technological safety standards.
- Technical measures/Precautions : Protect from humidity and water.
- Materials to avoid : Do not store near acids.  
 Do not store together with oxidizing and self-igniting products.  
 Never allow product to get in contact with water during storage.  
 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**
Version  
3.0Revision Date:  
06/26/2023SDS Number:  
102000030979Date of last issue: 12/09/2019  
Date of first issue: 12/12/2018

Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-3
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	ACGIH
		TWA (Aluminum)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Total Aluminum)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable Aluminum)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (total dust Aluminum)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction Aluminum)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust Aluminum)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction Aluminum)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (welding fumes Aluminum)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (pyro powders Aluminum)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable particulate matter Aluminum)	1 mg/m <sup>3</sup>	ACGIH

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version 3.0      Revision Date: 06/26/2023      SDS Number: 102000030979      Date of last issue: 12/09/2019  
Date of first issue: 12/12/2018

		TWA (Fumes)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (powder)	5 mg/m <sup>3</sup> (Aluminum)	OSHA P0
Silica	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL

**Personal protective equipment**

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	silver
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	6 - 8
		Concentration: 100 %
Melting point/range	:	Not applicable
Boiling point/boiling range	:	> 100 °C
Flash point	:	> 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	1.1 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Contact with acids and alkalis may release hydrogen. Stable under recommended storage conditions.
Conditions to avoid	:	Do not allow evaporation to dryness. No data available
Incompatible materials	:	Acids Bases Oxidizing agents

---



**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Acute toxicity**

Not classified based on available information.

**Components:**
**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Acute oral toxicity : (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

**Silica:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
(Mouse): 15,000 mg/kg

Acute inhalation toxicity : (Rat): 0.139 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**
**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Remarks: May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:**

**Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):**

Result: Irritating to eyes.

**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-]:**

Result: Eye irritation

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Remarks: Vapors may cause irritation to the eyes, respiratory system and the skin.

**Respiratory or skin sensitization**
**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Components:**
**Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):**

Result: May cause sensitization by skin contact.

Remarks: Causes sensitization.

May cause sensitization of susceptible persons by skin contact.

**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-]:**

Result: May cause sensitization by skin contact.

**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Result: May cause sensitization by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**


---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Components:**

**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Silica:**

Toxicity to daphnia and other : (Daphnia): 7,600 mg/l

aquatic invertebrates

Toxicity to algae : (Chlorella pyrenoidosa): 440 mg/l

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

**Components:**

**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:**

Additional ecological : No data available

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

information

**ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

**Silica:**

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****Domestic regulation****49 CFR**

Not regulated as a dangerous good

**49 CFR**

: Not classified as dangerous in the meaning of transport regulations.

**International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

---

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

Remarks : Not classified as dangerous in the meaning of transport regulations.

**ADR** : Not classified as dangerous in the meaning of transport regulations.

**IATA-DGR** : Not classified as dangerous in the meaning of transport regulations.

**IMDG-Code** : Not classified as dangerous in the meaning of transport regulations.

Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

---

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
Hydrochloric acid	7647-01-0	5000

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
Hydrochloric acid	7647-01-0	5000

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	>= 10 - < 20 %
----------	-----------	----------------

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Hydrochloric acid	7647-01-0	%
-------------------	-----------	---

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Hydrochloric acid	7647-01-0	%
-------------------	-----------	---

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307  
This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**
**Massachusetts Right To Know**

Aluminum	7429-90-5
Silica	7631-86-9

**Pennsylvania Right To Know**

	Not Assigned
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-	52408-84-1
Aluminum	7429-90-5
	Not Assigned
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	84434-11-7
2-Propenoic acid, 1,1'-[2-[[3-hydroxy-2,2-bis[[[(1-oxo-2-propen-1-yl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester	60506-81-2

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

Silica

7631-86-9

**California Prop. 65**

WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



WARNING: This product can expose you to chemicals including 2-Propenoic acid, 1,1'-[2-ethyl-2-[[1-(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California List of Hazardous Substances**

Aluminum

7429-90-5

Silica

7631-86-9

**California Permissible Exposure Limits for Chemical Contaminants**

Aluminum

7429-90-5

Silica

7631-86-9

**The ingredients of this product are reported in the following inventories:**

DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.

TSCA : On TSCA Inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated)

**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1  
Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3  
Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour  
workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/26/2023



**METALSTAR UV 21-8050 NL SILVER PMS  
10077**

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2019
3.0	06/26/2023	102000030979	Date of first issue: 12/12/2018

---

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8