

### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

#### **SECTION 1. IDENTIFICATION**

Product name : ROTOSTAR UV LED FP 71-40502 SILVER

Product code : 046131ER0

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation

Address : 830 East Erie Street

Painesville OH 44077

Telephone : 866-458-7837

(440) 954-7600

Telefax : (440) 354-6224

e-mail adresse : info.eckart.america.oh@altana.com

Emergency telephone : CHEMTREC: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

**GHS** label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H351 Suspected of causing cancer.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

H360Df May damage the unborn child. Suspected of damaging

fertility.

**Precautionary Statements** 

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have

been read and understood.

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be

allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous ingredients which must be listed on the label:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

 $Poly[oxy(methyl-1,2-ethanediyl)], \ . alpha.,.. alpha.',. alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-$ 

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(phenylmethyl)-

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Poly(oxy-1,2-ethanediyl), .alphahydroomega[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	28961-43-5	>= 50 - < 70
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega[(1-oxo-2-propen-1-yl)oxy]-	52408-84-1	>= 5 - < 10
Aluminum	7429-90-5	>= 5 - < 10
ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate	84434-11-7	>= 5 - < 10
9H-Thioxanthen-9-one, 2-(1-methylethyl)-	5495-84-1	>= 1 - < 5
1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(phenylmethyl)-	119313-12-1	>= 1 - < 5
2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester	15625-89-5	>= 0.1 - < 1
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate	55818-57-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Take the victim into fresh air.

Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

If inhaled : Remove to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Immediately flush eye(s) with plenty of water.

Remove contact lenses.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital. May cause an allergic skin reaction.

Most important symptoms and effects, both acute and

delayed

Causes serious eye irritation.

Suspected of causing cancer.

May damage the unborn child. Suspected of damaging

fertility.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Dry sand

ABC powder

Foam

Unsuitable extinguishing

media

High volume water jet

Carbon dioxide (CO2) High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
Use personal protective equipment.

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

Version Revision Date: SDS Number: Date of last issue: 04/24/2023 03/01/2024 4.1 102000033129 Date of first issue: 08/06/2020

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

: Do not breathe vapors/dust. Advice on safe handling

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage Earthing of containers and apparatuses is essential.

Reaction with water liberates extremely flammable gas

(hydrogen)

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from sources of ignition - No smoking.

Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with



# **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

the technological safety standards.

Technical

Protect from humidity and water.

measures/Precautions

Materials to avoid : Do not store near acids.

Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

No decomposition if stored and applied as directed.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-3
		(respirable fraction)		
		TWA	15 Million	OSHA Z-3
		(respirable fraction)	particles per cubic foot	
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (total	15 mg/m3	OSHA Z-1



# **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

		dust)	(Aluminum)	1
		TWA	5 mg/m3	OSHA Z-1
		(respirable	(Aluminum)	
		fraction)	,	
		TWA (Total	15 mg/m3	OSHA P0
		dust)	(Aluminum)	
		TWA	5 mg/m3	OSHA P0
		(respirable	(Aluminum)	
		dust fraction)		
		TWA	5 mg/m3	NIOSH REL
		(welding	(Aluminum)	
		fumes)		
		TWA (pyro	5 mg/m3	NIOSH REL
		powders)	(Aluminum)	
		TWA	1 mg/m3	ACGIH
		(Respirable	(Aluminum)	
		particulate		
		matter)	5 / 0	00114 D0
		TWA	5 mg/m3	OSHA P0
		(Fumes)	- / O	00114 D0
		TWA	5 mg/m3	OSHA P0
0.0		(powder)	(Aluminum)	LIO MEET
2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-	15625-89-5	TWA	1 mg/m3	US WEEL
yl)oxy]methyl]-1,3-propanediyl] ester				

#### Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be



### **ROTOSTAR UV LED FP 71-40502 SILVER**

Version Revision Date: SDS Number: Date of last issue: 04/24/2023 4.1 03/01/2024 102000033129 Date of first issue: 08/06/2020

washed after contact. The suitability for a specific workplace

should be discussed with the producers of the protective

gloves.

Eye protection Goggles

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Impervious clothing Skin and body protection

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

When using do not eat or drink. Hygiene measures

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance liquid Color silver

Odor characteristic Odor Threshold No data available

pΗ 6 - 8

Concentration: 100 %

No data available

No data available

Melting point/range Not applicable Boiling point/boiling range > 100 °C

Flash point > 100 °C

Evaporation rate No data available Flammability (solid, gas) No data available Flammability (liquids) Will not burn

Upper explosion limit / Upper

flammability limit

Lower explosion limit / Lower

flammability limit

Vapor pressure No data available Relative density No data available

Density 1.1 g/cm3

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-No data available

octanol/water

Autoignition temperature No data available Decomposition temperature No data available



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

Viscosity : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous : Contact with acids and alkalis may release hydrogen.

reactions No decomposition if stored and applied as directed.

Conditions to avoid : Do not allow evaporation to dryness.

No data available

Incompatible materials : Acids

Bases

Oxidizing agents

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Acute toxicity

Not classified based on available information.

#### **Components:**

### ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Acute oral toxicity : (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

#### Skin corrosion/irritation

Not classified based on available information.

### **Components:**

### ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: May cause skin irritation and/or dermatitis.

### 2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

Version Revision Date: 4.1 03/01/2024

SDS Number: 102000033129

Date of last issue: 04/24/2023 Date of first issue: 08/06/2020

#### Components:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: Irritating to eyes.

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: Eye irritation

### ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Vapors may cause irritation to the eyes, respiratory system and the skin.

### 2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: Eye irritation

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified based on available information.

#### Components:

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1):

Result: May cause sensitization by skin contact.

Remarks: Causes sensitization.

May cause sensitization of susceptible persons by skin contact.

# Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''-1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-:

Result: May cause sensitization by skin contact.

### ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Result: May cause sensitization by skin contact.

# 2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Result: May cause sensitization by skin contact.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Components:

2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester:

Carcinogenicity - : Limited evidence of carcinogenicity in animal studies

Assessment

IARC Group 2B: Possibly carcinogenic to humans

2-Propenoic acid, 1,1'-[2- 15625-89-5

ethyl-2-[[(1-oxo-2-propen-1-

yl)oxy]methyl]-1,3propanediyl] ester

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

May damage the unborn child. Suspected of damaging fertility.

**Components:** 

9H-Thioxanthen-9-one, 2-(1-methylethyl)-:

Reproductive toxicity - : Some evidence of adverse effects on sexual function and

Assessment fertility, based on animal experiments.

1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(phenylmethyl)-:

Reproductive toxicity - : Clear evidence of adverse effects on development, based on

Assessment animal experiments.

STOT-single exposure

Not classified based on available information.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

Version Revision Date: SDS Number: Date of last issue: 04/24/2023 4.1 03/01/2024 102000033129 Date of first issue: 08/06/2020

#### STOT-repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

**Further information** 

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Components:**

# ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### 9H-Thioxanthen-9-one, 2-(1-methylethyl)-:

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

: 1

: 1

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### 1-Butanone, 2-(dimethylamino)-1-[4-(4-morpholinyl)phenyl]-2-(phenylmethyl)-:

M-Factor (Acute aquatic

toxicity)

M-Factor (Chronic aquatic toxicity)

**Ecotoxicology Assessment** 

: Very toxic to aquatic life. Acute aquatic toxicity

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, 2-propenoate:

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### Persistence and degradability

No data available



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

#### Bioaccumulative potential

No data available

#### Other adverse effects

No data available

#### **Components:**

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omega.-[(1-

oxo-2-propen-1-yl)oxy]-:

Additional ecological

information

: No data available

#### ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Additional ecological : An environmental hazard cannot be excluded in the event of

information unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

### International Regulations

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Bisphenol A Epoxy resin)

Class : 9 Packing group : III

Labels : Miscellaneous Dangerous Goods

Packing instruction (cargo : 964



# **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

aircraft)

Packing instruction

(passenger aircraft)

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

964

(Bisphenol A Epoxy resin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A

EmS Code : F-A, S-F Marine pollutant : yes

Remarks : For single packagings <=5L / 5 kg, or combination

packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197

IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Carcinogenicity
Reproductive toxicity

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Aluminum 7429-90-5 >= 5 - < 10 %



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

#### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307 This product does not contain any priority pollutants related to the U.S. Clean Water Act

### **US State Regulations**

#### Massachusetts Right To Know

Aluminum		7429-90-5
9H-Thioxanthen-9-one,	2-(1-methylethyl)-	5495-84-1

### Pennsylvania Right To Know

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)

Kein gefährlicher Stoff oder gefährliches Gemisch gemäß dem Not Assigned Global Harmonisierten System (GHS).

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.''- 52408-84-1

1,2,3-propanetriyltris[.omega.-[(1-oxo-2-propen-1-yl)oxy]-

Aluminum 7429-90-5

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate 84434-11-7

9H-Thioxanthen-9-one, 2-(1-methylethyl)- 5495-84-1

### California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



### **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020



WARNING: This product can expose you to chemicals including 2-Propenoic acid, 1,1'-[2-ethyl-2-[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester, Ethanol, which is/are known to the State of California to cause cancer, and Ethanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### California List of Hazardous Substances

Aluminum 7429-90-5

### California Permissible Exposure Limits for Chemical Contaminants

Aluminum 7429-90-5

### The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the

Canadian NDSL., This product contains one or several components that are not on the Canadian DSL nor NDSL.

TSCA : All substances listed as active on the TSCA inventory

**TSCA list** 

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA



# **ROTOSTAR UV LED FP 71-40502 SILVER**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/24/2023

 4.1
 03/01/2024
 102000033129
 Date of first issue: 08/06/2020

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/01/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8