

# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

#### **SECTION 1. IDENTIFICATION**

Product name : STANDART PC 150 Aluminium Powder

Product code : 040816E30

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation

Address : 830 East Erie Street

Painesville OH 44077

Telephone : 866-458-7837 Telefax : (440) 354-6224

Emergency telephone : CHEMTREC: 800-424-9300

CHEMTREC: 1-703-527-3387 (International)

NCEC:

(contract no. ECKART29003-NCEC) US: +1 866 928 0789 (Toll free) Canada: +1 800 579 7421 (Toll Free)

Mexico: +52 55 5004 8763

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Flammable solids : Category 1

Combustible dust

**GHS** label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H228 Flammable solid.

May form combustible dust concentrations in air.

Precautionary Statements :

Prevention:

P210 Keep away from heat/sparks/open flames/hot

surfaces. No smoking.

P240 Ground/bond container and receiving

equipment.

P241 Use explosion-proof electrical/ ventilating/



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

lighting/ equipment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P370 + P378 In case of fire: Use for extinction: Special

powder for metal fires.

P370 + P378 In case of fire: Use for extinction: Dry sand.

Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 90 - <= 100

### **SECTION 4. FIRST AID MEASURES**

General advice : Take the victim into fresh air.

Move out of dangerous area.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

and effects, both acute and

delayed

: None known.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing : ABC powder



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

media Carbon dioxide (CO2)

Water Foam

Specific hazards during fire

fighting

Contact with water liberates extremely flammable gas

(hydrogen).

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Evacuate personnel to safe areas.

Avoid dust formation.

Remove all sources of ignition.

Environmental precautions :

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

s for : Use mechanical handling equipment.

Do not use a vacuum cleaner.

Do not flush with water.

Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Use explosion-proof equipment.

During processing, dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge.

When transferring from one container to another apply earthing measures and use conductive hose material.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid creating dust.

Routine housekeeping should be instituted to ensure that

dusts do not accumulate on surfaces.



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

Store away from heat.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Earthing of containers and apparatuses is essential.

Reaction with water liberates extremely flammable gas

(hydrogen)

Use explosion-proof equipment. Store in original container.

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from sources of ignition - No smoking.

Keep container closed when not in use.

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards. Protect from humidity and water.

Technical

measures/Precautions

Materials to avoid

: Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

Keep in a dry place.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-3



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -2.0

12/09/2019 102000030767 Date of first issue: 04/04/2019

(respirable fraction)		
TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
TWA (Respirable fraction)	1 mg/m3	ACGIH
TWA	5 mg/m3 (Aluminum)	NIOSH REL
TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1
TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA PO
TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
TWA (Respirable fraction)	1 mg/m3 (Aluminum)	ACGIH
TWA (Fumes)	5 mg/m3	OSHA P0

# Personal protective equipment

: Use suitable breathing protection if workplace concentration Respiratory protection

requires.

Breathing apparatus with filter.

P1 filter

Hand protection

Material : Leather

Glove length : Long sleeve gloves



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

Remarks : Leather gloves The choice of an appropriate glove does not

only depend on its material but also on other quality features

and is different from one producer to the other.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Face-shield

Safety glasses

Skin and body protection : Anti-static and fire resistant protective clothing. DIN EN

11612; EN 533; EN 1149-1; Anti-static safety shoes

Dust impervious protective suit

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder Color : silver Odor : odorless

Odor Threshold : No data available pH : No data available Melting point/freezing point : No data available Initial boiling point and boiling : No data available

range

Flash point : No data available Evaporation rate : No data available

Flammability (solid, gas) : The substance or mixture is a flammable solid with the

category 1.

combustible dust

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available Relative density : No data available

Density : 2.5 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : 340 °C



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

Decomposition temperature : No data available Viscosity : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous : Contact with acids and alkalis may release hydrogen.

reactions Stable under recommended storage conditions.

Dust may form explosive mixture in air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Bases

Oxidizing agents

Water

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

**Further information** 

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

### **SECTION 14. TRANSPORT INFORMATION**

### **Domestic regulation**

**49 CFR** 

UN/ID/NA number UN 1309

Proper shipping name Aluminum powder, coated

Class 4.1 Packing group

Labels Division 4.1 - Flammable solids

**ERG Code** 170 Marine pollutant no

International Regulations

**IATA-DGR** 

UN/ID No. UN 1309

Proper shipping name Aluminium powder, coated

Class 4.1 Packing group Ш

Division 4.1 - Flammable solids Labels

Packing instruction (cargo 448

aircraft)

Packing instruction : 445

(passenger aircraft)

**IMDG-Code** 

UN number UN 1309

ALUMINIUM POWDER, COATED Proper shipping name

Class 4.1 Packing group Ш Labels 4.1 EmS Code F-G, S-G

Marine pollutant

Remarks IMDG Code segregation group 15 - Powdered metals

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Combustible dust

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Aluminum 7429-90-5 >= 90 - <= 100 %

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### **US State Regulations**

# Massachusetts Right To Know

Aluminum 7429-90-5

### Pennsylvania Right To Know

Aluminum 7429-90-5

#### California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### California List of Hazardous Substances

Aluminum 7429-90-5



# **STANDART PC 150 Aluminium Powder**

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

#### California Permissible Exposure Limits for Chemical Contaminants

Aluminum 7429-90-5

#### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

**TSCA list** 

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -



# STANDART PC 150 Aluminium Powder

Version Revision Date: SDS Number: Date of last issue: -

2.0 12/09/2019 102000030767 Date of first issue: 04/04/2019

Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature: SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/09/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8