

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : METALURE A-61010 MB

Product code : 027500IA0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version 3.2 Revision Date: 03.04.2024 SDS Number: 102000000663 Print Date: 02.12.2024
Date of first issue: 05.08.2016

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGULATION (EC) No 1272/2008	Concentration (% w/w)
3-methoxy-3-methylbutan-1-ol	56539-66-3 260-252-4	Eye Irrit. 2; H319	>= 50 - <= 100
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 10 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

		EUH066	
--	--	--------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move the victim to fresh air. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks	: Causes serious eye irritation.
-------	----------------------------------

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Dry sand ABC powder Foam
Unsuitable extinguishing	: High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

media	Carbon dioxide (CO ₂)
	High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water courses or the soil.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version 3.2 Revision Date: 03.04.2024 SDS Number: 102000000663 Print Date: 02.12.2024
Date of first issue: 05.08.2016

Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40
		TWA (Respirable fraction)	4 mg/m ³	GB EH40
		TWA (inhalable dust)	10 mg/m ³	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m ³	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version
3.2

Revision Date:
03.04.2024

SDS Number:
102000000663

Print Date: 02.12.2024
Date of first issue: 05.08.2016

	<p>when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	500 ppm 1,210 mg/m3	GB EH40
		STEL	1,500 ppm 3,620 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
3-methoxy-3-methylbutan-1-ol	Workers	Inhalation	Long-term systemic effects	5.9 mg/m3
	Workers	Dermal	Long-term systemic effects	2 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	1.2 mg/kg
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Inhalation	Acute local effects	2420 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version 3.2 Revision Date: 03.04.2024 SDS Number: 102000000663 Print Date: 02.12.2024
Date of first issue: 05.08.2016

	Workers	Inhalation	Acute systemic effects	1210 mg/m3
	Workers	Dermal	Long-term systemic effects	186 mg/kg
	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Consumers	Oral	Long-term systemic effects	62 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg
	STP	100 mg/l
	Soil	29.5 mg/kg
	periodical release	21 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	: viscous
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: 173 °C
Flammability	: No data available
Flammability (liquids)	: Flammable liquids
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Flash point	: 15 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: substance/mixture is non-soluble (in water)
Viscosity, kinematic	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: No data available
Vapor Pressure for Components:	
3-methoxy-3-methylbutan-1-ol	: 47 Pa (20 °C)
acetone	: 240 hPa (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

Relative density : No data available

Density : 0.91 g/cm³

Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : No data available

9.2 Other information

Self-ignition : No data available

Miscibility with water : immiscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg
(Mouse): 3,000 mg/kg
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

acetone:

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version
3.2

Revision Date:
03.04.2024

SDS Number:
102000000663

Print Date: 02.12.2024
Date of first issue: 05.08.2016

Components:

3-methoxy-3-methylbutan-1-ol:

Result : Mild eye irritation

acetone:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

acetone:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : Solvents may degrease the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADR	:	PAINT
IMDG	:	PAINT, CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE
IATA	:	Paint, classified according to 3.3.3.1 IATA-DGR

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (E)
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: 3
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3 3-methoxy-3-methylbutan-1-ol (Number on list 3) aluminium powder (stabilised) (Number on list 40) acetone (Number on list 3)
--	---

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
---	------------------

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	: acetone
---	-----------

UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable
--	------------------

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	
---	--

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

15.2 Chemical safety assessment

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H228	: Flammable solid.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Flam. Sol.	: Flammable solids
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE A-61010 MB

Version	Revision Date:	SDS Number:	Print Date: 02.12.2024
3.2	03.04.2024	102000000663	Date of first issue: 05.08.2016

High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN