according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SILVERDREAM Starlight 70 IL

Product code : 007302FX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Cosmetic products

Substance/Mixture Colouring agents, pigments

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 H228: Flammable solid.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single H336: May cause drowsiness or dizziness.

exposure, Category 3, Central nervous

system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Revision Date: SDS Number: Print Date: 21.12.2024 Version

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Hazard pictograms

Signal word Danger

Hazard statements H228 Flammable solid.

> H319 Causes serious eve irritation.

> H336 May cause drowsiness or dizziness.

Prevention: Precautionary statements

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

Avoid breathing dust. P261

Wear protective gloves/ protective clothing/ P280

eye protection/ face protection/ hearing

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

> air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel

unwell.

P370 + P378 In case of fire: Use for extinction: Special

powder for metal fires.

P370 + P378 In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	ClassificationREGUL	Concentration
	EC-No.	ATION (EC) No	(% w/w)
	Index-No.	1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision D	Date: SDS Num	ber: Print Date	e: 21.12.2024
--------------------	---------------	-----------------	---------------

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

propan-2-ol	67-63-0	Flam. Liq. 2; H225	>= 25 - < 50
	200-661-7	Eye Irrit. 2; H319	
	603-117-00-0	STOT SE 3; H336	
		(Central nervous	
	01-2119457558-25	system)	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Wash off immediately with soap and plenty of water.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Carbon dioxide (CO2)

ABC powder

Water Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Contact with water liberates extremely flammable gas

(hydrogen).

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use personal protective equipment. Use personal protective equipment.

Avoid dust formation.

Remove all sources of ignition.

6.2 Environmental precautions

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

SDS Number: Print Date: 21.12.2024 Version Revision Date:

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use

explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot

surfaces and sources of ignition.

When using do not eat or drink. When using do not smoke. Hygiene measures

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and wellventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions

Protect from humidity and water. Do not allow to dry.

Do not store together with oxidizing and self-igniting products. Advice on common storage

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Further information on storage stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Go respirable, the substance has concentration inhalable dust any dust will be levels. Some must comply particles of a particular part response that distinguishes and 'respirable material that cavailable for cothe fraction definitions and contain comp should be cor a figure three Further inform inhalable dust when samplin MDHS14/4 Go respirable, the substance has	nation: For the purport are those fractions ag is undertaken in ageneral methods for so cracic and inhalable agradous to health incoming in air equal to or great or 4 mg.m-3 8-hour one subject to COSH-dusts have been asswith the appropriate wide range of sizes. It elicits, depend on two size fractions for etc., Inhalable dust appropriate to the properties of the explanatory material onents that have the mplied with., Where retimes the long-term TWA (Respirable dust) Take those fractions ag is undertaken in ageneral methods for so cracic and inhalable agardous to health incoming the mation of the latter in ageneral methods for so cracic and inhalable agardous to health incoming the mation of the latter in ageneral methods for so cracic and inhalable agardous to health incoming the mation of the latter in the latter i	eater than 10 mg.m-3 8-hour TWA of respirable dust. This I if people are exposed to dustigned specific WELs and explimits., Most industrial dusts The behaviour, deposition and he human respiratory system the nature and size of the partimit-setting purposes terme oppoximates to the fraction of mouth during breathing and initiatory tract. Respirable dust he gas exchange region of the large given in MDHS14/4., Wir own assigned WEL, all the no specific short-term expositions.	e collected described in lysis or sition of a present at a TWA of a means that ast above these contain and fate of any and the body article. HSE and 'inhalable' airborne approximates a lung. Fuller Where dusts relevant limits are limit is listed, and GB EH40 e dust and a collected described in lysis or sition of a present at a
	substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore			
	available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed a figure three times the long-term exposure limit should be used.			e lung. Fuller Vhere dusts relevant limits ure limit is listed,
		TWA (Respirable dust)	4 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Governments respirable, the substance has	t are those fractions ag is undertaken in ac eneral methods for so pracic and inhalable zardous to health inc	of airborne dust which will be ecordance with the methods campling and gravimetric ana aerosols., The COSHH defir cludes dust of any kind when	e collected described in lysis or iition of a present at a

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed. a figure three times the long-term exposure limit should be used. 67-63-0 TWA 400 ppm GB EH40 propan-2-ol 999 mg/m3 STEL 500 ppm GB EH40 1,250 mg/m3

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Dermal	Long-term systemic effects	888 mg/kg
	Consumers	Inhalation	Long-term systemic effects	89 mg/m3
	Consumers	Dermal	Long-term systemic effects	319 mg/kg
	Consumers	Oral	Long-term systemic effects	26 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
propan-2-ol	Fresh water	140.9 mg/l
	Marine water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine sediment	552 mg/kg
	STP	2251 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Soil 28 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 82 °C

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Flammability : The substance or mixture is a flammable solid with the

category 1.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : 13 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Vapor Pressure for Components:

propan-2-ol : 44 hPa (20 °C)

Relative density : No data available

Density : 1.3 - 2.0 g/cm3

Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : 51 - 75 µm

9.2 Other information

Explosives : Not explosive

Vapours may form explosive mixture with air.

Self-ignition : not auto-flammable

Miscibility with water : immiscible

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapours may form explosive mixture with air. Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Eye irritation

Components:

propan-2-ol:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21* - Aluminum thermal metallurgy wastes, other

particles and dust (including ball mill dust) containing

hazardous substances

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum. In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 1325

 IMDG
 : UN 1325

 IATA
 : UN 1325

14.2 UN proper shipping name

ADR : FLAMMABLE SOLID, ORGANIC, N.O.S.

(Aluminium pigment paste)

IMDG : FLAMMABLE SOLID, ORGANIC, N.O.S.

(Aluminium pigment paste)

IATA : Flammable solid, organic, n.o.s.

(Aluminium pigment paste)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 4.1 IMDG : 4.1 IATA : 4.1

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 40
Labels : 4.1
Tunnel restriction code : (E)

IMDG

Packing group : II

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Labels : 4.1

EmS Code : F-G, S-G

Remarks : IMDG Code segregation group 15 - Powdered metals

IATA (Cargo)

Packing instruction (cargo : 448

aircraft)

Packing instruction (LQ) : Y441
Packing group : II
Labels : 4.1

IATA (Passenger)

Packing instruction : 445

(passenger aircraft)

Packing instruction (LQ) : Y441
Packing group : II
Labels : 4.1

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

14 / 16

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered:

aluminium powder (stabilised)

(Number on list 40)

propan-2-ol (Number on list 3)

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

: Not applicable

: Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

Regulation (EU) 2019/1148 on the marketing and use of : aluminium powder (stabilised)

explosives precursors

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Regulation (EU) 2019/1148 on the marketing and use of

explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all aluminium powder (stabilised)

suspicious transactions, and significant disappearances and thefts (ANNEX II)

should be reported to the relevant national contact point.

This product is regulated by Regulation (EU) 2019/1148: all aluminium powder (stabilised) suspicious transactions, and significant disappearances and thefts (ANNEX II)

should be reported to the relevant national contact point.

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H228 : Flammable solid.

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids

STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response;

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILVERDREAM Starlight 70 IL

Version Revision Date: SDS Number: Print Date: 21.12.2024

5.3 19.12.2024 102000021521 Date of first issue: 02.01.2014

EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory: TRGS - Technical Rule for Hazardous Substances: TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Sol. 1 H228 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN