METALSTAR SuperEco 14 2877 PANTONE 877

Version	Revision Date:	SDS Number:	Date of last issue: 05/13/2024
1.1	05/14/2024	102000037501	Date of first issue: 05/13/2024

SECTION 1. IDENTIFICATION

Product name : METALSTAR SuperEco 14 2877 PANTONE 877
Product code : 028106RC0

Manufacturer or supplier's details

Company name of supplier : ECKART America Corporation
Address : 830 East Erie Street
Painesville OH 44077
Telephone : 866-458-7837
(440) 954-7600
Telefax : (440) 354-6224
e-mail adresse : info.eckart.america.oh@altana.com
Emergency telephone : **CHEMTREC**: 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

NCEC:
(contract no. ECKART29003-NCEC)
US: +1 866 928 0789 (Toll free)
Canada: +1 800 579 7421 (Toll Free)
Mexico: +52 55 5004 8763

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Safflower oil	8001-23-8	>= 10 - < 20
Aluminum	7429-90-5	>= 10 - < 20

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Take the victim into fresh air. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	None known.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Dry sand ABC powder Foam
Unsuitable extinguishing media	:	High volume water jet Carbon dioxide (CO2)
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas.
General advice	:	The product should not be allowed to enter drains, water

courses or the soil.
Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Conditions for safe storage : Earthing of containers and apparatuses is essential.
Reaction with water liberates extremely flammable gas (hydrogen)
Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep away from sources of ignition - No smoking.
Keep container closed when not in use.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Technical measures/Precautions : Protect from humidity and water.

Materials to avoid : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

No materials to be especially mentioned.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Safflower oil	8001-23-8	TWA (mist - total)	10 mg/m3	NIOSH REL
		TWA (mist - respirable)	5 mg/m3	NIOSH REL
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-3
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (respirable fraction)	5 mg/m3	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (Respirable fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (total dust)	15 mg/m3 (Aluminum)	OSHA Z-1

		TWA (respirable fraction)	5 mg/m3 (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminum)	OSHA P0
		TWA (welding fumes)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (pyro powders)	5 mg/m3 (Aluminum)	NIOSH REL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
		TWA (Fumes)	5 mg/m3	OSHA P0
		TWA (powder)	5 mg/m3 (Aluminum)	OSHA P0

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
No personal respiratory protective equipment normally required.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Goggles

		Safety glasses
Skin and body protection	:	Protective suit
Hygiene measures	:	General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	silver
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	> 100 °C
Flash point	:	> 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	1 g/cm3
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	> 21 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Contact with acids and alkalis may release hydrogen. Stable under recommended storage conditions.
Conditions to avoid	:	Do not allow evaporation to dryness. No data available
Incompatible materials	:	Acids Bases

Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity
Not classified based on available information.

Skin corrosion/irritation
Not classified based on available information.

Serious eye damage/eye irritation
Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization
Not classified based on available information.

Respiratory sensitization
Not classified based on available information.

Germ cell mutagenicity
Not classified based on available information.

Carcinogenicity
Not classified based on available information.

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity
Not classified based on available information.

STOT-single exposure
Not classified based on available information.

STOT-repeated exposure
Not classified based on available information.

Aspiration toxicity
Not classified based on available information.

Further information

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity
No data available

Persistence and degradability
No data available

Bioaccumulative potential
No data available

Other adverse effects
No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

49 CFR
Not regulated as a dangerous good

International Regulations

IATA-DGR

UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (paint related material)
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft)	:	964
Packing instruction (passenger aircraft)	:	964

IMDG-Code

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

		N.O.S. (paint related material)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes
Remarks	:	For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	>= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.
This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.
This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307
This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Aluminum	7429-90-5

Pennsylvania Right To Know

Resin	Not Assigned
Safflower oil	8001-23-8
Dodecanoic acid, 2-ethylhexyl ester	20292-08-4
Aluminum	7429-90-5
Alkyd Resins	63148-69-6
rosin resin	Not Assigned
	Not Assigned
Neodecanoic acid, manganese salt (1:?)	27253-32-3

California Prop. 65

WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Aluminum	7429-90-5

California Permissible Exposure Limits for Chemical Contaminants

Safflower oil	8001-23-8
Aluminum	7429-90-5

The ingredients of this product are reported in the following inventories:

DSL	:	This product contains one or several components listed in the Canadian NDSL.
TSCA	:	All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National

Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/14/2024

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8