

Date of impression 18.11.2020/17:09:33
page/of 1/1

edition 15.11.2020

material denomination STAPA IL HYDROLAN S 1500 Aluminium Paste

material-no. 053367GD0

material description Pigmentpaste of flaky aluminium powder produced of pure aluminium min. 99,5 % EN 576, with an inorganic coating
 Specific gravity app. 1,1 kg/l
 The solvent contained is isopropanol (IL) including lubricant and

material specification

insp. characteristic	specification	unit
TI00004 pigment content / non volatile	18,0 - 22,0	%
TI00004 volatile content	78,0 - 82,0	%
TI00005 sieving < 40 µm	99,9 - 100,0	%
TI00289 aqueous paint spray-out	pass	
TI00489 D 10	6,0 - 10,0	µm
TI00489 D 50	12,0 - 18,0	µm
TI00489 D 90	23,0 - 31,0	µm

total shelf life in month: 24

EC-safety data sheet-no. 053367GD0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
15.11.2020	15.11.2020	15.11.2020

This document has been printed automatically and will not be signed.