

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : STAPA SILTALLUX 8380 Aluminium Pigment Paste
Material number : 019012G70

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

Not a dangerous substance according to GHS.

GHS-Labeling

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

Hazardous components which must be listed on the label**Other hazards which do not result in classification**

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance name : STAPA SILTALLUX 8380

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	Flam. Liq.;4;H227 Asp. Tox.;1;H304	25 - 50
Fatty acids, C14-18 and C16-18- unsatd.	67701-06-8 266-930-6	Acute Tox.;5;H313	1 - 10
Solvent naphtha (petroleum), light arom.	64742-95-6	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	1 - 2,5

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

--	--	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice	: Move the victim to fresh air. Do not leave the victim unattended. No hazards which require special first aid measures.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off immediately with soap and plenty of water.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO₂)**5.2 Special hazards arising from the substance or mixture**

This information is not available.

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Remove all sources of ignition.
Avoid dust formation.**6.2 Environmental precautions**

This information is not available.

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
- Sweep up and shovel.
Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust
formation. Ensure adequate ventilation.
- For personal protection see section 8. Smoking, eating and
drinking should be prohibited in the application area.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of
ignition. Earthing of containers and apparatuses is essential.
- Normal measures for preventive fire protection.
- Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a
cool, well-ventilated place. Keep container closed when not in
use. Keep away from sources of ignition - No smoking.
- Electrical installations / working materials must comply with
the technological safety standards.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

- Further information on storage conditions : Protect from humidity and water. Do not allow to dry.
- Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	2017-11-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900			
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	100 mg/m3	2009-02-16	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m3	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m3	2012-07-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

powder (stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	TWA	500 ppm 2 000 mg/m3	2007-01-01	
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	TWA	400 ppm 1 600 mg/m3	1989-01-19	
Solvent	64742-95-	TWA	500 ppm 2 000 mg/m3	2007-01-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

naphtha (petroleum), light arom.	6				
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m ³	2010-03-01	
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	400 ppm 1 600 mg/m ³	1989-01-19	

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Skin and body protection : Long sleeved clothing
Safety shoes
Choose body protection according to the amount and
concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration
requires.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water
courses or the soil.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid

Colour : silver

Odour : characteristic

pH : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Bulk density : No data available

Flammability (solid, gas) : Combustible Solids

Auto-flammability :

Auto-flammability not auto-flammable

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1,3 - 2,0 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive

9.2 Other information

Self-Accelerating decomposition temperature (SADT)	: No data available
Self-heating substances	: No data available
Heat of combustion	: No data available
Impact sensitivity	: No data available
Surface tension	: No data available
Conductivity	: No data available
Sublimation point	: No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Molecular weight : No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Hazardous decomposition : No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because
no mortality of rats was observed at the maximum achievable
concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Fatty acids, C14-18 and C16-18-unsatd. :

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 46 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:**

Solvent naphtha (petroleum), light arom. (64742-95-6) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**Additional ecological : No data available
information

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : In accordance with local and national regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

14.5 Environmental hazards**14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

STAPA SILTALLUX 8380 Aluminium Pigment Paste

Version 2.1

Revision Date 24.06.2020

Print Date 28.12.2020

SECTION 16: Other information**Full text of H-Statements**

H226	: Flammable liquid and vapour.
H227	: Combustible liquid.
H228	: Flammable solid.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H313	: May be harmful in contact with skin.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.