

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : STAPA ALUPOR N 913  
Material number : 022545PX0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guntersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Acute toxicity, Category 5, Oral, H303  
Skin corrosion/irritation, Category 3, H316

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA ALUPOR N 913

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

### GHS-Labeling

Signal word : Warning

Hazard statements : H303: May be harmful if swallowed.  
H316: Causes mild skin irritation.

Precautionary statements : **Response:**  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.

### Hazardous components which must be listed on the label

Identification	CAS-No.
2,2'-oxydiethanol	111-46-6

### Other hazards which do not result in classification

Combustible Solids

## SECTION 3: Composition/information on ingredients

Substance No. :

### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
2,2' -oxybisethanol	111-46-6 203-872-2	Acute Tox.;4;H302	25 - 50
dodecylbenzenesulphonic acid, compound with isopropylamine	26264-05-1 247-556-2	Skin Irrit.;2;H315 Eye Irrit.;2;H319	1 - 10

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

(1:1)			
Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters	97468-33-2	Skin Sens.;1B;H317 Aquatic Chronic;4;H413	0,1 - 0,25

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

This information is not available.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Use personal protective equipment.  
Avoid dust formation.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust  
formation. Ensure adequate ventilation.

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
2,2' - oxybisethanol	111-46-6	AGW	10 ppm 44 mg/m <sup>3</sup>	2008-06-01	DE TRGS 900
Peak-limit: excursion factor (category)		4;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2,2' -	111-46-6	AGW (Vapour)	10 ppm	2013-09-19	DE TRGS 900

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA ALUPOR N 913

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

oxybisethano 	and aerosols)	44 mg/m3		
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).Sum of vapor and aerosols.When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	



**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium powder	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

(stabilised)					
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m <sup>3</sup>	2017-10-02	
2,2' - oxybisethanol	111-46-6	TWA	10 mg/m <sup>3</sup>	2008-01-01	
stearic acid	57-11-4	TWA	10 mg/m <sup>3</sup>	2016-03-01	

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Long sleeved clothing  
 Safety shoes  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of dust or aerosol formation use respirator with an approved filter.  
 Dust safety masks are recommended when the dust concentration is more than 10 mg/m<sup>3</sup>.

**Environmental exposure controls**

- General advice :
- : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Water : The product should not be allowed to enter drains, water courses or the soil.
- :

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: not auto-flammable
Auto-flammability	not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.

No data available

**10.5 Incompatible materials**

Materials to avoid : Acids

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****2,2' -oxybisethanol :**

Acute oral toxicity : LD50 Humans: 1 120 mg/kg

Acute inhalation toxicity : Rat: > 4,6 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: 13 300 mg/kg

**dodecylbenzenesulphonic acid, compound with isopropylamine (1:1) :**

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

**Skin corrosion/irritation**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

---

**Product**

May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product**

Product dust may be irritating to eyes, skin and respiratory system.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

**Further information****Product**

No data available

**SECTION 12: Ecological information****12.1 Toxicity****Components:****Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters (97468-33-2) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects**



**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

**Product:**

Additional ecological information : No data available

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

**SECTION 14: Transport information****14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group****14.5 Environmental hazards****14.6 Special precautions for user**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA ALUPOR N 913

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

Not classified as dangerous in the meaning of transport regulations.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

### 15.2 Chemical safety assessment

No data available

## SECTION 16: Other information

### Full text of H-Statements

H228 : Flammable solid.  
H302 : Harmful if swallowed.  
H303 : May be harmful if swallowed.  
H315 : Causes skin irritation.  
H316 : Causes mild skin irritation.  
H317 : May cause an allergic skin reaction.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA ALUPOR N 913**

Version 3.0

Revision Date 10.12.2019

Print Date 18.02.2022

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.