

**STAPA BG HYDROLAN 2154 Aluminium Paste**

Version            Revision Date:            SDS Number:            Date of last issue: -  
2.0                12/02/2019              102000000187        Date of first issue: 03/21/2018

---

**SECTION 1. IDENTIFICATION**

Product name                : STAPA BG HYDROLAN 2154 Aluminium Paste  
Product code                : 007497GD0

**Manufacturer or supplier's details**

Company name of supplier   :  
Address                        :

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Acute toxicity (Oral)        : Category 4  
Acute toxicity (Inhalation) : Category 4  
Skin irritation                : Category 2  
Eye irritation                : Category 2A

**GHS label elements**

Hazard pictograms        :



Signal word                : Warning

Hazard statements        : H302 + H332 Harmful if swallowed or if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements :

**Prevention:**

P261                        Avoid breathing dust/ fume/ gas/ mist/  
vapours/ spray.  
P264                        Wash skin thoroughly after handling.  
P270                        Do not eat, drink or smoke when using this  
product.  
P271                        Use only outdoors or in a well-ventilated area.  
P280                        Wear protective gloves/ eye protection/ face

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Ethanol, 2-butoxy-

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 - < 70
Ethanol, 2-butoxy-	111-76-2	>= 30 - < 50
Silica	7631-86-9	>= 1 - < 5

---

**SECTION 4. FIRST AID MEASURES**

General advice : Move the victim to fresh air.  
Do not leave the victim unattended.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
  
If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry sand  
Special powder against metal fire
- Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Use personal protective equipment.  
  
Wear self-contained breathing apparatus for firefighting if necessary.

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Use personal protective equipment.  
Avoid dust formation.
- Environmental precautions :  
  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Earthing of containers and apparatuses is essential.  
  
Avoid dust formation.
- Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.  
  
Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

Keep container closed when not in use.  
Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

- Technical measures/Precautions : Protect from humidity and water.  
Do not allow to dry.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.  
Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-3
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version 2.0      Revision Date: 12/02/2019      SDS Number: 102000000187      Date of last issue: -  
 Date of first issue: 03/21/2018

		TWA	5 mg/m3 (Aluminium)	NIOSH REL
		TWA (Total)	15 mg/m3 (Aluminium)	OSHA P0
		TWA (Respirable fraction)	5 mg/m3 (Aluminium)	OSHA P0
		TWA (total dust)	15 mg/m3 (Aluminium)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminium)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminium)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminium)	OSHA P0
		TWA (welding fumes)	5 mg/m3 (Aluminium)	NIOSH REL
		TWA (pyro powders)	5 mg/m3 (Aluminium)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
		TWA (Fumes)	5 mg/m3	OSHA P0
Ethanol, 2-butoxy-	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
Silica	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version 2.0      Revision Date: 12/02/2019      SDS Number: 102000000187      Date of last issue: -  
 Date of first issue: 03/21/2018

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Ethanol, 2-butoxy-	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

**Personal protective equipment**

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Hand protection  
Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**STAPA BG HYDROLAN 2154 Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 171 °C
Flash point	: 65 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: not auto-flammable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Solubility(ies)	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Explosive properties	: Not explosive

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.

---



## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

Conditions to avoid : Do not allow to dry.  
No data available

Incompatible materials : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if swallowed or if inhaled.

**Components:****Ethanol, 2-butoxy-:**

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg  
Method: Converted acute toxicity point estimate

Acute inhalation toxicity : > 3.1 mg/l  
Exposure time: 1 h  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

**Silica:**

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg  
(Mouse): 15,000 mg/kg

Acute inhalation toxicity : (Rat): 0.139 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**STAPA BG HYDROLAN 2154 Aluminium Paste**

Version      Revision Date:      SDS Number:      Date of last issue: -  
2.0          12/02/2019          102000000187      Date of first issue: 03/21/2018

---

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Components:****Silica:**

Remarks: No data available

**STAPA BG HYDROLAN 2154 Aluminium Paste**

Version            Revision Date:            SDS Number:            Date of last issue: -  
2.0                12/02/2019                102000000187            Date of first issue: 03/21/2018

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Silica:**

Toxicity to daphnia and other : (Daphnia (water flea)): 7,600 mg/l  
aquatic invertebrates

Toxicity to algae                                : (Chlorella pyrenoidosa (algae)): 440 mg/l

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

**Components:****Silica:**

Additional ecological                                : No data available  
information

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues                                : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging                                : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****National Regulations**

**49 CFR**    : Not classified as dangerous in the meaning of transport

---

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

regulations.

### International Regulations

**Remarks** : Not classified as dangerous in the meaning of transport regulations.

**ADR** : Not classified as dangerous in the meaning of transport regulations.

**IATA-DGR** : Not classified as dangerous in the meaning of transport regulations.

**IMDG-Code** : Not classified as dangerous in the meaning of transport regulations.

Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	>= 50 - < 70 %
Ethanol, 2-butoxy-	111-76-2	>= 30 - < 50 %

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Ethanol, 2-butoxy-	111-76-2	40 %
--------------------	----------	------

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### US State Regulations

#### Massachusetts Right To Know

Aluminum	7429-90-5
Ethanol, 2-butoxy-	111-76-2
Silica	7631-86-9
Fatty acids, C14-18 and C16-18-unsatd.	67701-06-8

#### Pennsylvania Right To Know

Aluminum	7429-90-5
Ethanol, 2-butoxy-	111-76-2
Silica	7631-86-9

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.



**WARNING:** This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Aluminum	7429-90-5
----------	-----------

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

Ethanol, 2-butoxy-	111-76-2
--------------------	----------

Silica	7631-86-9
--------	-----------

### California Permissible Exposure Limits for Chemical Contaminants

Aluminum	7429-90-5
----------	-----------

Ethanol, 2-butoxy-	111-76-2
--------------------	----------

Silica	7631-86-9
--------	-----------

### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

## STAPA BG HYDROLAN 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	12/02/2019	102000000187	Date of first issue: 03/21/2018

---

OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/02/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN