

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Agent Alu matt 180 kgs  
Product code : 08836025V

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
  
Telephone : +499152770  
  
Telefax : +499152777008  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version	Revision Date:	SDS Number:	Print Date:
7.1	08.01.2020	102000005086	03.03.2022
			Date of first issue: 30.01.2014

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

acetone

xylene

n-butyl acetate

ethyl acetate

Solvent naphtha (petroleum), light arom.

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

### Additional Labelling

EUH208 Contains n-butyl acrylate. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
acetone	67-64-1 200-662-2 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 20 - < 25
xylene	1330-20-7 215-535-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
ethyl acetate	141-78-6 205-500-4 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2.5 - < 10
aluminium powder (stabilised)	7429-90-5 231-072-3  01-2119529243-45	Flam. Sol. 1; H228	>= 1 - < 10
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2.5 - < 10
zinc oxide	1314-13-2	Aquatic Acute 1;	>= 1 - < 2.5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

	215-222-5 01-2119463881-32	H400 Aquatic Chronic 1; H410	
zinc 5-nitroisophthalate	60580-61-2 262-309-9	Aquatic Chronic 3; H412	$\geq 1 - < 2.5$
n-butyl acrylate	141-32-2 205-480-7	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	$\geq 0.1 - < 0.25$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version	Revision Date:	SDS Number:	Print Date: 03.03.2022
7.1	08.01.2020	102000005086	Date of first issue: 30.01.2014

---

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC
Further information	Indicative			
		TWA	500 ppm 1,210 mg/m <sup>3</sup>	GB EH40
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			
aluminium powder	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

(stabilised)				
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance			



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

	hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
n-butyl acrylate	141-32-2	TWA	2 ppm 11 mg/m <sup>3</sup>	2000/39/EC
Further information	Indicative			
		STEL	10 ppm 53 mg/m <sup>3</sup>	2000/39/EC
Further information	Indicative			
		TWA	1 ppm 5 mg/m <sup>3</sup>	GB EH40
		STEL	5 ppm 26 mg/m <sup>3</sup>	GB EH40

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
acetone	Workers	Skin contact	Long-term systemic effects	186 mg/kg
	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg
	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

xylene	Consumers	Inhalation	Long-term local effects	65.3 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg
	Consumers	Ingestion	Long-term systemic effects	12.5 mg/kg
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg
ethyl acetate	Workers	Inhalation	Acute local effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	734 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Long-term systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	367 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg
	Consumers	Inhalation	Long-term systemic effects	367 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	4.5 mg/kg
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	25 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
naphtha (petroleum), hydrodesulphurized heavy; Low boiling	Workers	Skin contact	Long-term systemic effects	47 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

point hydrogen treated naphtha				
	Workers	Inhalation	Long-term systemic effects	330 mg/m3
	Consumers	Ingestion	Long-term systemic effects	28 mg/kg
	Consumers	Skin contact	Long-term systemic effects	28 mg/kg
	Consumers	Inhalation	Long-term systemic effects	71 mg/m3
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Ingestion	Long-term systemic effects	300 mg/kg
	Consumers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.83 mg/kg
	Workers	Inhalation	Long-term local effects	0.5 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
acetone	Soil	29.5 mg/kg
	Fresh water	10.6 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine water	1.06 mg/l
	Marine sediment	3.04 mg/kg
	STP	100 mg/l
	xylene	Fresh water
Marine water		0.01 mg/l
Fresh water sediment		13.7 mg/l
Marine sediment		1.37 mg/l
Soil		2.68 mg/l
Secondary Poisoning		20 mg/kg
STP		9.6 mg/l
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	STP	35.6 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.098 mg/kg
	Soil	0.090 mg/kg
ethyl acetate	Soil	0.148 mg/kg
	STP	650 mg/l
	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
zinc oxide	Fresh water	0.0206 mg/l
	Marine water	0.0061 mg/l
	Fresh water sediment	117.8 mg/kg
	Marine sediment	56.5 mg/kg
	Soil	35.6 mg/kg
	STP	0.1 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Tightly fitting safety goggles

Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : No data available

Odour Threshold : No data available

pH : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

Freezing point : No data available  
: 55 °C

Flash point : -19 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.9 g/cm<sup>3</sup>

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : 13 - 15 s at 20 °C  
Cross section: 4 mm

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

Method: DIN 53211

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

### **Components:**

#### **acetone:**

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg  
(Mouse): 3,000 mg/kg  
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

#### **xylene:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

#### **ethyl acetate:**

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

#### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

#### **aluminium powder (stabilised):**

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

#### **n-butyl acrylate:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks: May cause skin irritation in susceptible persons.

#### **Components:**

##### **acetone:**

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

##### **xylene:**

Result: Skin irritation

##### **n-butyl acrylate:**

Result: Skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Remarks: Eye irritation

#### **Components:**

##### **acetone:**

Remarks: Severe eye irritation

##### **xylene:**

Result: Eye irritation

##### **n-butyl acrylate:**

Result: Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

### Components:

#### **n-butyl acrylate:**

Result: May cause sensitisation by skin contact.

#### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Carcinogenicity**

Not classified based on available information.

### Components:

#### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

### Components:

#### **xylene:**

Assessment: May cause respiratory irritation.

#### **n-butyl acetate:**

Assessment: May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

#### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

Assessment: May cause drowsiness or dizziness.

#### **n-butyl acrylate:**

Assessment: May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Components:**

##### **xylene:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

##### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

Assessment: Causes damage to organs through prolonged or repeated exposure.

##### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Components:**

##### **xylene:**

May be fatal if swallowed and enters airways.

##### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

##### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

#### **Components:**

##### **zinc oxide:**

Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **acetone:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

##### **ethyl acetate:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

##### **Solvent naphtha (petroleum), light arom.:**

##### **Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

##### **naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha:**

##### **Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

##### **n-butyl acrylate:**

##### **Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

##### Components:

##### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version  
7.1

Revision Date:  
08.01.2020

SDS Number:  
102000005086

Print Date: 03.03.2022  
Date of first issue: 30.01.2014

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

#### Components:

##### **zinc oxide:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADR : PAINT

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

**IMDG** : PAINT

**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADR** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### **ADR**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

#### **IMDG**

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Class 3 - Flammable liquids

### 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : no

#### **IMDG**

Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version	Revision Date:	SDS Number:	Print Date: 03.03.2022
7.1	08.01.2020	102000005086	Date of first issue: 30.01.2014

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 75.04 %, 675.33 g/l

#### 15.2 Chemical safety assessment

### SECTION 16: Other information

#### Full text of H-Statements

- H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H228 : Flammable solid.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H372 : Causes damage to organs through prolonged or repeated exposure.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

- Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version 7.1      Revision Date: 08.01.2020      SDS Number: 102000005086      Print Date: 03.03.2022  
Date of first issue: 30.01.2014

---

Flam. Sol. : Flammable solids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2017/164/EU / STEL : Short term exposure limit  
2017/164/EU / TWA : Limit Value - eight hours  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Agent Alu matt 180 kgs

Version	Revision Date:	SDS Number:	Print Date: 03.03.2022
7.1	08.01.2020	102000005086	Date of first issue: 30.01.2014

---

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN