

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA SILTASTAR 615 Aluminium PIGMENT PASTE

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STAPA SILTASTAR 615 Aluminium PIGMENT PASTE  
Material number : 023492G70

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

### SECTION 2: Hazards identification

#### GHS Classification

: Skin corrosion/irritation, Category 2, H315  
Specific target organ toxicity - single exposure, Category 3,  
Central nervous system, H336

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA SILTASTAR 615 Aluminium PIGMENT PASTE

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

Long-term (chronic) aquatic hazard, Category 3, H412

### GHS-Labeling

Symbol(s)

:



Signal word

:

Warning

Hazard statements

:

H315: Causes skin irritation.  
 H336: May cause drowsiness or dizziness.  
 H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

:

**Prevention:**  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
**Response:**  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label

Identification	CAS-No.
Distillates (petroleum), hydrotreated light	64742-47-8
Solvent naphtha (petroleum), light arom.	64742-95-6

### Other hazards which do not result in classification

Combustible Solids

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA SILTASTAR 615 Aluminium PIGMENT PASTE

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

### SECTION 3: Composition/information on ingredients

Substance name : Versuch 83002237 STAPA ZP 11072

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
Distillates (petroleum), hydro-treated light; Kerosine — unspecified	64742-47-8 265-149-8	Flam. Liq.;4;H227 ;2;H315 STOT SE;3;H336 Asp. Tox.;1;H304 Aquatic Acute;3;H402 Aquatic Chronic;3;H412	10 - 20
Solvent naphtha (petroleum), light arom.	64742-95-6	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	2,5 - 10
1,2,4-trimethylbenzene	95-63-6 202-436-9	Flam. Liq.;3;H226 Skin Irrit.;2;H315 Eye Irrit.;2A;H319 Acute Tox.;4;H332 STOT SE;3;H335	1 - 2,5

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

		Aquatic Chronic;2;H411	
--	--	---------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Use personal protective equipment.  
Avoid dust formation.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust  
formation. Ensure adequate ventilation.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.


Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Page 7 / 21	102000028580	A member of  <b>ALтана</b>
-------------	--------------	---

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**United States of America (USA):**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
aluminium powder	7429-90-5	TWA (Respirable fraction)	1 mg/m <sup>3</sup>	2008-01-01	



**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

(stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m <sup>3</sup>	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m <sup>3</sup>	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium	7429-90-5	PEL (Pyro)	5 mg/m <sup>3</sup>	2017-10-02	

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

powder (stabilised)		powders)			
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA	500 ppm 2 000 mg/m <sup>3</sup>	2007-01-01	
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA	200 mg/m <sup>3</sup>	2010-03-01	
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA	400 ppm 1 600 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA (Mist)	5 mg/m <sup>3</sup>	2011-07-01	
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA (Mist)	5 mg/m <sup>3</sup>	1989-01-19	
Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47- 8	TWA (Mist)	5 mg/m <sup>3</sup>	2013-10-08	
Distillates	64742-47-	ST (Mist)	10 mg/m <sup>3</sup>	2013-10-08	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA SILTASTAR 615 Aluminium PIGMENT PASTE


Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

(petroleum), hydro-treated light; Kerosine — unspecified	8				
Distillates (petroleum), hydro-treated light; Kerosine — unspecified	64742-47-8	PEL (particulate)	5 mg/m <sup>3</sup>	2014-11-26	
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2 000 mg/m <sup>3</sup>	2007-01-01	
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m <sup>3</sup>	2010-03-01	
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	400 ppm 1 600 mg/m <sup>3</sup>	1989-01-19	
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	2013-10-08	
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm	2014-03-01	
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	1989-01-19	
1,2,4-trimethylbenzene	95-63-6	PEL	25 ppm 125 mg/m <sup>3</sup>	2014-11-26	

### 8.2 Exposure controls

Page 11 / 21	102000028580	A member of 
--------------	--------------	---

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

**Personal protective equipment**

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of dust or aerosol formation use respirator with an approved filter.

**Environmental exposure controls**

- General advice :
- : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Water : The product should not be allowed to enter drains, water courses or the soil.
- :

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- Appearance : Pasty solid
- Colour : silver
- Odour : characteristic
- pH : No data available
- Freezing point : No data available
- Boiling point/boiling range : No data available

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Water solubility	: No data available
Miscibility with water	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

---

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.

No data available

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

**Components:****Solvent naphtha (petroleum), light arom. :**

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: &gt; 3 160 mg/kg

**1,2,4-trimethylbenzene :**

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

Product dust may be irritating to eyes, skin and respiratory system.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available



**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,  
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may  
degrease the skin.

**SECTION 12: Ecological information****12.1 Toxicity****Components:****Distillates (petroleum), hydrotreated light (64742-47-8) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

**Solvent naphtha (petroleum), light arom. (64742-95-6) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**1,2,4-trimethylbenzene (95-63-6) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA SILTASTAR 615 Aluminium PIGMENT PASTE

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

---

### SECTION 14: Transport information

#### 14.1 UN number

#### 14.2 Proper shipping name

#### 14.3 Transport hazard class

#### 14.4 Packing group

#### 14.5 Environmental hazards

#### 14.6 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H226 : Flammable liquid and vapour.  
H227 : Combustible liquid.  
H228 : Flammable solid.  
H303 : May be harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H313 : May be harmful in contact with skin.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA SILTASTAR 615 Aluminium PIGMENT PASTE**

Version 1.0

Revision Date 16.12.2019

Print Date 06.08.2020

- H336 : May cause drowsiness or dizziness.
- H402 : Harmful to aquatic life.
- H411 : Toxic to aquatic life with long lasting effects.
- H412 : Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.