

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PLATINSTAR FPG GX-72900 Silver
Product code : 022412FY0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

ethyl acetate
propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version
3.0

Revision Date:
25.01.2023

SDS Number:
102000024701

Print Date: 16.04.2024
Date of first issue: 02.06.2016

	607-022-00-5 01-2119475103-46	(Central nervous system) EUH066	
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 25 - < 50
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 1 - < 10
butyl lactate	34451-19-9 205-316-4	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
ABC powder
Foam

Unsuitable extinguishing media : High volume water jet
Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Earthing of containers and apparatuses is essential. Reaction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

areas and containers with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	GB EH40
		STEL	400 ppm 1,468 mg/m ³	GB EH40
		STEL	400 ppm 1,468 mg/m ³	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU
	Further information: Indicative			
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m ³	GB EH40
		STEL	500 ppm 1,250 mg/m ³	GB EH40
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
 Date of first issue: 02.06.2016

		TWA (Respirable fraction)	4 mg/m ³	GB EH40
		TWA (inhalable dust)	10 mg/m ³	GB EH40
<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>				
		TWA (Respirable dust)	4 mg/m ³	GB EH40
<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version
3.0

Revision Date:
25.01.2023

SDS Number:
102000024701

Print Date: 16.04.2024
Date of first issue: 02.06.2016

butyl lactate	34451-19-9	TWA	5 ppm 30 mg/m ³	GB EH40
Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m ³
	Workers	Inhalation	Long-term local effects	734 mg/m ³
	Workers	Inhalation	Acute systemic effects	1468 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Acute local effects	1468 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	367 mg/m ³
	Consumers	Inhalation	Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic effects	734 mg/m ³
	Consumers	Inhalation	Acute local effects	734 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg
propan-2-ol	Workers	Skin contact	Long-term local effects	63 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4.5 mg/kg
	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic effects	500 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg
	Consumers	Skin contact	Long-term systemic effects	319 mg/kg
aluminium powder (stabilised)	Consumers	Inhalation	Long-term systemic effects	89 mg/m ³
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m ³
	Workers	Inhalation	Long-term local effects	3.72 mg/m ³
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

	STP	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l
propan-2-ol	Soil	28 mg/kg
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140.9 mg/l
	Marine sediment	552 mg/kg
	STP	2251 mg/l
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : silver

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

Odour	:	characteristic
Odour Threshold	:	No data available
Freezing point	:	No data available
Boiling point/boiling range	:	76 °C
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	-4 °C
Auto-ignition temperature	:	Not relevant
Decomposition temperature	:	No data available
pH	:	6 - 8 Concentration: 100 %
Viscosity, kinematic	:	No data available
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	No data available
Relative vapour density	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

butyl lactate:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Eye irritation

Components:

ethyl acetate:

Result : Eye irritation

propan-2-ol:

Result : Eye irritation

butyl lactate:

Result : Eye irritation

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

Components:

butyl lactate:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1210

IMDG : UN 1210

IATA : UN 1210

14.2 UN proper shipping name

ADR : PRINTING INK

IMDG : PRINTING INK

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version 3.0 Revision Date: 25.01.2023 SDS Number: 102000024701 Print Date: 16.04.2024
Date of first issue: 02.06.2016

IATA : Printing ink

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)
Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : 3

IATA (Passenger)
Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : 3

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 ethyl acetate (Number on list 3) propan-2-ol (Number on list 3) aluminium powder (stabilised) (Number on list 40) butyl lactate (Number on list 3) Phosphoric acid polyester (72243-070628, Germany) (Number on list 3)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H228	:	Flammable solid.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version	Revision Date:	SDS Number:	Print Date: 16.04.2024
3.0	25.01.2023	102000024701	Date of first issue: 02.06.2016

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



PLATINSTAR FPG GX-72900 Silver

Version
3.0

Revision Date:
25.01.2023

SDS Number:
102000024701

Print Date: 16.04.2024
Date of first issue: 02.06.2016
