

**Date of impression** 09.04.2024/14:10:18  
**page/of** 1/1

**edition** 09.01.2024

**material denomination** **STANDART PCBF 5000**  
**material-no.** 023570E30  
**material description** \*Pigment preparation containing less than 50% silica-encapsulated aluminum pigment and more than 50% carboxylated super durable polyester with an acid value of 25.

**material specification**

<b>insp. characteristic</b>	<b>specification</b>	<b>unit</b>
TI00018 bulk density	0,20 - 0,50	g/cm3
TI00147 Aluminium content	39,0 - 49,0	%
TI00283 powder coating application	pass	
TI00288 D 10	19,0 - 26,0	µm
TI00288 D 50	45,0 - 55,0	µm
TI00288 D 90	74,0 - 82,0	µm
TI00484 Binder content		%

total shelf life in month: 24

EC-safety data sheet-no. 023570E30

The Data on this technical information sheet correspond with the current status of our knowledge and experience.  
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.  
 We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
09.01.2024	09.01.2024	09.01.2024

This document has been printed automatically and will not be signed.