

| | | Date of impression page/of | 09.04.2024/14:07:57 1/1 |
|---------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------|----------------------------|
| | | edition | 09.01.2024 |
| material denomination material-no. material description | STANDART PCUplus 800 Alum 023670EL0 Lamellar, doubleencapsulated (Sol-Gel & Polymer) nor | | er |

aluminumpigment powder for powder coatings.

material specification

| insp. characteristic | specification | unit |
|------------------------------------|---------------|-------|
| TI00005 sieving < 45 μm | 99,5 - 100,0 | % |
| TI00018 bulk density | 0,05 - 0,25 | g/cm3 |
| TI00283 powder coating application | pass | |
| TI00288 D 10 | 2,0 - 6,0 | μm |
| TI00288 D 50 | 5,0 - 11,0 | μm |
| TI00288 D 90 | 11,0 - 19,0 | μm |

total shelf life in month: 36

EC-safety data sheet-no. 023670EL0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.

The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

| Draft | Approval | Release |
|--------------------|------------|-----------------|
| Technical services | Production | Quality control |
| 09.01.2024 | 09.01.2024 | 09.01.2024 |

This document has been printed automatically and will not be signed.